



لیست قیمت محصولات داهوا

dahua
TECHNOLOGY

۰۲۱-۹۱۰۰۶۰۰۸
WWW.ATINEH.COM

۲۸ ماه گارانتی
مادطلبی
مرکز جامع ارائه خدمات و گارانتی

	MODEL	PRICE
1	DH-HAC-HFW1500RP-Z-IRE6-A · Max. 20fps@5MP(2592×1944), 1/2.7"Progressive CMOS · 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P· HD and SD · output switchable· Built-in mic· 2.7-12mm motorized lens IP67, DC12V · Max. IR length 60m, Smart IR	49,450,000

2	DH-HAC-HFW1500DP	5MP Starlight HDCVI IR Bullet Camera> Max 25 fps@5MP (16:9 video output)> CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed <lens (6 mm, 8 mm optional) > Max. IR length 80 m, Smart IR IP67, DC12V	33,012,000
3	DH-HAC-HFW1500SLP	.Progressive CMOS· HD and SD output switchable"1/2.7 . Day/Nigh (ICR),BLC / HLC / DWDR / AGC· 3.6mm fixed lens ,(2.8mm, 6mm optional)· Max. IR length 30m, Smart IR· IP67 DC12. 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P	30,520,000
4	DH-HAC-HFW1500THP-I8	5MP HDCVI IR Bullet Camera· Max. 20fps@5MP· HD and SD . ·output switchable· 3.6mm fixed lens (6mm, 8mm optional) Max. IR length 80m, Smart IR · IP67, DC12V	33,421,500
5	DH-HAC-HFW1500TP-A	5MP Starlight HDCVI IR Bullet Camera > Max 25fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed ,lens (2.8 mm optional) > Built-in mic(-A)> Max. IR length 30 m Smart IR> IP67, DC12V	27,400,000
6	DH-HAC-HFW2249TP-I8-A	2MP Full-color Starlight HDCVI Bullet Camera · Full-color ·starlight· 120dB true WDR, 3DNR· 40m(131ft) LED distance Max. 30fps@1080P· HD/SD output switchable· Audio in ,interface, built-in mic· 3.6mm fixed lens (6mm optional)· IP67 DC12V±30%	56,340,000
7	DH-HAC-HFW1231TMP-I8-A	<2MP Starlight HDCVI IR Bullet Camera> Max 30 fps@1080p ,Starlight, 130 dB true WDR, 3D NR> 3.6 mm fixed lens (2.8 mm mm, 8 mm optional) > CVI/CVBS/AHD/TVI switchable> Super 6 Adapt> Built-in mic> Max. IR length 80 m, Smart IR> IP67, DC V 12	31,020,000
8	DH-HAC-HFW1231CMP	<2MP Starlight HDCVI IR Bullet Camera > Max 30 fps@1080P Starlight, 130 dB true WDR, 3D NR> 3.6 mm fixed lens (2.8 mm .optional) > CVI/CVBS/AHD/TVI switchable> Super Adapt> Max IR length 30 m, Smart IR> IP67, DC12V	28,182,000

9	DH-HAC-HFW1239TP-A-LED	·Full-color starlight· 20m LED distance· Max. 30fps@1080P · CVI/CVBS/AHD/TVI Switchable· Built-in mic· 3.6mm fixed lens (2.8mm Optional) · IP67, DC12V±30% DC	27,470,000
10	DH-HAC-HFW1239TP-LED	·Full-color starlight· 20m LED distance· Max. 30fps@1080P · CVI/CVBS/AHD/TVI Switchable· 3.6mm fixed lens (2.8mm Optional) · IP67, DC12V±30% DC	26,840,000
11	DH-HAC-HFW1209CMP-LED	2MP Full-color HDCVI Bullet Camera> 24/7 color imaging> 20 m illumination distance> Max. 30 fps @ 1080p> Built-in mic A)> CVI / CVBS / AHD / TVI switchable> Fixed lens (2.8 mm; 3.6 mm optional) > IP67, 12V ± 30% DC	20,130,000
12	DH-HAC-HFW1200CMP	@ MP HDCVI Bullet Camera with IR Illumination> Up to 30fps 2 1080P> Switchable CVI / CVBS / AHD / TVI outputs> Fixed lens 3.6mm (2.8mm optional)> Built-in microphone (-A)> Max. IR illumination range 30m, Intelligent IR illumination > IP67, DC 12V	17,450,000
13	DH-HAC-HFW1209CP-LED	·Full-color starlight· 20 m illumination distance· Max · 30fps@1080P· CVI/CVBS/AHD/TVI switchable· Fixed lens (2.8 mm;3.6 mm optional) · IP67, 12V±30% DC	16,720,000
14	DH-HAC-HFW1200RP-Z-IRE6	Max 30fps@1080P(1920×1080)· HD and SD output · ,switchable· 2.7-12mm Motorized lens· Max. IR length 60m Smart IR · IP67, DC12V	36,620,000
15	DH-HAC-HFW1230DP	·Starlight· Max. 30fps@1080P· HD and SD output switchable · ,3.6mm fixed lens (6mm, 8mm optional) · Max. IR length 80m Smart IR· IP67, DC12V	25,870,000

16	DH-HAC-HFW1200DP	Max 30fps@1080P(1920×1080)· HD and SD output · switchable· 3.6mm fixed lens (6mm, 8mm optional)· Max. IR length 80m, Smart IR · IP67, DC12V	21,574,800
17	DH-HAC-HFW1200TP-A	,2Megapixel CMOS. 25/30fps@1080P "1/2.7 . 25/30/50/60fps@720P. 3.6mm fixed lens. Built-in mic. HD and ,SD output switchable. DWRD, Day/Night(ICR), AWB, AGC ,BLC,HLC, 2DNR ,OSD . Max. IR length 30m, Smart IR. IP67 DC12V	19,120,000
18	DH-HAC-HFW1200TP	2MP HDCVI IR Bullet Camera· Max 30fps@1080P· HD and SD . ·output switchable· 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 30m, Smart IR · IP67, DC12V	16,800,000
19	DH-HAC-HFW1200THP-I8	2MP HDCVI IR Bullet Camera· Max 30fps@1080P· HD and SD . ·output switchable· 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 80m, Smart IR · IP67, DC12V	22,814,000
20	DH-HAC-HFW1230THP-I8	2MP Starlight HDCVI IR Bullet Camera· Max. 30fps@1080P· HD and SD output switchable· 3.6mm fixed lens (6mm, 8mm optional) · Max. IR length 80m, Smart IR· IP67, DC12V	23,200,000
21	DH-HAC-HFW1230TP	.2MP Starlight HDCVI IR Bullet Camera· Max. 30fps@1080P . Starlight· HD and SD output switchable· 3.6mm fixed lens ,(2.8mm, 6mm optional)· Max. IR length 30m, Smart IR · IP67 DC12V	25,620,000
22	DH-HAC-HFW1230TLP	·2MP Starlight HDCVI IR Bullet Camera· Max. 30fps@1080P . HD and SD output switchable· 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 40m, Smart IR · IP67, DC12V	21,960,000

23	DH-HAC-HFW1200SP	Max 30fps@1080P(1920×1080). 2MP HDCVI IR Bullet Camera· HD and SD output switchable· 3.6mm fixed lens ,(2.8mm, 6mm optional)· Max. IR length 30m, Smart IR · IP67 DC12V	18,280,000
24	DH-HAC-HFW1200TLP-A	Max 30fps@1080P> HD and SD output switchable> 3.6mm < fixed lens (2.8mm, 6mm optional) > Built-in mic> Max. IR length 80m, Smart IR> IP67, DC12V	19,110,000
25	DH-HAC-HFW1200TLP	Max 30fps@1080P· HD and SD output switchable· 3.6mm · fixed lens (2.8mm, 6mm optional)· Max. IR length 40m, Smart IR · IP67, DC12V	16,620,000
26	DH-HAC-HFW1200RP	2MP HDCVI IR Bullet Camera· Max . ·30fps@1080P(1920×1080)· HD and SD output switchable ,3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 20m Smart IR · IP67, DC12V	14,020,000
27	DH-HAC-HDW1500TP-Z-A	. Max. 20fps@5MP(2592×1944). 1/2.7"Progressive CMOS · 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P· HD and SD · output switchable· Built-in mic· 2.7-12mm motorized lens IP67, DC12V· Max. IR length 60m, Smart IR	48,230,000
28	DH-HAC-HDW1509TLQP-A-LED	5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output)> 120dB true WDR, 3D NR> 24/7 color imaging> 20 m illumination distance> CVI/CVBS/AHD/TVI switchable> Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional)> IP67, 12 V DC> Quick-to-install eyeball saves installation time	38,000,000
29	DH-HAC-HDW1509TLP-A-LED	5MP Full-color Starlight HDCVI Eyeball Camera · Full-color ·starlight· 20 m LED distance· Max. 20fps@5MP CVI/CVBS/AHD/TVI switchable· Built-in mic (-A)· 3.6 mm fixed lens (2.8 mm optional)· IP67, 12V±30% DC	33,900,000

30	DH-HAC-HDW1500TMQP-A	< 5MP Starlight HDCVI POC IR Quick-to-install Eyeball Camera Max 25 fps@5MP (16:9 video output)> CVI/CVBS/AHD/TVI <switchable> Quick-to-install eyeball saves installation time .mm fixed lens (2.8 mm, 6 mm optional)> Bulit-in mic> Max 3.6 IR length 60 m, Smart IR> IP67, PoC (only CVI)/12V±30% DC	31,000,000
31	DH-HAC-HDW1500TLMQP	< 5MP Starlight HDCVI POC IR Quick-to-install Eyeball Camera Max 25 fps@5MP (16:9 video output)> CVI/CVBS/AHD/TVI <switchable> Quick-to-install eyeball saves installation time mm fixed lens (2.8 mm, 6 mm optional)> Max. IR length 60 3.6 m, Smart IR> IP67, PoC (only CVI)/12V±30% DC	26,901,000
32	DH-HAC-HDW1500EMP-A	Max. 20fps@5MP(2592×1944)· Built-in mic · IP67, DC12V· HD · and SD output switchable· 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR	34,180,000
33	DH-HAC-HDW1231TQP-A	2MP Starlight HDCVI Quick-to-install IR Eyeball Camera > Max fps@1080P> Starlight, 130 dB true WDR, 3D NR> 3.6 mm 30 fixed lens (2.8 mm, 6 mm optional)> CVI/CVBS/AHD/TVI ,switchable> Super Adapt> Built-in mic> Max. IR length 40 m Smart IR> IP67, DC12V> Quick-to-install saves installation time	29,678,000
34	DH-HAC-HDW1239TP-A-LED	·Full-color starlight· 40m LED distance· Max. 30fps@1080P · CVI/CVBS/AHD/TVI switchable· Built-in mic· 3.6mm fixed lens (2.8mm Optional) · IP67, 12V±30% DC	30,520,000
35	DH-HAC-HDW1239TP-LED	·Full-color starlight· 40m LED distance· Max. 30fps@1080P · CVI/CVBS/AHD/TVI switchable· 3.6mm fixed lens (2.8mm Optional) · IP67, 12V±30% DC	29,050,000
36	DH-HAC-HDW1230EMP-A	·2MP Starlight HDCVI IR Eyeball Camera· Max. 30fps@1080P · HD and SD output switchable· Built-in mic· 3.6mm fixed lens ,(2.8mm, 6mm optional) · Max. IR length 50m, Smart IR· IP67 DC12V	23,810,000

37	DH-HAC-HDW1230TLP-A	·2MP Starlight HDCVI IR Eyeball Camera· Max. 30fps@1080P . HD and SD output switchable· 3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 40m, Smart IR · IP67, DC12V, Built in Mic	26,840,000
38	DH-HAC-HDW1209TLQP-A-LED	2MP Full-color Starlight HDCVI Eyeball Camera > Full-color <starlight> 20 m illumination distance> Max. 30fps @ 1080P CVI / CVBS / AHD / TVI switchable> Fixed lens (2.8 mm; 3.6 mm optional)> IP67, 12V ± 30% DC	17,314,000
39	DH-HAC-HDW1209TLQP-LED	2MP Full-color Starlight HDCVI Eyeball Camera . Full-color . starlight. 20 m illumination distance. Max. 30fps @ 1080P. CVI CVBS / AHD / TVI switchable. Fixed lens (2.8 mm; 3.6 mm / optional). IP67, 12V ± 30% DC	16,642,000
40	DH-HAC-ME1200EQP-L	2MP HDCVI Active Deterrence Camera. * The parameters and datasheets below can only be applied to 1200-S5 series. . Max fps@1080p, CVI/CVBS/AHD/TVI switchable. Active 30 deterrence with warm light. Built-in PIR, 10 m/110°detecting range/angle. Quick-to-install eyeball save installation time. 3.6 mm fixed lens (2.8 mm optional). Max. IR length 30 m, Smart	21,608,500
41	DH-HAC-HDW1200EMP-A	2MP HDCVI IR Eyeball Camera· Max . ·30fps@1080P(1920×1080)· HD and SD output switchable ,3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 50m Smart IR · IP67, DC12V. Built in mic	18,891,800
42	DH-HAC-HDBW1200EP	,2MP HDCVI IR Dome Camera· Max 30fps@1080P · IP67, IK10 . DC12V · HD and SD output switchable· 3.6mm fixed lens (2.8mm optional)· Max. IR length 30m, Smart IR	21,340,000
43	DH-HAC-HDW1200MP	2MP HDCVI IR Eyeball Camera· Max . ·30fps@1080P(1920×1080)· HD and SD output switchable ,3.6mm fixed lens (2.8mm, 6mm optional)· Max. IR length 30m Smart IR · IP67, DC12V	15,648,400

44	DH-HAC-HDW1200RP	2MP HDCVI IR Eyeball Camera- Max . ·30fps@1080p(1920×1080)· HD and SD output switchable 3.6mm fixed lens (2.8mm optional)· Max. IR length 20m, Smart IR · DC12V	12,920,000
45	DH-HAC-ME1200EP-LED	2MP HDCVI Active Deterrence Camera Max 30fps@1080P· HD and SD output · switchable· 2.8mm/3.6mm fixed lens· 10m/110°detecting range/angle· Max. IR length 20m, Smart IR· IP67, DC12V	22,930,000
46	DH-HAC-HUM3201BP-P	2MP Starlight HDCVI Pinhole Camera > Starlight, 120dB true WDR, 3DNR> Max 30fp@1080P> HD and SD output switchable> 2.8mm fixed lens> Audio in interface> DC12V	41,600,000
47	DH-HAC-ME1500CP	5MP HDCVI Active Deterrence Camera> Max 20fps@5MP> HD and SD output switchable> 2.8mm fixed lens (3.6mm ,optional)> Max. IR length 20m, Smart IR> Built-in PIR 14±1m/110° detecting range/angle > Active deterrence with white light & siren> IP67, DC12V	32,520,000
48	DH-HAC-B2A51P	·(1944×2592)5MP HDCVI IR Bullet Camera· Max. 20fps@5MP . HD and SD output switchable· 3.6mm fixed lens (2.8mm,6mm optional)· Max. IR length 20m, Smart IR · IP67, DC12V	21,358,000
49	DH-HAC-B2A21P	2MP HDCVI IR Bullet Camera· Max. 30fps@1080P . HD and SD output switchable· 3.6mm fixed lens ·(1080×1920) (6mm optional)· Max. IR length 20m, Smart IR . IP67, DC12V	13,250,000
50	DH-HAC-B1A21P	2MP HDCVI IR Bullet Camera· Max. 30fps@1080P . HD and SD output switchable· 3.6mm fixed lens ·(1080×1920) ,(2.8mm, 6mm optional)· Max. IR length 20m, Smart IR. IP67 DC12V	11,590,000

51	DH-HAC-T2A51P	5MP HDCVI IR Eyeball Camera· Max. 20fps@5MP . HD and SD output switchable· 3.6mm fixed lens ·(1944×2592) ,(2.8mm,6mm optional)· Max. IR length 20m, Smart IR. IP67 DC12V	22,370,000
52	DH-HAC-T2A21P	2MP HDCVI IR Eyeball Camera· Max. 30fps@1080P . HD and SD output switchable· 3.6mm fixed lens ·(1080×1920) ,(2.8mm,6mm optional)· Max. IR length 20m, Smart IR · IP67 DC12V	13,558,200
53	DH-HAC-T1A51P	5MP HDCVI Fixed IR Eyeball Camera> Max. 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional)> Max. IR length 20 m, Smart IR> DC12V	19,558,000
54	DH-HAC-T1A21P	2MP HDCVI IR Eyeball Camera· Max. 30fps@1080P . HD and SD output switchable· 3.6mm fixed lens ·(1080×1920) (2.8mm, 6mm optional) · Max. IR length 20m, Smart IR. DC12V	12,070,000
55	DH-SD59430I-HC	4Megapixel CMOS· Powerful 30x optical zoom· 120dB "1/3 · ,true WDR, 3D DNR· Max. 25/30fps@4M/1080P 25/30/50/60fps@720P · IR distance up to 100m · IP66	410,460,000
56	DH-SD59230I-HC	2Megapixel STARVIS™ CMOS· Powerful 30x optical "1/2.8 · .zoom· Starlight technology· 120dB true WDR, 3D DNR· Max 25/30fps@1080P, 25/30/50/60fps@720P · IR distance up to 150m · IP66	305,380,000

57	DH-XVR5432L-I2	Channel Penta-brid 5M-N/1080P 1.5U WizSense Digital 32. Video Recorder. H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 8MP; Max 128) Mbps incoming bandwidth. Up to 2 channels video stream analog channel) perimeter protection. Up to 16 channels video stream (analog channel) SMD plus. Up to 2 channels video stream (analog channel) human face recognition. IoT & POS functionalities	394,660,000
58	DH-XVR5232AN-I3	Channel Penta-brid 5M-N/1080P 1U 2HDDs WizSense 32. Digital Video Recorder . H.265+/H.265 dual-stream video .compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 32 channels IP camera inputs, each channel up to 6MP Max 128 Mbps incoming bandwidth. Up to 2 channels video stream (analog channel) Perimeter Protection. Up to 16 channels video stream (analog channel) SMD Plus. Up to 2 channels video stream (analog channel) human face recognition. IoT & POS functionalities	270,150,000
59	DH-XVR5216AN-4KL-I3	Channel Penta-brid 4K-N/5MP 1U 2HDDs WizSense Digital 16 Video Recorder . H.265+/H.265 dual-stream video .compression- Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 32 channels IP camera inputs, each channel up to 8MP Max 128 Mbps incoming bandwidth- Up to 2 channels video stream (analog channel) Perimeter Protection- Up to 16 channels video stream (analog channel) SMD Plus- Up to 2 channels video stream (analog channel) human face recognition- IoT & POS functionalities	249,340,000
60	DH-XVR5216AN-4KL-S2	Channel Penta-brid 4K-N/5MP 1U 2HDDs WizSense Digital 16 Video Recorder . H.264+/H.264 dual-stream video .compression- Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 32 channels IP camera inputs, each channel up to 8MP Max 128 Mbps incoming bandwidth- Up to 2 channels video stream (analog channel) Perimeter Protection- Up to 16 channels video stream (analog channel) SMD Plus- Up to 2 channels video stream (analog channel) human face recognition- IoT & POS functionalities	234,480,000

61	DH-XVR5216AN-I3	Channel Penta-brid 5M-N/1080P 1U 2HDDs WizSense 16. Digital Video Recorder . H.265+/H.265 dual-stream video .compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 24 channels IP camera inputs, each channel up to 6MP Max 128 Mbps incoming bandwidth. Up to 2 channels video stream (analog channel) Perimeter Protection. Up to 16 channels video stream (analog channel) SMD Plus. Up to 2 channels video stream (analog channel) human face recognition IoT & POS functionalities	158,210,000
62	DH-XVR5116H-I3	H.265+/H.265 dual-stream video compression· Supports · HDCVI/AHD/TVI/CVBS/IP video inputs· Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth· Up to 2 channels video stream (analog channel) Perimeter Protection· Up to 16 channels video stream (analog channel) SMD Plus· Up to 2 channels video stream (analog channel) human face recognition · IoT & POS functionalities	124,950,000
63	DH-XVR5116HS-I3	Channel Penta-brid 5M-N/1080P Compact 1U 1HDD 16 WizSense Digital Video Recorder> H.265+/H.265 dual-stream video compression> Supports Full-channel AI Coding> Supports HDCVI/AHD/TVI/CVBS/IP video inputs> Max 24 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth> Up to 2 channels video stream (analog channel) Perimeter Protection> Up to 16 channels video stream (analog channel) SMD Plus> Up to 2 channels video stream (analog channel) human face recognition> IoT & POS functionalities	126,770,000
64	DH-XVR5108HS-4KL-I3	Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WizSense 8. Digital Video Recorder . H.265+/H.265 dual-stream video .compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 16 channels IP camera inputs, each channel up to 8MP Max 128 Mbps incoming bandwidth. Up to 2 channels video stream (analog channel) Perimeter Protection. Up to 8 channels video stream (analog channel) SMD Plus. Up to 2 channels video stream (analog channel) human face recognition. IoT & POS functionalities	124,260,000

65	DH-XVR5108HS-I3	Channel Penta-brid 5M-N/1080p Compact 1U 1HDD 8. WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression. Supports Full-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth. Up to 1 channel video stream (analog channel) Perimeter Protection. Up to 8 channels video stream (analog channel) SMD Plus. Up to 1 channel video stream (analog channel) human face recognition. IoT & POS functionalities	85,877,000
66	DH-XVR5104HS-4KL-I3	Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WizSense 4. Digital Video Recorder . H.265+/H.265 dual-stream video .compression. Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 8 channels IP camera inputs, each channel up to 8MP Max 64 Mbps incoming bandwidth. Up to 2 channels video stream (analog channel) Perimeter Protection. Up to 4 channels video stream (analog channel) SMD Plus. Up to 2 channels video stream (analog channel) human face recognition IoT & POS functionalities	76,310,000
67	DH-XVR5104HS-I3	Channel Penta-brid 5M-N/1080p Compact 1U 1HDD 4. WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression. Supports Full-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth. Up to 1 channel video stream (analog channel) Perimeter Protection. Up to 4 channels video stream (analog channel) SMD Plus. Up to 1 channel video stream (analog channel) human face recognition. IoT & POS functionalities	52,087,560
68	DH-XVR4116HS-I	Channel Penta-brid 720p Compact 1U 1HDD WizSense 16. .Digital Video Recorder. H.265+/H.265 video compression Supports Full-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth. Long transmission distance over coax cable. Up to 8 channels video stream (analog channel) SMD Plus	80,983,000

69	DH-XVR4108HS-I	Channel Penta-brid 1080N/720p Compact 1U 1HDD 8. WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression. Supports Full-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 10 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth. Up to 8 channels video stream (analog channel) SMD Plus	58,719,000
70	DH-XVR4104HS-I	Channel Penta-brid 1080N/720p Compact 1U 1HDD 4. WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression.Supports Full-channel AI-Coding.Supports HDCVI/AHD/TVI/CVBS/IP video inputs.Max 5 channels IP camera inputs, each channel up to 2MP; Max 32 Mbps incoming bandwidth.Up to 4 channels video stream (analog channel) SMD Plus	46,380,000
71	DH-XVR1B16H	Channel Penta-brid 4M-N/1080P Cooper 1U 1HDD Digital 16. .Video Recorder. H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 24 channels IP camera inputs, each channel up to 6MP; Max 96Mbps incoming bandwidth. Long transmission distance over coax cable. Supports 1 SATA HDD, up to 6TB. Smart Search and Intelligent Video System	89,060,000
72	DH-XVR1B16-I	-H.265+/H.265 dual-stream video compression- Supports Full - channel AI-Coding- Supports HDCVI/AHD/TVI/CVBS/IP video inputs- Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth- Long transmission) distance over coax cable- Up to 8 channels video stream analog channel) SMD Plus	77,580,000

73	DH-XVR1B08-I	Channel Penta-brid 1080N/720p Cooper 1U 1HDD WizSense 8. Digital Video Recorder . H.265+/H.265 dual-stream video compression. Supports Full channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth. Up to 4 channels video stream (analog channel) SMD Plus	37,294,500
74	DH-XVR1A08	Channel Penta-brid 1080N/720P Cooper 1U· H.264 video 8 . ·compression· Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 10 channels IP camera inputs, each channel up to 5MP Max 40Mbps Incoming Bandwidth· Long transmission distance over coax cable· Supports 1 SATA HDD, up to 6TB	39,620,000
75	DH-XVR1B04-I	Channel Penta-brid 1080N/720p Cooper 1U 1HDD WizSense 4. Digital Video Recorder . H.265+/H.265 dual-stream video compression. Supports Full channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth. Up to 4 channels video stream (analog channel) SMD Plus	30,072,500
76	DH-XVR1A04	4Channel Penta-brid 1080N/720P Cooper 1U· H.264 video . ·compression· Supports HDCVI/AHD/TVI/CVBS/IP video inputs ;Max 5channels IP camera inputs, each channel up to 2MP Max 20Mbps Incoming Bandwidth· Long transmission distance over coax cable· Supports 1 SATA HDD, up to 6TB	30,050,000

IP Price List

1	PSD81602-A360	8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lensPTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080PSupport 360-degree ,panoramic viewWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC BLCSmart tracking, Intelligent Function(Tripwire, Intrusion)2/1 channel Audio In/Out, 7/2 channel Alarm In/OutRS485, Micro SD memory, IP67, IK10	Call
2	PSD8802-A180	4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lensPTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080PSupport 180-degree ,panoramic viewWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC BLCSmart tracking, Intelligent Function(Tripwire, Intrusion)2/1 channel Audio In/Out, 7/2 channel Alarm In/OutRS485, Micro SD memory, IP67, IK10	Call
3	PFW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Bullet CameraFour 2Megapixel progressive scan STARVIS™ CMOS "1/2.8 H.265+/H.265/H.264+/H.264 triple-stream encodingMax 25fps@4096x1800, 3.0mm fixed lensSupport 180-degree ,panoramic viewDWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC BLCIntelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio ,In/Out, 2/2 channel Alarm In/OutMax. IR LEDs length 30m +Micro SD memory, IP67, IK10,PoE	Call
4	PFW8601-A180	3x2MP Multi-Sensor Panoramic Network IR Bullet ™CameraThree 1/2.8" 2Megapixel progressive scan STARVIS CMOS H.265+/H.265/H.264+/H.264 triple-stream encodingMax 25fps@4096x832, 3.6mm fixed lens, Support ,degree panoramic viewWDR, Day/Night(ICR), 3DNR, AWB-180 AGC, HLC, BLCIntelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio ,In/Out, 2/1 channel Alarm In/OutMax. IR LEDs length 30m +Micro SD memory, IP67, IK10,PoE	Call

5	PDBW8800-A180	4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 2Megapixel progressive scan STARVIS™ CMOS 1/2.8 H.265+/H.265/H.264+/H.264Max 25fps@4096x1800, 3.0mm fixed lensSupport 180-degree panoramic viewDWDR Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLCIntelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/OutMax. IR LEDs length 30m, Micro SD memory, IP67 +IK10,PoE	Call
6	ITC237-PW1B-IRZ	-Megapixel Full HD WDR Access ANPR Camera 2 پروند ,Embedded with LPR algorithm inside the camera-plate cutout snapshot preview, recording-White list database,1 ch relay out to control the barrier performance for outdoor applications-1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE	1 65,000,000
7	IPC5831EP-ZE	Megapixel progressive scan STARVIS™ CMOS 8 1/2.5 H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296)2.7mm ,12mm motorized lens, Max. Aperture F1.6WDR~ , Day/Night(ICR), 3DNR, AWB, AGC, BLCMicro SD card memory GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs 128 Length 50m , Smart IR, IP67,IK10, PoE (Tripwire Intrusion Object Abandoned/Missing Face)	12,400,000
8	IPC-HFW2831T-ZAS-S2	"8MP Lite IR Vari-focal Bullet Network Camera8MP, 1/2.7 Progressive CMOSlow illuminance 0.008 Lux@F1.5high image definition 8MP@15fps & 4MP@25/30fps2.7-13.5mm Motorized LensSMART H.264+/H.265+, (MJPEG in Sub ,Stream)IVS Intrusion, TripwireMicro SD 256GB, 1ch Audio I/O ,1ch Alarm I/OWDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol ,Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67 IR LEDs 60m Distance, Onvif Profile S/G/T 4	99,000,000

9	HFW2831T-ZS-S2	"8MP Lite IR Vari-focal Starlight Bullet Network Camera1/2.7 progressive scan CMOS image sensor, low illuminance, high image definitionSmart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate8MP (3840 × 2160) @15 ,fps, 2688×1520 @25/30 fpsWDR(120db), Day/Night(ICR) 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm–13.5 mm Motorized fixed lensMax. IR LEDs Length 60m, Micro SD card memory , 256 GBIP67, PoE, Smart Detection (Tripwire Intrusion)	98,000,000
10	IPC-HFW2831TP-AS-S2	"8MP Lite IR Fixed-focal Bullet Network Camera8MP, 1/2.7 CMOS image sensormax. 8MP (3840 × 2160) @15 fps, and /+supports 2688×1520 (2688 × 1520) @25/30 fpsSmart H.265 Smart H.264+, H.265; H.264; H.264B; MJPEG (only supported ,by the sub stream) Built-in IR LED, max IR distance: 80m 3.6mm Fixed LenzMin. Illumination 0.009 Lux@F2.0ONVIF ;(Profile S/Profile G/Profile T); CGI; Milestone GenetecWDR(120db), 3D NR, HLC, BLC, AGC, AWB, Rol, Smart ;IRIntrusion, tripwireAlarm: 1 in, 1 out; audio: 1 in, 1 out supports max. 256 GB Micro SD card12V DC/POE power support supply, IP67, IK10	73,000,000
11	IPC-HFW2831S-S-S2	"8MP Lite IR Fixed-focal Bullet Network Camera1/2.7 Progressive CMOS image sensor, low illuminance, high image ,+definition Illumination 0.009 Lux@F2.0SMART H.264+/H.265 × MJPEG, high compression rate, ultra-low bit rate8MP (3840 (fps, and supports 2688×1520 (2688 × 1520 15@ (2160 ,fps WDR (120 db), 3D DNR, HLC, BLC, AGC, AWB, Rol 25/30@ Smart IRIntrusion, tripwire, SD Card 256GB, IP67, PoE	67,000,000
12	IPC-HFW1830SP-0360B-S6	8MP 8MP 1/2.7" CMOS Entry IR Fixed-focal Bullet Network CameraOutputs max. 8MP@15fps, supports 2688 × 1520 ,fps Illumination 0.004 Lux@F2.0 (B/W 25/30@ (1520 × 2688) (RE)H.265+&H.264+ high compression rate, and ultra-low 30 ,bit rate.WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC .Built-in MIC3.6mm fixed lens, Built-in IR LED, and the max illumination distance is 30 m. 12 V DC/PoE power supply, IP67	58,000,000

13	HFW2531TP-ZS	5Megapixel progressive CMOS2.7~13.5mm Motorized "1/2.7 (1296×2304)lens 15fps@5M(2592×1944)&25/30fps@3M H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD ,card 128GB, Max IR LEDs Length 60m ,Smart IR IP67, PoE Smart Detection (Tripwire Intrusion)	86,000,000
14	DH-IPC-HFW5449T1-ZE-LED	4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 .fps, Focal Length 2.7 mm–12 mmMin 30@ (1520 × Illumination 0.0005 Lux@F1.0 , S/N Ratio > 56 dBbuilt-in warm ,illuminator, and the max. illumination distance : 70 mROI ,SMART H.264+/H.265+, flexible coding, WDR 140db , 3D NR HLC, BLCIVS (Perimeter Protection) : Tripwire; intrusion; fast moving, loitering detection, people gathering; parking detection, Face Detection, People Counting, Intelligent SearchAlarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, built-in Mic and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0	165,000,000
15	HFW5442EP-ZE-0832	4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOSH.265,H.264,H.264B,H.264H, MJPEG ,(1520×2688)triple-stream encodingMax 25/30fps@4Mp ,50/60fps@2Mp(1920 × 1080)WDR(140dB), Day/Night(ICR) ,3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest 8mm-32mm Motorized lenz, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GBAudio in/Out 1/1, Alarm In/Out 2/1Smart Detection Tripwire, intrusion (Recognition of ,vehicle and people), Object Abandoned / Missing, fast moving loitering detection, parking detection and people gatheringSupport Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas ,independent detection, Scene Change, Heatmap, IP67, IK10 PoE	1 40,000,000

16	IPC-HFW5241E-Z5E	"2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8 0.0015 Progressive STARVIS™ CMOS low illuminance Lux@F1.3 high image definition 2MP@25/30fps 7-35mm ; Motorized Lens SMART H.264+/H.265+ IVS: Tripwire; intrusion fast moving (with accurate classification of vehicle and human); loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD , card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS , Defog, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T	1 22,000,000
17	DH-IPC-HFW4431TP-S-S4	4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp (2688x1520) H.265 & H.264 triple-stream , encoding IVS (Tripwire, Intrusion, Object Abandoned/Missing , Face detection) WDR (120dB), Day/Night (ICR), 3DNR, AWB AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE	55,200,000
18	DH-IPC-HFW3849T1-AS-PV-S3	8MP Smart Dual Illumination Active Deterrence Fixed-focal , Bullet WizSense Network Camera 1/2.8" CMOS image sensor low illuminance, high image definition Outputs max. 8 MP fps Min. Illumination 0.004 lux@F1.0 25/30@ (2160 x 3840) (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux . (illuminator on) Built-in warm illuminator, and the max illumination distance: 30m Intrusion, tripwire (support the classification and accurate detection of vehicle and human) WDR 120db, 3D NR, HLC, BLC, digital watermarking, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256G SD card; built-in dual MICs; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0, One-click arming/disarming through alarm input	118,000,000
19	DH-IPC-HFW3449EP-AS-LED-3.6	"4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp (2688x1520) H.265/Smart H.265+/H.264/Smart H.264+ triple-stream encoding IVS (Tripwire, Intrusion, Recognition of vehicle and people, SMD , Plus) WDR (120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	66,300,000

20	DH-IPC-HFW3449EP-AS-LED-2.8	4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" CMOS 2.8mm fixed lens 4Megapixel progressive CMOS 25/30fps@4Mp(2688x1520)H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	66,300,000
21	HFW3441TP-ZS-27135	4MP IR Vari-focal Bullet WizSense Network Camera 4Megapixel progressive CMOS Min. Illumination:0.005"1/3 Lux@F1.52.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688x1520)SMART H.264+/H.265+ triple stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE	93,000,000
22	DH-IPC-HFW2449S-S-IL	4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image Outputs max. 4 MP (2688 fps, and supports 2560 x 1440 @25/30 fps H.265 20@(1520 x .codec, high compression rate, ultra-low bit rate Min Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) Built-in warm light/IR LED the max. illumination distance is 30 mROI, SMART H.264+/H.265+, flexible coding Rotation mode, WDR, 3D NR HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC12 VDC/PoE power supply, easy for installation, IP67 protection SMD Plus	49,500,000

23	DH-IPC-HFW2441T-ZS	4MP IR Vari-focal Bullet WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 fps Min. Illumination, 0.008 lux@F1.5 25/30@(1440 × 2560), (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm–13.5 mm Built-in IR LED, and the ,+max. illumination distance is 60 m ROI, SMART H.264+/H.265 flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire support the classification and accurate detection of vehicle) ,and human) Alarm: 1 in, 1 out (Only - ZAS supports), audio: 1 in out (Only - ZAS supports), 256G SD card, built in MIC 12 1 VDC/PoE power supply, easy for installation, IP67, IK10 (optional) protection, SMD Plus	84,000,000
24	IPC-HFW2439SP-SA-LED-0360B-S2	4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP Progressive CMOS Low illuminance 0.004 Lux@F1.0 high "1/3" image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T	46,200,000
25	HFW2431TP-AS-S2	4MP Lite IR Fixed-focal Bullet Network Camera, 1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520) @20 fps, and ,supports 2560×1440 (2560 × 1440) @25/30 fps Built-in IR LED ,max IR distance: 80 m, Intelligent detection: Intrusion tripwire H.265; H.264; H.264B; MJPEG(only supported WDR(120 dB), 3D NR, HLC, BLC, digital watermarking Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE , IP67 protection, IK10 protection (optional)	56,500,000
26	HFW2431TP-ZS-S2	4MP WDR IR Bullet Network Camera 1/3" 4MP image × sensor SMART H.264/H.265 dual stream encoding 4MP (2688 fps, 2560 × 1440 @25fps) Min. Illumination: 0.008 20@(1520 ,Lux@F1.5, 2.7–13.5 mm Motorized lens WDR(120dB) Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance: 60 m, Smart IR, IP67, PoE	73,500,000

27	IPC-HFW1431S1-S4-S5	"4MP Entry IR Fixed-focal Bullet Network Camera 4MP, 1/3 Progressive CMOS Slow illumination 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart ,H.265+/H.264+WDR(120db), ROI, BLC, HLC, 3D DNR, AWB AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)	31,500,000
28	HFW1431SP-0360B-S4	4MP Entry IR Fixed-focal Bullet Network Camera 4Megapixel progressive CMOS SMART H.264/H.265 dual" 1/3 stream encoding 4MP (2688 x 1520)@20 fps, 2560 x 1440 25fps Min. Illumination:0.03 Lux@F2.0, 3.6 Fixed@ ,lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC ROI max IR distance:30 m, Smart IR, IP67, PoE	37,000,000
29	HFW3541EP-AS	"5MP IR Fixed focal Bullet WizSense Network Camera 1/2.7 CMOS image sensor, Outputs max. 5MP (2592 x 1944) @20 fps ,H.265 codec SMART H.264+/H.265+WDR(120db), 3D DNR, HLC BLC, digital watermarking, Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE) 12V DC/POE IP67 SMD Plus Supports max. 256 G Micro SD card, built-in Mic	Call
30	IPC-HFW3549T1P-AS-PV	MP 1/2.7" CMOS image sensor, low luminance, Smart Dual-5 / Illumination Min. Illumination : 0.003 lux@F1.0 (Color, 30 IRE) lux@F1.0 (B/W, 30 IRE) / 0 lux (illuminator on) Lens 0.0003 ,Fixed-focal 3.6 mm , 15.6 m Recognize & 7.8 m Identify Illumination Distance : 30 m (2 IR LED) / 30 m (2 warm light) AI H.265, AI H.264 , Smart H.265+, Smart H.264+, Built-in x MIC Main stream: 2880 x 1620 or 2960 x 1668 @20fps / 2688 ,(30 fps) WDR (120db), 3D DNR, HLC, BLC, AWB, AGC@ 1520 ROI(4 years), Smart Illumination, Defog, Scene Self-adaption Storage : FTP, SFTP, Micro SD card (support max. 256 G), NAS ROM : 128MB, RAM : 512MB, S/N Ratio > 56db , Sound and Light Alarm,Active Deterrence, IVS (Tripwire, intrusion), SMD Smart Search, Quick Pick, AI SSA Audio In/out : 1/1 , Alarm ,4.0 in/out : 1/1, RJ-45 (10/100 Base-T) , 3.3 W (12 VDC); 4.4 W (PoE), IP67	99,500,000

31	HFW3549EP-AS-LED-0360B	5MP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera 5MP, 1/2.7" CMOS image sensor low illuminance 0.003 Lux@F1.05MP@20 fps, 4MP@25/30 fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V PoE, IP67, Built-in warm light, max. illumination distance: 30m, Onvif Profile S/G/T	73,500,000
32	IPC-HFW3541TP-ZS-27135	5MP IR Vari-focal Bullet WizSense Network Camera 5MP, Progressive CMOS 0.005 Lux@F1.5 (Color, 30IRE) 1/2.7 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on) high 0.0005 image definition 5MP@20fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ 3 Streams IVS Intrusion, Tripwire Accurate Human/Vehicle Classification, SMD Plus Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T	1 11,000,000
33	IPC-HFW2531TP-AS-S2	5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7 Progressive CMOS low illuminance 0.008 Lux@F1.6 high image definition 5MP@20fps, 3.6mm fixed Lens SMART H.264+/H.265+, IVS Intrusion/Tripwire 1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB WDR (120db), 3D DNR, HLC, BLC AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T	64,800,000
34	HFW2431SP-S-S2	4MP WDR IR Bullet Network Camera 1/3" 4MP image x sensor SMART H.264/H.265 dual stream encoding 4MP (2688 fps, 2560 x 1440 @ 25fps) Min. Illumination: 0.008 20@(1520 Lux@F1.6, 3.6mm Fixed lens WDR (120dB), Day/Night (ICR) 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance m, Smart IR, IP67, PoE 30	42,500,000

35	HFW2249SP-S-IL-0360B	2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)Outputs max. 2 MP ,+fps, Fixed Lens 3.6mmSmart H.265 25/30@(1080 × 1920) Smart H.264+, H.264H, H.265, H.264, H.264BBuilt-in warm light/IR LED : 30m/30mROI, WDR, 3D NR, HLC, BLC, digital watermarkingSMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC.12 VDC/PoE power supply, easy for installation, IP67	41,000,000
36	HFW2249SP-S-IL-0280B	2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)Outputs max. 2 MP ,+fps, Fixed Lens 2.8mmSmart H.265 25/30@(1080 × 1920) Smart H.264+, H.264H, H.265, H.264, H.264BBuilt-in warm light/IR LED : 30m/30mROI, WDR, 3D NR, HLC, BLC, digital watermarkingSMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human) Supports max. 256 G Micro SD card, built in MIC.12 VDC/PoE power supply, easy for installation, IP67	41,000,000
37	HFW2231SP-S-0360B-S2	"2MP WDR IR Bullet Network Camera, starlight1/2.8 2Megapixel progressive CMOSMin. Illumination:0.002 ,Lux@F1.6Outputs max. 2MP (1920 × 1080) @25/30 fps ,3.6mm Fixed lensSMART H.264/H.265 dual-stream encoding ,IVS(Tripwire, intrusion)WDR(120dB), Day/Night(ICR), 3DNR AWB, AGC, BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE	31,000,000
38	HFW2230SP-S	2MP IR Bullet Network Camera1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding ,25/30fps@1080P(1920×1080)DWDR, Day/Night(ICR), 3DNR ,AWB, AGC, BLC, HLC, ROI3.6mm, Max. IR LEDs Length 30m ,Smart IRMicro SD card memory 128 GB, IP67, PoE AVI(Tripwire Intrusion)	30,000,000

39	IPC-HFW2239SP-SA-LED-S2	"2MP Lite Full-color Fixed-focal Bullet Network Camera1/2.8 CMOS image sensor,Outputs max. 2MP (1920 × 1080) @25/30 fps ROI, SMART H.264+/H.265+, flexible coding,Min ,Illumination 0.0017 Lux@F1.0Intelligent detection: Intrusion tripwireWDR(120db), 3D NR, HLC, BLC, digital watermarkingSupports max. 256 GB Micro SD card and built-in Mic,12V DC/PoE ,IP67	37,500,000
40	IPC-HFW2231T-ZS-S2	"2MP Lite IR Vari-focal Bullet Network Camera2MP, 1/2.8 Progressive CMOS, low illuminance 0.002 Lux@F1.5high image ,definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens SMART H.264+/H.265+ IVS Intrusion, Tripwire, Micro SD card ,GBWDR(120db), RoI, BLC, HLC, 3D DNR, AWB, AGC 256 Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T	65,000,000
41	HFW1530SP-0360B-S6	× 5MP 1/2.7" CMOS image sensorOutputs max. 5MP (2880 fps,Fixed-focal 3.6mm min illumination 0.003 20@ (1620 ,+Lux@F2.0 (B/W, 30 IRE)H.265 codec, SMART H.264 +/H.265 Built-in IR LED, and the max. illumination distance is 30 m Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC, IP67,POE	39,800,000
42	DH-IPC-HFW1239S1-LED-S5	,2MP Lite Full-color Fixed-focal Bullet Netwok Camera2MP Progressive CMOSlow illuminance 0.005 Lux @F1.6high "1/2.8 image definition 2MP@25/30fps3.6mm fixed lensSMART H.264+/H.265+DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart ,Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance Onvif Profile S/T	26,400,000
43	HFW1230T1P-ZS	2MP Entry, 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 2MP (1920 × 1080)@25/30 fps.Min. Illumination : 0.008 Lux@F1.7 (Color, 30 IRE), 0.0008 ,Lux@F1.7 (B/W, 30 IRE) Motorized vari-focal, 2.8 mm–12 mm IR Distance 50 m(2 IR)Smart H.265+, Smart H.264+, H.265 codec, high compression rate, ultra-low bit rate. DWDR, 3D ,DNR, HLC, BLC, AWB, AGC, RoI(4 years), Smart Illumination S/N Ratio > 56 dB 1 Port RJ-45 (10/100 Base-T), 12V DC/PoE (802.3af), IP67, Humidity ≤95%	52,000,000

44	HFW1230S1P-0360B-S5	2MP Entry IR Fixed-Focal Bullet Network Camera1/2.8" CMOS ,image sensor, low illuminanceFixed Lens 3.6mm, F2.0 Horizontal: 84°Outputs max. 2MP (1920 × 1080) @25/30 fpsSmart H.265+, Smart H.264+, H.265, H.264, H.264BONVIF .(Profile S/Profile T)Built-in efficient IR illuminator, and the max ,illumination distance is 30 m ROI, DWDR, 3D NR, HLC, BLC digital watermarking2V DC/PoE power supply, IP67	24,000,000
45	HFW1230SP-S4-S5	"2MP Entry IR Fixed-focal Bullet Network Camera1/2.7 2Megapixel progressive CMOSSMART H.264/H.265 dual .stream encodingmax. 2MP (1920 × 1080p) @25/30 fpsMin ,illumination:0.01 Lux@F2.03.6 Fixed lensDWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30m, Smart IRIP67, PoE	27,000,000
45	HFW1230SP-S4-S5	"2MP Entry IR Fixed-focal Bullet Network Camera1/2.7 2Megapixel progressive CMOSSMART H.264/H.265 dual .stream encodingmax. 2MP (1920 × 1080p) @25/30 fpsMin ,illumination:0.01 Lux@F2.03.6 Fixed lensDWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30m, Smart IRIP67, PoE	27,000,000
46	HDW4431EMP-AS-S4	4MP IR Eyeball Network Camera1/3" 4Megapixel progressive CMOS2.8mm fixed lens 25/30fps@4Mp(2688×1520)H.265&H.264 triple-stream ,encodingIVS(Tripwire, Intrusion, Object Abandoned/Missing ,Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB AGC, BLC, HLCBuilt-in MicMicro SD memory 256GBMax. IR LEDs Length 50m, Smart IR, IP67, PoE	48,000,000
47	HDBW3441EP-AS	"4MP IR Fixed focal Dome WizSense Network Camera1/3 CMOS image sensorOutputs max. 4MP (2688 × 1520)@30 fps ,H.265 codec,SMART H.264+/H.265+WDR(120db), 3D DNR HLC, BLC, digital watermarkingSupports max. 256 G Micro SD card,12V DC/POE,IP67, IK10, SMD Plus Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE) Audio Input 1 channel (RCA port),Audio Output 1 channel (RCA port) Alarm Input 1 channel in,Alarm Output 1 channel out	57,000,000

48	HDW3441TMP-AS-0280B	4MP IR Fixed focal Eyeball WizSense Network Camera 4Megapixel progressive CMOSMin. Illumination:0.005"1/3 Lux@F1.62.8mm Motorized -lens25/30fps@4Mp(2688x1520)SMART H.264+/H.265+ triple stream encodingIVS(Tripwire; intrusion (Recognition of human ,and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC BLC, HLC, RoI Built-in Mic, Micro SD memory 256GBMax. IR LEDs Length 50m, Smart IR, IP67, PoE	54,000,000
49	HDBW2831EP-S-S2	8Megapixel progressive CMOSMin. Illumination:0.009 "1/2.7 ,Lux@F2.03.6mm Fixed Lensmax. 8MP (3840 × 2160) @15 fps ,+fpsSMART H.264+/H.265 25/30@ (1520 × 2688) 1520×2688 :flexible codingIVS(Tripwire; intrusion), Abnormality detection ,Motion detection, video tampering WDR(120dB) Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoIMicro SD memory 256GBBuilt-in IR LED Max.Length 30m, IP67, PoE	69,500,000
50	HDBW2531RP-ZAS	5Megapixel progressive CMOS2.7~13.5mm Motorized "1/2.7 (1296×2304)lens 20fps@5M(2592×1944)&25/30fps@3M H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/outMirco SD card 128GBMax IR LEDs Length 30m ,Smart IRIP67,IK10, PoE	86,000,000
51	IPC-HDBW2531E-S-S2	"5MP Lite IR Fixed-focal Dome Network Camera5MP, 1/2.7 Progressive CMOSMin. Illumination 0.008 Lux @ F1.6Max ,5MP@20fpsSMART H.264+/H.265+IVS: Intrusion ,tripwireMirco SD card 256GBWDR(120dB), Day/Night(ICR) ,3DNR, AWB, AGC, BLC, HLC, RoI max IR distance: 30m, 12V DC PoE, IP67,IK10	43,200,000
52	IPC-HDW2831TP-AS-S2	8MP Lite IR Fixed-focal Eyeball Network Camera1/2.7" CMOS image sensorOutputs max. 8MP (3840 × 2160) @15 fps Min Illumination 0.009 Lux@F2.0Built-in IR LED, max IR distance: 30 m SMART H.264+/H.265+ WDR, 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card, built-in MIC12V DC/PoE,IP67	70,000,000

53	DH-IPC-HDW2449T-S-IL	<p>4MP Smart Dual Illumination Fixed-focal Eyeball WizSense ,Network CameraOutputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 @25/30 fpsMin. Illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on)H.265 codec, high compression rate, ultra-low bit rateBuilt-in warm light/IR LED, the max. illumination distance is 30 mROI, SMART H.264+/H.265+, flexible coding WDR, 3D NR, HLC, BLC, digital watermarkingIntrusion, tripwire support the classification and accurate detection of vehicle) ,and human Supports max. 256 G Micro SD card; built in MIC VDC/PoE power supply, easy for installation, IP67 12 protection,SMD Plus</p>	51,000,000
54	IPC-HDW2439TP-AS-LED-0360B	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera4MP Progressive CMOSlow illuminance 0.004 Lux@F1.0high "1/3 image definition 4MP@25/30fps3.6mm Fixed lensSMART ,H.264+/H.265+IVS Intrusion/TripwireWDR (120db), 3D DNR HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>	47,200,000
55	IPC-HDW2439TP-AS-LED-0280B-S2	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera4MP Progressive CMOSlow illuminance 0.004 Lux@F1.0high "1/3 image definition 4MP@25/30fps2.8mm Fixed lensSMART ,H.264+/H.265+IVS Intrusion/TripwireWDR (120db), 3D DNR HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>	47,200,000

56	DH-IPC-HDBW2441E-S	4MP 1/2.9" CMOS image sensor, IR Fixed-focal Dome WizSense ,Network CameraOutputs max. 4 MP (2688 × 1520)@20 fps and supports 2566 × 1440@25/30 fpsMin. Illumination 0.008 lux@F1.6 (Color,30IRE), 0.0008 lux@F1.6 (B/W,30IRE), 0 lux Illuminator on H.265 codec, high compression rate, ultra-low) bit rateBuilt-in IR LED, and the max. illumination distance is 30 ,mROI, SMART H.264+/H.265+, flexible coding, , WDR 120db 3D NR, HLC, BLCIntrusion, tripwire (support the classification .and accurate detection of vehicle and human) Supports max ,G Micro SD card; built in MIC12 VDC/PoE power supply 256 easy for installation, IP67, IK10 protection, SMD Plus	46,800,000
57	DH-IPC-HDBW2441R-ZS	4MP IR Vari-focal Dome WizSense Network Camera, 4-MP × CMOS image sensorOutputs max. 4 MP (2688 "1/2.9 × fps and supports 2560 × 1440 , (2560 20@(1520 fpsMin. Illumination 0.008 lux@F1.5 (Color, 30 25/30@(1440 (IRE) , 0.0008 lux@F1.5 (B/W, 30 IRE) , 0 lux (Illuminator on H.265 codec, high compression rate, ultra-low bit rateBuilt-in IR LED, and the max. illumination distance : 40 m, ROI, SMART H.264+/H.265+WDR 120dB, 3D NR, HLC, BLC, Focal Length 2.7 mm–13.5 mmIntrusion, tripwire (support the classification and accurate detection of vehicle and human)Alarm: 1 in, 1 out ;(Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports) 256G SD card; built in MIC 12 VDC/PoE power supply, easy for installation, IP67 and IK10 protection, SMD Plus	79,500,000
58	HDBW2431RP-ZS-27135-S2	4MP WDR IR Dome Network Camera1/3" 4Megapixel progressive CMOSSMART H.264/H.265 dual stream .encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin Illumination:0.008 Lux@F1.52.7–13.5 mm Motorized ,lensWDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC ROI Smart Detection (Tripwire Intrusion)Micro SD memory GB1/1 Audio in/out, 1/1 Alarm in/outmax IR distance:40 256 m, Smart IRIP67, IK10, PoE	72,000,000

59	HDBW2431RP-ZAS-S2	4MP WDR IR Dome Network Camera1/3" 4Megapixel progressive CMOSSMART H.264/H.265 dual stream .encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin Illumination:0.008 Lux@F1.52.7–13.5 mm Motorized ,lensWDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC ROI Smart Detection (Tripwire Intrusion)Micro SD memory GB1/1 Audio in/out, 1/1 Alarm in/outmax IR distance:40 256 m, Smart IRIP67, IK10, PoE	73,000,000
60	HDBW2431EP-S-0360B-S2	4MP IR Mini Dome Network Camera1/3" 4Megapixel progressive CMOSSMART H.264/H.265 dual stream .encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,Illumination:0.008 Lux @ F1.63.6 mm Fixed lensWDR(120dB) Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion)Micro SD memory 256 GBmax IR distance:30 m, Smart IRIP67, IK10, PoE	41,000,000
61	HDBW2431EP-S-0280B-S2	4MP IR Mini Dome Network Camera1/3" 4Megapixel progressive CMOSSMART H.264/H.265 dual stream .encoding4MP (2688 × 1520)@20 fps,2560 × 1440 @25fpsMin ,Illumination:0.008 Lux @ F1.62.6 mm Fixed lensWDR(120dB) Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion)Micro SD memory 256 GBmax IR distance:30 m, Smart IRIP67, IK10, PoE	41,000,000
62	HDW2431TP-AS-0280B-S2	4MP Lite IR Fixed-focal Eyeball Network Camera1/3" CMOS image sensor, Outputs 4MP (2560 × 1440)@25/30 fps H.265 .coding, SMART H.264+/H.265+, Fixed Lens 2.8mmMin ,Illumination 0.008 Lux @ F1.6 WDR(120db), 3D NR, HLC, BLC digital watermarking,Intelligent detection: Intrusion, tripwire Max. 256 GB SD card and built-in Mic ,12V DC/POEIP67	43,200,000
63	HDW2431TMP-AS-0280B-S2	"4MP WDR IR Eyeball Network Camera, Starlight1/3 4Megapixel progressive CMOSSMART H.264/H.265 dual stream encoding4MP (2688 × 1520)@20 fps,2560 × 1440 25fpsMin. Illumination:0.008 Lux@F1.62.8 mm Fixed@ ,lensWDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC ROI Smart Detection (Tripwire Intrusion)Micro SD memory GB, Built in Micmax IR distance:30 m, Smart IRIP67, PoE 256	44,000,000

64	HDBW1431EP-0280B-S4	4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Network, low illuminanceMin. Illumination : 0.03 Lux @ F2.0 Illumination Distance : 30 m(3 IR LED), S/N Ratio > 56db Lens, :Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° / Diagonal :111°Smart H.265+, H.265, Smart H.264+, H.264Main Stream (20 fps), high compression rate, ultra-low bit 1520 × 2688 ,rateWDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol(4 years) ,Smart IlluminationStorage(FTP, SFTP, NAS) , ROM : 128MB > RAM : 512MB12V DC/POE (802.3af), Power Consumption 5.5W, 1 port RJ-45 (10/100 Base-T) ,IP67, IK10	37,500,000
65	HDW1431T1P-A-0360B-S4	4MP Entry IR Fixed-focal Eyeball Network Camera1/3"4Megapixel progressive CMOS, Fixed-focal (1440×2560)3.6mm20fps@4.1M(2688×1520) & 25fps@4M H.265+/H.265/H.264+/H.264 dual-stream ,encodingWDR(120dB), Day/Night(ICR), Image flip, 3D DNR HLC, BLC, digital watermar Support ROI,Built-in MICMax. IR LEDs Length 30m, IP67, PoE	37,200,000
66	HDW1431T1P-0280B-S4-S5	4MP Entry IR Fixed-focal Eyeball Network Camera (1520×2688)4Megapixel progressive CMOS 20fps@4.1M"1/3 -25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual & ,stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB AGC, BLC, HLC Support ROI,Max. IR LEDs Length 30m, IP67, PoE	34,000,000
67	DH-IPC-HDW2249TP-S-IL-0280B	2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera 2-MP 1/2.8" CMOS image sensor, low , luminanceMin. Illumination : 0.0002 lux@F1.6 (B/W, 30 IRE) Fixed Lens 2.8 mm Outputs max. 2 MP (1920 × 1080)@25/30 ,fpsSmart Codec : Smart H.265+, Smart H.264+, H.264H, H.265 H.264, H.264B SMD Plus, Intrusion, tripwire (accurate detection of vehicle and human). Supports max. 256G Micro SD card, built in MIC.ROI, WDR, 3D NR, HLC, BLC, digital watermarkingBuilt-in warm light/IR LED : 30m/30m12 VDC/PoE power supply, easy for installation, IP67	41,000,000

68	HDW2231TMP-AS-S2	"2MP WDR IR Eyeball Network Camera, Starlight1/2.8 2Megapixel progressive CMOSMin. Illumination:0.002 Lux@F1.6Outputs max. 2MP (1920 × 1080) @25/30 fps2.8mm Fixed lensSMART H.264/H.265 dual-stream ,encodingIVS(Tripwire, intrusion)WDR(120dB), Day/Night(ICR) 3DNR, AWB, AGC, BLC, HLC, RoI Built-in Mic, Micro SD memory 256GBMax. IR LEDs Length 30m, Smart IR, IP67, PoE	35,000,000
69	IPC-HDW2231TP-AS-0280B-S2	,2MP Lite IR Fixed-focal Eyeball Network Starlight Camera2MP Progressive CMOSlow illuminance 0.002 Lux @F1.6high "1/2.8 image definition 2MP@25/30fps2.8mm fixed lensSMART ,H.264+/H.265+IVS Intrusion/TripwireWDR (120db), 3D DNR HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T	34,500,000
70	IPC-HDW2230T-AS-S2	2MP IR Eyeball Network Camera2MP, 1/2.7" Progressive CMOSlow illuminance 0.005 Lux @ F1.6high image definition 2MP@25/30fps2.8mm fixed lensSMART H.264+/H.265+IVS Intrusion, TripwireMicro SD 256GB, Built-in MicDWDR, 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T	30,000,000
71	IPC-HDBW2230E-S-S2	"2MP Lite IR Fixed-focal Dome Network Camera2MP, 1/2.7 Progressive CMOSlow illuminance 0.005` Lux @F1.6high image definition 2MP@25/30fps2.8mm Fixed LensSMART ,H.264+/H.265+IVS Tripwire; intrusionMicro SD 256GBDWDR ,3D DNR, HLC, BLC, AWB, AGC, RoI, Smart Illumination Day/Night ICR Auto Switch 12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T	29,800,000
72	HDW1530TP-0280B-S6	5MP Entry IR Fixed-focal Eyeball Network Cam 1/2.7" CMOS image sensorlow illuminance 0.003 Lux @F2Outputs max. 5MP ,H.265 code, SMART H.264 +/H.265DWDR 20@ (1620 × 2880) 3D NR, HLC, BLC, digital watermarking Built-in MIC,12 V DC/PoE power supply	40,500,000

73	DH-IPC-HDW1239T1-A-LED-S5	2MP Lite Full-color Fixed-focal Eyeball Network Camera Outputs max. 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression rate, ultra-low bit rate Min. Illumination : 0.005 Lux @F1.6, Built-in LEDs, max LED distance: 15 m, built in MICROI, SMART H.264/H.265, flexible coding, applicable to various Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, 12V DC/PoE power support, IP67 protection	29,500,000
74	DH-IPC-HDW1239T1-LED-0360B-S5	,MP Entry Full-color Fixed-focal Bullet Network Camera 2MP 2 Progressive CMOS low illuminance 0.005 Lux @F1.6 high "1/2.8 image definition 2MP@25/30fps 3.6mm fixed lens Smart ,H.265+/Smart H.264+DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T	26,400,000
75	DH-IPC-HDW1239T1P-LED-0280B-S5	,MP Entry Full-color Fixed-focal Bullet Network Camera 2MP 2 Progressive CMOS low illuminance 0.005 Lux @F1.6 high "1/2.8 image definition 2MP@25/30fps 2.8mm fixed lens Smart ,H.265+/Smart H.264+DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T	26,400,000
76	DH-IPC-HDW1230T1-A-S5	.2MP Entry IR Fixed-Focal Eyeball Network Camera Outputs max 2MP (1920 × 1080) @25/30 fps H.265 codec, high compression -rate, ultra-low bit rate, Min. Illumination : 0.01 Lux @F2.0 Built in efficient IR illuminator, and the max. illumination distance is mROI, SMART H.264+/H.265+, flexible coding, applicable to 30 ,various, built in MICRotation mode, DWDR, 3D NR, HLC, BLC S/N Ratio 56 dB, digital watermarking 12V DC/PoE power supply, IP67 protection	27,800,000
77	HDW1230T1P-0280B-S5	"2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7 2Megapixel progressive CMOS SMART H.264/H.265 dual .stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min ,Illumination:0.01 Lux@F2.0, 2.8 Fixed lens DWDR Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR, IP67, PoE	24,000,000
78	HDBW1230EP-0360B-S2	2Megapixel progressive scan CMOS, 3.6mm fixed lens "1/2.7 H.265+/H.265/H.264+/H.264 dual-stream encoding ,25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE	27,000,000

79	DH-SD29204T-GN	2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical "1/2.7 ,ZoomH.264+/H.264 EncodingMax. 25/30fps@ 1080P 25/30/50/60fps@720PWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focusMax 100°/s pan speed, 360° endless pan rotationUp to 300 presets, 5 auto scan, 8 tour, 5 patternBuilt-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion Scene Change Face Abandoned-Missing Object	72,500,000
80	DH-SD1A203T-GN	2MP STARVIS™ CMOS "1/2.8 (Starlight)H.265+/H.265/H.264+/H.264 Triple-streams encodingMax. 25/30fps@ 1080P, 2.7mm ~ 8.1mm , 3x Optical ZoomWDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto ~ focusMax Pan: 80° /s; Tilt: 40° /s speedPan: 0° ~ 355°; Tilt: 5° ,rotationUp to 300 presets, 5 auto scan, 8 tour, 5 pattern 90° Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned/Missing Face Detection)	74,000,000
81	SD3A205-GNP-PV	;2MP Starlight IR AI WizSense Network PTZ CameraH.265 ;H.264B; H.264M; H.264H; MJPEG; MJPEG (Sub Stream) H.265+; H.264+ Focal Length 2.7 mm–13.5 mm, Optical Zoom 5xTripwire and intrusion, Deep-learning-based perimeter protectionm SMD Plus IR distance up to 30mStarlight ,technologyUp to 300 presetsDWDR, HLC, BLC, AGC, AWB -2D/3D DNR, Day/Night Auto (ICR), Rol, Defog Built-in Mic, Built ;in Speaker, Two Way Audio ONVIF Profile S&G&T; CGI IP66 TVS 2000V lightning proof; surge protection; voltage transient protection	96,500,000
82	DH-SD6CE230U-HNI	2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 "1/2.8 EncodingMax. 50/60fps@ 1080P4.5mm~135mm Powerful 30x optical zoomMax 200°/s pan speed, 360° endless pan ,rotationWDR(120db), Day/Night(ICR), Ultra DNR, BLC ,HLCAuto-tracking,Tripwire, Intrusion,Abandoned/Missing Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 ,presets,8 tour, 5 pattern, Auto scan, Auto PanAlarm 7/2 in/out Audio 1/1 in/out, 1*Video outputRS485, IR Distance up to 200m, PoE+, IP67, IK10	3 40,000,000

83	DH-SD6CE245XA-HNR	<p>"2MP 45x Starlight IR WizSense Network PTZ Camera1/2.8 2Megapixel STARVIS™ CMOS.H.265+/H.265/H.264+/H.264 Triple-streams encodingMinimum Illumination:Color(0.005Lux@F1.6) ,B/W(0.0005Lux@F1.6)Max. 50/60fps@1080P ,3.95mm~177.7mm Focal Length 45x optical zoomWDR(120dB) -Day/Night(ICR), 2D/3D DNR, BLC, HLC, AGC, AWB Auto tracking, Perimeter protection, Face detection, SMD PlusTripwire and intrusion, alarm triggering by target types (human and vehicle) Support Defog, ROIUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan1*Video output, Rs4857/2 ,+Alarm in/out, 1/1 Audio in/outIR Distance up to 250m, PoE IP67, IK10</p>	480,000,000
84	DH-SD6CE245U-HNI	<p>2MP 45x Starlight IR PTZ Network Camera1/2.8" 2Megapixel STARVIS™ CMOS.H.265+/H.265/H.264+/H.264 Triple-streams ,encodingMinimum Illumination:Color(0.005Lux@F1.6) ,B/W(0.0005Lux@F1.6)Max. 50/60fps@1080P ,3.95mm~177.7mm Focal Length 45x optical zoomWDR(120dB) Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWBAuto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 ,presets,8 tour, 5 pattern, Auto scan, Auto Pan1*Video output Rs4857/2 Alarm in/out, 1/1 Audio in/outIR Distance up to 250m, PoE+, IP67, IK10</p>	Call

85	SD5A245XA-HNR	<p>"2MP 45x Starlight IR WizSense Network PTZ Camera1/2.8 ;2Megapixel STARVIS™ CMOSH.265; H.265+; H.264+; H.264 MJPEG (Sub Stream)Max. 50/60 fps@1080PPan/Tilt Range :Pan: 0°–360°; Tilt: -15°–+90°Manual Control Speed Pan ,s–240°/s; Tilt: 0.1°/s–120°/sWDR(120db), HLC, BLC/0.1° ,2D/3D DNR, Rol, EIS, Defog, AWB, AGC, Privacy Masking ,Day/Night AutoAuto Tracking, SMD Plus, Intrusion Tripwire, Object Abandoned/Missing, Face DetectionUp to presets,8 tour, 5 pattern, Auto scan, Auto PanAlarm I/O 300 Audio I/O 1/1, Supports Two Way TalkFocal Length 3.95 ,2/1 :mm–177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W Lux@F1.6 0 Lux (IR on) IR distance up to 150 m, 45x 0.0005 +optical zoomONVIF Profile S&G&T, DC 24V/2.5A ± 25%; PoE ;(802.3at), Operating Temperature –40°C to +70°C IP67; IK10 TVS 6000V lightning protection; surge protection; voltage transient protection</p>	470,000,000
86	DH-SD5A232XB-HNR	<p>"2MP 32x Starlight IR WizSense Network PTZ Camera1/2.8 2Megapixel STARVIS™ CMOS32x optical zoom,Max. 50/60 fps@2MMin Illumination Color: 0.005 lux@F1.6,Focal Length ;+mm–154 mm Smart H.265+; H.265; Smart H.264 4.8 H.264BFace detection ,tracking and perimeter protection,SMD ,PLUS IR distance up to 150 m,PoE+, IP67, IK10WDR(120db) Day/Night(ICR), 3DNR, AWB, AGC, BLC</p>	407,000,000
87	DH-SD5A232XA-HNR	<p>™2Megapixel STARVIS™1/2.8 CMOSH.265+/H.265/H.264+/H.264 Triple-streams encodingMax. 50/60fps@1080P, 4.9mm~156mm 32x optical zoomMax 400°/s pan speed, 360° endless pan ,rotationWDR(120dB), Day/Night(ICR), Ultra DNR(2D/3D), BLC ,HLCSupport Defog, ROI, Auto-tracking and IVS(Tripwire Intrusion,Abandoned/Missing, Face Detection) Up to 300 ,presets,8 tour, 5 pattern, Auto scan, Auto PanAlarm 2/1 in/out Audio 1/1 in/outIR Distance up to 150m, PoE+, IP67, IK10</p>	4 07,000,000

88	DH-SD49425ZB-HNR	<p>4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor: 1/2.8" STARVIS™ CMOS1/2.8" 4Megapixel CMOS Powerful 25x optical zoom, ROM: 4GB, RAM: 1GBStarlight technology, Max.25/30fps@4M, Illuminator Number: 4Focal Length: 4.8 mm–120 mm, Field of View: H: 60.0°–2.5°; V :D: 66.7°–2.9°Min. Illumination: Color ;2.2°–30.8° 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6: 0Lux@F1.6 (IR light on)Illuminator On/Off Control: Zoom ,Prio/Manual/SmartIRPerimeter protection, Face Detection Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing ,Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC :AGC, ANR, ROI, Electronic DefogPan: 0.1°–200°/s, Tilt ,s, Presets: 300, Tour: 8 (up to 32 presets per tour)/120°–0.1° Pattern: 5, Scan: 5 IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/1</p>	267,000,000
89	SD49425XB-HNR	<p>"4MP 25x Starlight IR WizSense Network PTZ Camera1/2.8 STARVIS™ Progressive CMOSH.265+/H.265/H.264+/H.264/MJPEG (sub stream)Max.25/30fps@4M, 960P, 720P4.8mm~120mm 25x optical zoomMax 240°/s pan speed, 360° endless pan rotationWDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus ,IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright LightSupport Defog and EISUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto +PanBuilt-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE</p>	2 67,000,000
90	SD49225XA-HNR-S3	<p>"2MP 25x Starlight IR WizSense Network PTZ Camera1/2.8 2Megapixel STARVIS™ CMOS , 25x optical zoom, Min Illumination Color: 0.005 lux@F1.6Max. 25/30 fps@1080pIR distance up to 100 m , Perimeter protection,Face detection,SMD Plus,IP66Pan: 0° to 360° endless ,Tilt: –15° to ;+auto flip 180° , Pan: 200°/s; Tilt: 100°/s Smart H.265 ,90°+ H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream) Tripwire and intrusion. Support alarm triggering by ,target types (human and vehicle) WDR(120dB) ,Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB AGC</p>	220,000,000

91	SD49225XA-HNR	™2MP 25x Starlight IR PTZ AI Network Camera1/2.8" STARVIS .CMOSH.265+/H.265/H.264+/H.264/MJPEG (sub stream)Max 60fps@1080P,960P, 720P4.8mm~120mm 25x optical~1 zoomMax 240°/s pan speed, 360° endless pan rotationWDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus ,IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright LightSupport Defog and EISUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto +PanBuilt-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE	2 20,000,000
92	SD49225ZB-HNR	2Megapixel STARVIS™ CMOSPowerful 25x optical zoom "1/2.8 .Focal Length 4.8 mm–120 mmMax. 25/30 fps@1080p - Min - Illumination Color: 0.005 lux@F1.6 / B/W: 0.0005 lux / 0 lux (IR light on)IVS (Perimeter Protection) : Tripwire , intrusion / SMD ;Plus / Face Detection / Motion Detection Smart H.265+; H.265 , Smart H.264+WDR(120dB),DNR(2D/3D), BLC, HLC, AWB, AGC - Rol , Electronic DefogIR distance up to 100 m - Smart IR - 4 IR S/N Ratio ≥ 55 dBPresets 300 / Tour 8 (up to 32 presets per tour) / Pattern 5 / Scan 50Alarm I/O : 2/1 - IP66 - Power Supply VDC, 3 A - PoE+Storage : FTP/ Micro SD card (512 GB)/ NAS 12	220,000,000
93	SD59430U-HNI	,CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding "1/3 Ultra-low bit rateMax. 25/30fps@4M(2592×1520) & 50/60fps ,1080P resolutionWDR, Day/Night(ICR), Ultra DNR, Auto iris@ Auto focus4.5mm ~ 135.0mm , 30x Optical ZoomMax 400°/s pan speed, 360° endless pan rotationUp to 300 presets, 5 auto scan, 8 tour, 5 patternMicro SD card memory , 64 GBAudio In/Out, Alarm In/Out, IP66, POE+IR Distance up to 100m(AC24V)/ 80m(DC12V)Smart Detection -Tripwire Intrusion Scene Change Face Anondoned) (Missing Object	3 50,000,000

94	SD5A432XB-HNR	<p>"4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8", +4Megapixel STARVIS™ Progressive CMOS H.265+, H.264, H.265, H.264, MJPEG (Sub Stream) 3 Stream, Max :25/30fps@4MMin. Illumination Color: 0.005 Lux@F1.35, B/W Lux@F1.6, 0 Lux (IR on) 4.8 mm–154 mm Powerful 32x 0.0005 optical zoom, Max. Aperture F1.35–F4.4 Support human, motor vehicle and non-motor vehicle image capture Tripwire and intrusion. Support alarm triggering by target types (human and ,vehicle) Support filtering false alarms caused by animals :rustling leaves, bright lights, etc. Pan: 0° to 360° endless , Tilt to +90°, auto flip 180°, Pan: 0.1°–300°/s , Tilt: 0.1°–200°/s 15°– ,WDR(120), EIS, Defog, RoI, 2D DNR, 3D DNR, HLC, BLC, AWB AGC, Alarm I/O : 2/1 , Audio I/O : 1/1 ,PoE+ ,IP67; IK10; TVS V 6000</p>	440,000,000
95	DH-SD5A432GB-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS, Max. Resolution 2560 (H) × 1440 (V) Electronic Shutter Speed 1/1 s–1/30,000 s, Min Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 m (IR), Focal Length 4.8 mm–154 mm Manual Control Speed Pan: 0.1°/s–300°/s, Tilt ,s–200°/s Preset 300, Tour 8 (up to 32 presets per tour)/0.1° Pattern 5, Scan 5 Perimeter Protection, Face Detection, Auto ,Tracking, Quick Pick, SMD BLC, WDR 120 db, WB, AGC, ANR RoI, EIS, Defog Electronic, S/N Ratio ≥55 dB Storage : FTP, Micro SD card (512 GB); NAS, Alarm I/O 2/1, Audio I/O 1/1 Power Supply 24 VDC, 2.5 A (± 25%), Operating Temperature –40 °C to +70 °C</p>	460,000,000

96	SD5A432XA-HNR	<p>"4MP 32x Starlight IR WizSense Network PTZ Camera1/2.8 ,+4Megapixel STARVIS™ Progressive CMOS.H.265+, H.264 .H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max :25/30fps@4MMin. Illumination Color: 0.005 Lux@F1.35, B/W Lux@F1.35, 0 Lux (IR on)4.9 mm–156 mm Powerful 32x 0.0005 :optical zoom, Max. Aperture F1.35–F4.4Max Presets Speed Pan: 400°/s Tilt: 300°/s, Pan: 0°–360° endless ,rotationWDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC ,AWB, AGC, Day/Night Auto ICRDeep Learning, Auto Track Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm FilteringUp to presets,8 tour, 5 pattern, Auto scan, Auto PanMicro SD 300 card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile ,S&G&TIR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10 6000V lightning proof; surge protection; voltage transient protection</p>	<p>4 28,000,000</p>
97	SD5A445XA-HNR	<p>"4MP 45x Starlight IR WizSense Network PTZ Camera1/2.8 4Megapixel STARVIS™ Progressive CMOS.H.265+/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4MMin. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on)3.95 mm–177.7 mm Powerful 45x optical zoom Max. Aperture :F1.6–F4.95Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan endless rotationWDR(120), EIS, Defog, Rol,2D DNR, 3D 360°–0° ,DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICRDeep Learning ,Auto Track, Tripwire, intrusion, Object Abandoned/Missing SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm FilteringUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto PanMicro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF ,+Profile S&G&TIR distance up to 150m, DC 24 V/2.5 A, PoE IP67, IK10, 6000V lightning proof; surge protection</p>	<p>5 35,000,000</p>

98	SD6CE445XA-HNR	<p>"4MP 45x Starlight IR WizSense Network PTZ Camera1/2.8 4Megapixel STARVIS™ Progressive .CMOSH.265+/H.265/H.264+/H.264/MJPEG(Sub Stream) Max ;25/30fps@4MPMinimum Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on)3.95 mm–177.75 mm Powerful 45x optical zoom Max. Aperture -:F1.6–F4.95Pan/Tilt Range Pan: 0°–360° endless; Tilt auto flip 180° Preset Speed Pan: 300° /s; Tilt: 200° /s,90°–20° ,WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, Rol EIS, DefogDeep-learning-based auto tracking and perimeter .protectionFace detection, SMD Plus, Tripwire, Intrusion Human/Vehicle/Motor-non Motor Vehicle DetectionUp to 300 presets,8 tour, 5 pattern, Auto scan, Auto PanMicro SD card (256G), 1/1 Audio I/O, 7/2 Alarm I/O, ONVIF Profile S&G&TIR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</p>	<p>5 60,000,000</p>
99	DHI-NVR1104HS-S3/H (V2.0)	<p>& Channel IPC Input, 4K Lite H.265 NVR 1/4 Live 4 PlaybackSmart H.265+/Smart H.264+/H.265/H.264Network Bandwidth 80 Mbps for access, 80 Mbps for storage and & 60Mbps for forwarding. Up to 8MP Resolution for Preview PlaybackDecoding Capacity : 1–ch@8MP(30FPS) or ch@5MP(30FPS) or 2–ch@4MP(30FPS) or–1 ch@3MP(30FPS) or 4–ch@1080P(30FPS)Video Output 1–2 VGA/1 HDMI simultaneous video output, maximum resolution 1080P1 SATA 2.0 port, up to 8TB1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only1 RJ–45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G</p>	<p>27,000,000</p>

100	NVR2104HS-P-I	<p>Channel Compact 1U 4PoE WizSense Network Video 4 Recorder, New 4.0 user interface H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch 1 VGA/1 HDMI simultaneous video output, HDMI 4K, non-simultaneous video output is also supported on 1080p 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 :face databases and 5,000 face images Max. decoding capability 1080P@30fps. Supports adaptive decoding Network×4 Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Resolution 12M/8M/5M/4M/3M/2M/720P/D1 AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6- channel 1080p@30 fps AI -enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2 channel 4MP@30 fps; 4-channel 1080p@30 fps 4 PoE Ports, 1 ,SATA port, up to 8 TB, 1 front USB 2.0 port, 1 rear USB 2.0 port RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE power 1 supply (10/100 Mbps)</p>	60,000,000
101	NVR2104HS-4KS2	<p>channel IP camera input H.265/H.264 codec decoding Max 4 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>	32,500,000
102	NVR2104HS-P-4KS2	<p>channel IP camera input, H.265/H.264 codec decoding Max 4 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA ,HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port P2P support</p>	42,500,000

103	DHI-NVR1108HS-S3/H	& Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live 8 PlaybackSmart H.265+/Smart H.264+/H.265/H.264Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 & Mbps for forwarding. Up to 8MP Resolution for Preview PlaybackDecoding Capacity : 1–ch@8MP(30FPS) or ch@5MP(30FPS) or 2–ch@4MP(30FPS) or–1 ch@3MP(30FPS) or 4–ch@1080P(30FPS)Video Output 1–2 VGA/1 HDMI simultaneous video output, maximum resolution 1080P1 SATA 2.0 port, up to 8TB1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only1 RJ–45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G	33,500,000
104	NVR2108HS-4KS2	channel IP camera input, H.265/H.264 codec decoding Max 8 80Mbps incoming bandwidthUp to 8Mp resolution preview&playbackUp to 1ch@8MP/4ch@1080P decodingHDMI/VGA simultaneous video outputSupport 1 SATA HDD up to 6TB, 2 USB2.0100 Mbps Network Card, P2P support	40,000,000
105	NVR2108HS-8P-4KS2	channel IP camera input, H.265/H.264 codec decoding Max 8 80Mbps incoming bandwidthUp to 8Mp resolution preview&playbackUp to 1ch@8MP/4ch@1080P decodingHDMI/VGA simultaneous video outputSupport 1 SATA ,HDD up to 6TB, 2 USB2.0100 Mbps Network Card, 8Port PoE P2P support	56,500,000
106	NVR2108HS-S3	Channel Lite Series, Compact 1U 1HDD Network Video 8 RecorderSmart H.265+/H.265/Smart H.264+/H.264 decoding formatMax. decoding capability: 6 × 1080p@30 fps. Supports adaptive decodingAI by camera: perimeter protection,and SMD PlusMulti-channel Playback Up to 8 channels, HDD Interface 1 × SATA port, up to 16 TB Audio Input/Out : 1/1 , Network Port 1 RJ-45, 10/100 MbpsPower Supply 12 VDC, 1.5 A	43,000,000

107	NVR2108HS-I2	Channel Compact 1U 1HDD WizSense Network Video 8 RecorderSmart H.265+/H.265/Smart H.264+/H.264/MJPEG .decoding formatMax. decoding capability: 6 × 1080p@30 fps Supports adaptive decoding 1-channel face detection and recognition (AI by NVR)1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR)AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1Power Supply 12 VDC, 1.5 A, Operating Temperature –10 °C to +55 °C	58,000,000
108	NVR2108HS-I	Channel 12MP WizSense NVR 1/4/8 Live & PlaybackSmart 8 H.265+/H.264+/MJPEGNetwork Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwardingAi Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch : 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch -2MP@30fpsHDMI/VGA Simultaneous Max Output 4K, non Simultaneous Max output 1080p1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Libraryor 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification1 SATA II port, up to 8TB1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G	58,000,000
109	NVR4108HS-4KS2	channel IP camera input1/4/8/9 channel Live Preview, 8CH 8 Playback H.265/H.264 codec decodingMax 80Mbps incoming bandwidthUp to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video outputSupport 1 SATA HDD up to 6TB, 2 USB2.0100 Mbps Network Card, P2P support	47,000,000
110	DHI-NVR2216-4KS2	Channel 4K Lite H.265 NVR 1/4 Live & PlaybackDual-core 16 embedded processor, H.265/H.264 codec decodingMax 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output2 SATA III Ports, up to 6TB capacity for each, Total 12TB1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only RJ-45 port (1000Mbps), P2P Support 1	62,000,000

111	NVR2116HS-I	& Channel 12MP WizSense NVR 1/4/9/16 Live 16 PlaybackSmart H.265+/H.264+/MJPEGNetwork Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwardingAi Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fpsHDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p1ch Face Detection and Face Recognition Ai by NVR up to Face Libraryor 2ch Perimeter Ai By NVR or 4ch SMD Plus 5000 Ai by NVR, Human/Vehicle Classification1 SATA II port, up to ,8TB1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port ,rear USB 2.0 port1 RJ-45 port (1000Mbps), P2P Support 1 ONVIF (profile T/profile S/profile G)	73,000,000
112	NVR2116HS-I2	Channel Compact 1U 1HDD WizSense Network Video 16 RecorderSmart H.265+/H.265/Smart H.264+/H.264/MJPEG ;decoding formatNetwork Bandwidth: AI off: Access: 144 Mbps ;Storage: 144 Mbps; Forward: 72 MbpsAI on: Access: 72 Mbps ;Storage: 72 Mbps; Forward: 36 MbpsResolution: 12MP; 8MP 5MP; 4MP; 3MP; 2MP; 720p; D1Decoding Capability: AI -disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2 channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fpsAI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps1 × VGA, 1 × HDMI (simultaneous) 4K Output1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR);AI by camera: Face detection and recognition, perimeter protection, and SMD Plus1 SATA II port, up to 10TB1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)	72,000,000

113	DHI-NVR2216-I	& Channel 12MP WizSense NVR 1/4/9/16 Live 16 PlaybackSmart H.265+/H.264+/MJPEGNetwork Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwardingAi Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fpsHDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p1ch Face Detection and Face Recognition Ai by NVR up to Face Libraryor 2ch Perimeter Ai By NVR or 4ch SMD Plus 5000 Human/Vehicle Classification2 SATA 2.0 port, up to 9Ai by NVR ,8TB each, Total 16TB1 front USB 2.0 port, 1 rear USB 2.0 port ,1ch Audio I/O for Two Way Talk Only1 RJ-45 port (1000Mbps) P2P Support, ONVIF (profile T/profile S/profile G)	90,000,000
114	NVR4116HS-4KS2	Channel Compact 1U 4K&H.265 Lite Network Video 16 RecorderSmart H.265+/Smart H.264+/H.265/H.264; H.265 auto switchMax 80Mbps Incoming BandwidthUp to 8MP Resolution for Preview and Playback8-channel ;decoding@1080p (30 fps)AI by Camera: Perimeter protection SMD Plus; people counting; heat map target classification (human, vehicle)HDMI(4K)/VGA simultaneous video output1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 portAudio I/O 1/1 for Two Way Talk Only100 Mbps Network Card, P2P support	69,000,000
115	NVR4116HS-4KS2/L	channel IP camera input, 16 channel Live Preview Smart 16 H.265/H.264 codec decodingMax 80Mbps incoming bandwidthUp to 8MP Resolution for Preview and Playback ch@720P decoding capacity Support SMD Plus by Camera-16 HDMI(4K)/VGA simultaneous video outputSupport 1 SATA HDD up to 8TB, 2 USB2.0100 Mbps Network Card, P2P support	69,000,000

116	NVR4216-4KS2/L	channel IP camera input, 16 channel Live PreviewSmart 16 H.265+/H.264+ codec decodingMax160Mbps incoming .bandwidthMax. decoding capability: 8 × 1080p@30 fps Supports adaptive decoding 8–ch@1080P decoding capabilityHDMI(4K)/VGA simultaneous video outputAI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0)4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)	90,000,000
117	NVR4216-16P-4KS2/L	channel IP camera input, 16 channel Live PreviewSmart 16 H.265+/H.264+ codec decodingMax160Mbps incoming .bandwidthMax. decoding capability: 8 × 1080p@30 fps Supports adaptive decoding 8–ch@1080P decoding capabilityHDMI(4K)/VGA simultaneous video outputAI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 × front USB2.0 , 1 × back USB2.0)4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, 16 Port PoE, ONVIF(profile T/S/G)	1 51,000,000
118	NVR4232-4KS2/L	Channel 1U 2HDDs Network Video RecorderSmart 32 H.265+/H.264+ codec decodingMax160Mbps incoming bandwidthMax. decoding capability: 8 × 1080p@30 :fpsHDMI(4K)/VGA simultaneous video outputAI by Camera ,Face detection with attributes, perimeter protection, IVS people counting, heat map, and SMD, Human & Vehivle Classification2 SATA III ports, up to 10 TB each port, 1 × front ,USB2.0; 1 × back USB2.04 Alarm Input, 2 Relay Output 1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)*1	108,000,000
119	NVR4232-4KS2	channel IP camera input, 16 channel Live Preview 32 H.265/H.264 codec decodingMax 200Mbps incoming bandwidthUp to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video outputSupport 2 SATA HDD up to 6TB2 USB Ports (1 USB2.0, 1 USB3.0)4 Alarm Input, 2 Relay Output1*1000Mbps Network Card, P2P support	1 08,000,000

120	DHI-NVR5232-4KS2(V2.0)	32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.0)Smart H.265+/H.265/H.264+/H.264/MJPEG decodingMax 320Mbps incoming bandwidth, Up to 12Mp-resolution preview & playback Max 4-ch@8MP(30fps), 16 ch@1080P(30fps) decoding1*HDMI(4K)/1*VGA simultaneous video output2*SATA HDDs(10 TB for each HDD), 2 USB(1 ,USB3.0,1 USB2.0)1*1000 Mbps Network Card, RS232 RS485,4/2 Alarm In/out , P2P Support	1 79,000,000
121	NVR4432-4KS2/I	Channel 1.5U 4HDDs WizSense Network Video 32 RecorderSmart H.265+/H.265/Smart H.264+/H.264/MJPEGAccess, storage or forwarding at 256 Mbps, Max. decoding capability: 10 × 1080p@30 fps Face detection; face recognition; perimeter protection,SMD PlusMulti-channel Playback Up to 16 channelThe maximum HDD capacity 4 SATA ports, up to 10 TBAlarm Input 16,Alarm Output 42 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port	1 95,000,000
122	NVR5432-4KS2(V2.0)	32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.0) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decodingMax 320Mbps incoming bandwidthUp to 12Mp-resolution preview & playbackMax 4-ch@8MP(30fps), 16 ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network CardRS232, RS485,16/6 Alarm In/out , P2P Support	2 55,000,000
123	DHI-NVR5464-4KS2(V2.0)	64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.0)Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decodingMax 320Mbps incoming bandwidth, Up to 12Mp-resolution preview & playbackMax 4-ch@8MP(30fps), 16 ch@1080P(30fps) decoding2*HDMI/2*VGA simultaneous video output4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0)Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support	3 00,000,000

124	NVR5832-4KS2	channel IPC input, 32 Channel Live 32 Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10	3 30,000,000
125	DHI-NVR5864-4KS2(V2.0)	Channel 2U 4K & H.265 Pro Network Video Recorder 64 (V2.0) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp -resolution preview & playback Max 4-ch@8MP(30fps), 16 ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 ,USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support	4 40,000,000
126	NVR608-32-4KS2	Intel Dual-core Processor, 32 channel IPC input, 32 Channel :Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen H.265/H.264/MJPEG codec decoding, Max (1/4/8/9/16 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output	3 75,000,000
127	NVR608-64-4KS2	Intel Quad-core Processor 64 channel IPC input, 32 Channel Live :Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen H.265/H.264/MJPEG codec decoding Max ,(1/4/8/9/16 384Mbps incoming bandwidth Up to 12Mp resolution preview playback 2HDMI/VGA simultaneous video output 8 SATA III & ports, up to 10 TB for a single HDD,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 , USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 RS485, 16 Alarm In , 8 Relay Output	6 50,000,000

128	DHI-NVR608-128-4KS2	Channel 2U Ultra 4K H.265 Network Video Recorder (1st 128 (Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16 H.265/H.264/MJPEG codec decodingMax 384Mbps incoming bandwidthUp to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA PortSupport Raid 0/1/5/10Support Smart Tracking and Intelligent Video4 USB(2 ,USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485 Alarm In/Output 16/8	7 60,000,000
129	ESS1508C	2U standard 19-inch rack caseConnect master device via eSATA or USB1 eSATA port transmission speed up to 3Gbps1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection	1 16,000,000
130	PFS3006-4ET-36	Port Fast Ethernet Switch with 4-Port PoE4 PoE ports with-6 -Mbps Base-TX2 uplink ports with 10/100Mbps Base 10/100 TXPort1-4 ≤30W, whole PoE budget ≤36WSupport 802.3af and 802.3at standardsOperatingTemperature: -10°C to 55°Csupport 250 m long distance PoE transmissionSupport+ PoE watchdogSwitching Capacity 1.2 Gbps, Packet Forwarding Rate 0.89 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3XESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV	22,500,000
131	PFS3106-4ET-60 (V2.0)	Port PoE Switch (Unmanaged)4 × RJ-45 10/100 Mbps (PoE)1-4 RJ-45 10/100/1000 Mbps (Uplink)1 × SFP 100/1000 Mbps × (Uplink)Intelligent PoE, Hi-PoE 60W (Orange Port), PoE watchdog, 250 m long distance PoE transmissionWide operating temperature: -30°C to +65°C (-22°F to 149°F)Switching Capacity 6.80 Gbps, Packet Forwarding Rate+ Mpps, Packet Buffer Memory 1 Mbit, MAC Table Size 8K 3.57 ;Communication Standard IEEE802.3; IEEE802.3u; IEEE802.3X ;IEEE 802.3ab; IEEE 802.3zPoE Standard IEEE802.3af IEEE802.3at; Hi-PoE, 250 m long distance PoE transmissionStatics Protection Air discharge:15kV Contact discharge:8kV, Thunder-proof Common mode:4kV Differential mode:2kV	41,000,000

132	PFS3010-8ET-65	-Port Fast Ethernet Switch with 8-Port PoEPort 1-8: 8 × RJ-10 Mbps (PoE)Port 9-10: uplink with 10/100 10/100 45 MbpsSupport 802.3af and 802.3at standardsSupport 250 m long distance PoE transmissionSupport PoE watchdogPort1-8 ,30W, whole PoE budget ≤65WSwitching Capacity 2.0 Gbps≥ ,Packet Forwarding Rate 1.49 Mpps , MAC Table Size 2K Jumbo Frame 2048 byte ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV	32,150,000
133	PFS3110-8ET-96 (V2.0)	Port Unmanaged Desktop Switch with 8 Port PoEPort 1-8: 8-10 RJ-45 10/100 Mbps (PoE)Port 9: 1 × RJ-45 10/100/1000 × Mbps (uplink)Port 10: 1 × SFP 1000 Mbps (uplink)Communication Standard IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE 802.3ab/IEEE /802.3zPoE Standard IEEE802.3af/ IEEE802.3at/ Hi-PoE IEEE802.3btPort 1-2 ≤ 90 W, Port 3-8 ≤ 30W, total≤ 96 ,WIntelligent PoE, BT 90W, Long distance PoE, PoE watchdog Wide working temperatureLightning Protection Air discharge:8kV Contact discharge:6kV, ESD Protection Common mode:4kV Differential mode:2kV	59,500,000
134	PFS3218-16ET-135	Layer 2 PoE switch2*10/100/1000 Base-T (Combo port)2*1000 ,Base-X (Combo port)16 × RJ45 10/100 MbpsPort 1-2≤60W ,Port 3-16≤30W, total≤135WIEEE802.3, IEEE802.3u ,IEEE802.3x, IEEE802.3ab, IEEE802.3zPoE Standard IEEE802.3af ,IEEE802.3at, Hi-PoEIntelligent PoE, PD Alive(PoE Watchdog) Long Distance PoE Transmission, Smooth TransmissionWide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port IsolationSwitching Capacity 7.2 Gbps, Packet Forwarding Rate Mpps, Packet Buffer Memory 4 Mbit, MAC Table Size 5.3568 ,8K ESD Air discharge: 8kV Contact discharge: 6kV Thunderproof Common mode: 4kV Differential mode: 2kV	102,000,000

135	PFS3226-24ET-240	Layer 2 PoE switch2*10/100/1000 Base-T (Combo port)2*1000 Base-X (Combo port)24 × RJ45 10/100MbpsIntelligent PoE, PD ,Alive(PoE Watchdog), Long Distance PoE Transmission Smooth TransmissionWide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port IsolationPort1/2 support Hi-PoE ,(60W), PoE+, PoEPort 1-2≤60W, Port 3-24≤30W ,total≤240WIEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab IEEE802.3zPoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE Switching Capacity 8.8Gbps, Packet Forwarding Rate 6.5472 MppsMAC Table Size 8KESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV	131,000,000
136	PFT1300	PoE Extender1*10/100 Base-T PoE power receiving port1*10/100 Base-T PoE power supply port, supply power for ,the next extender1*10/100 Base-T PoE power supply port supply power for IPCSupport passive PoE cascade power supply and Ethernet data exchangeSupport IEEE 802.3af/at standard ,power supply IP Cameraable to cascade level 2 PoE Extender connect to 3 IPC (power consumption <=8W), max transmission distance 300m	6 650,000
137	PFM700	Channel HDMI Transmission 1* Signal*1080P/1080I/720P/576P/576I/480P/480I Resolution Output Signal , *60M (max)Transmission Distance *Input voltage DC5V*Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3	18,700,000
138	NKB1000	Keyboard to Control : Dahua High Speed Dome (all models)Dahua Standalone DVR , Dahua Network High Speed ,DomeNetwork Video Server, Connection : RS485, RS422, USB RS232 & NetworkThree Dimensional Joystick Control of PTZ & FunctionsPreset Position, Auto Scan, Auto Pan, Auto Tour Pattern Control, On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB	12,200,000