

ل رد

ت

(ج) د

1 PSD81602-A360	<p>8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10</p>		Call
2 PSD8802-A180	<p>4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10</p>		Call
3 PFW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
4 PFW8601-A180	<p>3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.6mm fixed lens, Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
5 PDBW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
6 IPC-EBW8842-AS	<p>8MP IR Fisheye WizMind Network Camera 8MP 1/1.7" CMOS image sensor, low luminance, and high definition image Min. Illumination 0.01 Lux@F2.0 (Color, 30 IRE), 0.001 Lux@F2.0 (B/W, 30 IRE), 0 Lux (Illuminator on) Focal Length 1.85mm, Field of View Horizontal: 185°; Vertical: 180° Outputs max. 8M (3280 × 2480) @25/30 fps Built-in IR LED, and the max. illumination distance is 10 m IVS: Intrusion, tripwire, heat map, people counting, Smart Search DWDR, HLC, BLC, AWB, AGC, 3D DNR, ROI, Defog, ICR, SMART H.264 +/H.265 Built-in Dual Array Mic and Speaker, Audio in/out 1/1, Alarm in/out 2/2, Micro SD 256GB 12V DC/PoE, IP67 and IK10 protection</p>		295,000,000
7 ITC237-PW1B-IRZ	<p>دور. ANPR اقلات شخ ص لامناسب برای ورودی های ارکینگ 2 Megapixel Full HD WDR Access ANPR Camera -Embedded with LPR algorithm inside the camera -plate cutout, snapshot preview, recording -White list database, 1ch relay out to control the barrier performance for outdoor applications- 1/2.8" 2Megapixel progressive scan CMOS H.265/H.264M/H.264H/H.264B dual-stream encoding 25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC Micro SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE</p>		165,000,000

8	IPC5831EP-ZE	  <p>1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) 2.7mm~12mm motorized lens, Max. Aperture F1.6 WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory, 128 GB, 1/1 Audio In/Out, 2/1 Alarm In/Out Max. IR LEDs Length 50m, Smart IR, IP67, IK10, PoE (Tripwire) Intrusion Object Abandoned/Missing Face)</p>	 <p>124,000,000</p>
9	IPC-HFW2849T-AS-IL	 <p><b>NEW</b></p> <p>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" Progressive CMOS image sensor, 8MP(3840×2160)@20fps, (2688×1520)@25/30fps Min. Illumination 0.008 Lux@F1.6 (Color, 30 IRE) 0.0008 Lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) Illumination Distance up to 60 m (195.85 ft) (IR) up to 50 m (164.04 ft) (Warm light) Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate Intelligent monitoring: Intrusion, tripwire, SMD Plus RoI, WDR 120db, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, IK10, Metal Case</p>	 <p>89,000,000</p>
10	IPC-HFW2831T-ZAS-S2	 <p>8MP Lite IR Vari-focal Bullet Network Camera 8MP, 1/2.7" Progressive CMOS low illuminance 0.008 Lux@F1.5 high image definition 8MP@15fps &amp; 4MP@25/30fps 2.7-13.5mm Motorized Lens SMART H.264+/H.265+, (MJPEG in Sub Stream) IVS Intrusion, Tripwire Micro SD 256GB, 1ch Audio I/O, 1ch Alarm I/O WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, RoI, Smart illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p>	 <p>99,000,000</p>
11	HFW2831T-ZS-S2	<p>8MP Lite IR Vari-focal Starlight Bullet Network Camera 1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of Interest, Voltage Detection 2.7 mm~13.5 mm Motorized fixed lens Max. IR LEDs Length 60m, Micro SD card memory , 256 GB IP67, PoE, Smart Detection (Tripwire) Intrusion)</p>	 <p>98,000,000</p>
12	IPC-HFW2831TP-AS-S2	 <p>8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor max. 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps Smart H.265+/ Smart H.264+, H.265; H.264; H.264B; MJPEG (only supported by the sub stream) Built-in IR LED, max IR distance: 80m, 3.6mm Fixed Lenz Min. Illumination 0.009 Lux@F2.0 ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec WDR(120db), 3D NR, HLC, BLC, AGC, AWB, RoI, Smart IR Intrusion, tripwire Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE power support supply, IP67, IK10</p>	 <p>73,000,000</p>
13	IPC-HFW2831S-S2	 <p>8MP Lite IR Fixed-focal Bullet Network Camera 1/2.7" Progressive CMOS image sensor, low illuminance, high image definition Illumination 0.009 Lux@F2.0 Smart H.264+/H.265+, MJPEG, high compression rate, ultra-low bit rate 8MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps WDR (120 db), 3D DNR, HLC, BLC, AGC, AWB, RoI, Smart IR Intrusion, tripwire, SD Card 256GB, IP67, PoE</p>	 <p>67,000,000</p>
14	IPC-HFW1830SP-0360B-S6	 <p>8MP 8MP 1/2.7" CMOS Entry IR Fixed-focal Bullet Network Camera Outputs max. 8MP@15fps, supports 2688 × 1520 (2688 × 1520) @25/30 fps Illumination 0.004 Lux@F2.0 (B/W, 30 IRE) H.265+&amp;H.264+ high compression rate, and ultra-low bit rate. WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Built-in MIC 3.6mm fixed lens, Built-in IR LED, and the max. illumination distance is 30 m. 12 V DC/PoE power supply, IP67</p>	 <p>58,000,000</p>
15	HFW2531TP-ZS	 <p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 15fps@5M(2592×1944)&amp;25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB, Max IR LEDs Length 60m ,Smart IR IP67, PoE, Smart Detection (Tripwire) Intrusion)</p>	 <p>86,000,000</p>
16	DH-IPC-HFW5449T1-ZE-LED	  <p>4MP 1/1.8" CMOS image sensor, Full-color Vari-focal Warm LED Bullet WizMind Network Camera Outputs max. 4MP (2688 × 1520) @30 fps, Focal Length 2.7 mm~12 mm Min. Illumination 0.0005 Lux@F1.0, S/N Ratio &gt; 56 dB Built-in warm illuminator, and the max. illumination distance : 70 m ROI, SMART H.264+/H.265+, flexible coding, WDR 140db , 3D NR, HLC, BLC IVS (Perimeter Protection) : Tripwire; intrusion; fast moving, loitering detection, people gathering; parking detection, Face Detection, People Counting, Intelligent Search Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card, <b>built-in Mic</b> and speaker 12V DC/PoE power supply, ePoE, IP67 protection, SMD 3.0</p>	 <p>165,000,000</p>

17	HFW5442EP-ZE-0832	<p>4MP Pro AI IR Vari-focal, WizMind 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688x1520), 50/60fps@2Mp(1920 x 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lens, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas Independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p> <p>  <b>Wiz Mind</b></p>	 140,000,000
18	IPC-HFW5241E-Z5E	<p>2MP IR Vari-focal Bullet WizMind Network Camera 2MP 1/2.8" Progressive STARVIS™ CMOS low illuminance 0.0015 Lux@F1.3 high image definition 2MP@25/30fps 7-35mm Motorized Lens SMART H.264+/H.265+ IVS: Tripwire; intrusion; fast moving (with accurate classification of vehicle and human); loitering detection; people gathering; parking detection Face Detection with Face Attributes and Face Expression People Counting with Queue Management Micro SD card 256 GB, 1ch Audio I/O, 2/1 Alarm I/O WDR (120db), EIS, Defog, 3D DNR, HLC, BLC, AWB, AGC, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, IK10, 4 IR LEDs 120m Distance, Onvif Profile S/G/T</p> <p>  <b>Wiz Mind</b></p>	 122,000,000
19	IPC-HFW5541E-ZE-S3	<p>5MP IR Vari-focal Bullet WizMind Network Camera 5-MP (2960 x 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (illuminator on 60m) 2.7 mm~13.5 mm Motorized Lens, Field of View H: 114°~32°; V: 58°~17°; D: 138°~36° Smart H.265+; Smart H.264+, AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 ( Less false alarm, longer detection distance ) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, Rol, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB IP67 and IK10 protection</p> <p>  <b>Wiz Mind</b></p>	 155,000,000
20	DH-IPC-HFW4431TP-S4	<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>	 55,200,000
21	DH-IPC-HFW3849T1-AS-PV-S3	<p>8MP Smart Dual Illumination Active Deterrence Fixed-focal Bullet WizSense Network Camera 1/2.8" CMOS image sensor, low illuminance, high image definition Outputs max. 8 MP (3840 x 2160)@25/30 fps Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm illuminator, and the max. illumination distance: 30 m Intrusion, tripwire (support the classification and accurate detection of vehicle and human) WDR 120db, 3D NR, HLC, BLC, digital watermarking, Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256G SD card; <b>Dual Built-in Mic</b>; 1-ch speaker 12 VDC/PoE power supply, IP67 protection, Sound and light alarm (red and blue lights) SMD 3.0, One-click arming/disarming through alarm input</p> <p>  <b>Wiz Sense</b></p>	 118,000,000
22	IPC-HFW3849T1-AS-PV-S4	<p>8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 8 MP (3840 x 2160)@25/30 fps, H.265 codec, high compression rate, ultra-low bit rate Min. Illumination 0.004 lux@F1.0 (Color, 30 IRE), 0.0004 lux@F1.0 (B/W, 30 IRE), 0 lux (illuminator on) Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m IVS: Intrusion, Tripwire, SMD 4.0, Quick Pick, Ai SSA, Ai Coding, <b>Dual Built-in Mic</b>, Built-in Speaker, Audio in/out 1/1, Alarm Input 1 channel in: 5mA 3V~5 VDC, Alarm Output 1 channel out: 300mA 12 VDC, Micro SD 256G, support two-way talk Power Supply 12V DC/PoE (802.3af), IP67 protection, One-tap arming/disarming through alarm input, Sound and light alarm (red and blue lights)</p> <p>  <b>Wiz Sense</b></p>	 119,000,000
23	DH-IPC-HFW3449EP-AS-LED-3.6	<p>4MP Full-color WDR IR Mini Bullet Network Camera 1/2.7" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p> <p></p>	 66,300,000

24	DH-IPC-HFW3449EP-AS-LED-2.8	<p>4MP Full-color WDR IR Mini Bullet Network Camera            1/2.7" 4Megapixel progressive CMOS            2.8mm fixed lens            25/30fps@4Mp(2688×1520)            H.265/Smart H.265+/H.264/Smart H264+ triple-stream encoding            IVS(Tripwire, Intrusion, Recognition of vehicle and people, SMD Plus)            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC            Micro SD memory 256GB            Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p> 		66,300,000
25	HFW3441TP-ZS-27135	<p>4MP IR Vari-focal Bullet WizSense Network Camera            1/3"4Megapixel progressive CMOS            Min. Illumination:0.005 Lux@F1.5            2.7 mm~13.5 mm Motorized lens            25/30fps@4Mp(2688×1520)            SMART H.264+/H.265+ triple-stream encoding            IVS(Tripwire; intrusion (Recognition of human and vehicle))            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI            Micro SD memory 256GB            Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p> 		93,000,000
26	IPC-HFW2849S-S-IL	<p>8MP Smart Dual Light 2.8mm Fixed-focal Bullet WizSense Network Camera            8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image            Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps            Min. Illumination 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on)            Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m            WDR 120db, BLC, HLC, AWB, AGC, RoI, 3D DNR, ICR, Smart Illumination            IVS: Intrusion, Tripwire, SMD Plus, Smart Search            Built-in Mic, Micro SD 256GB            12 VDC/PoE (802.3af), IP67 Protection,</p>  		70,000,000
27	IPC-HFW2841T-ZS	<p>8MP IR Vari-focal Bullet WizSense Network Camera            8-MP 1/2.7" Progressive CMOS image sensor 8MP(3840 × 2160)@20fps, (2688 × 1520)@25/30fps            Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate            Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) 0.0008 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on)            Built-in IR LED, and the max. illumination distance is 60 m            WDR 120db, BLC, HLC, AWB, AGC, RoI, 3D DNR, ICR, Smart Illumination            Intelligent monitoring: Intrusion, tripwire, SMD Plus            Built-in Mic, Micro SD 256GB, 12 VDC/PoE, IP67, IK10</p> 		1,120,000,000
28	IPC-HFW2549T-AS-IL	<p>5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera            5-MP 1/2.7" Progressive CMOS image sensor 5MP(2960 × 1668)@20fps, (2688 × 1520)@25/30 fps            Smart H.265+; Smart H.264+ high compression rate, ultra-low bit rate            Focal Length 2.7 mm~13.5 mm            Min. Illumination 0.007 lux@F1.6 (Color, 30 IRE) 0.0007 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)            Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m            WDR, RoI, HLC, BLC, AWB, AGC, 3D DNR, Smart illumination            Intelligent monitoring: Intrusion, tripwire, SMD Plus            Alarm in/out 1/1, Audio in/out 1/1, Built-in Mic, Micro SD 256GB            12 VDC/PoE, IP67, IK10, Metal Case</p>  		78,000,000
29	IPC-HFW2449S-S-LED	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera            4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image            Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps            H.265 codec, high compression rate, ultra-low bit rate            Min. Illumination :0.005 lux@F1.0            Built-in warm light/IR LED, the max. illumination distance is 30 m            ROI, SMART H.264+/H.265+, flexible coding            Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking            Intrusion, tripwire (support the classification and accurate detection of vehicle and human)            Supports max. 256 G Micro SD card, built in MIC            12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.</p>  		49,500,000
30	DH-IPC-HFW2449S-S-IL	<p>4MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera            4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image            Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps            H.265 codec, high compression rate, ultra-low bit rate            Min. Illumination :0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on)            Built-in warm light/IR LED, the max. illumination distance is 30 m            ROI, SMART H.264+/H.265+, flexible coding            Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking            Intrusion, tripwire (support the classification and accurate detection of vehicle and human)            Supports max. 256 G Micro SD card, built in MIC            12 VDC/PoE power supply, easy for installation, IP67 protection, SMD Plus.</p>  		49,500,000
31	IPC-HFW2441S-S	<p>4MP IR Fixed-focal Bullet WizSense Network Camera            4-MP 1/2.9" Progressive CMOS image sensor, Outputs 4MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps            Min. Illumination 0.006 Lux@F1.6(Color,30IRE) 0.0006 Lux@F1.6(B/W,30IRE) 0 lux (Illuminator on)            H.265 codec, high compression rate, ultra-low bit rate            Built-in IR LED, and the max. illumination distance is 30m            RoI, SMART H.264+/H.265+, WDR 120db, 3D NR, HLC, BLC, AWB, AGC, 3D DNR            Intelligent monitoring: Intrusion, tripwire, SMD            Micro SD card 256GB, built-in MIC, 12 VDC/PoE, IP67, Metal Case</p>  		43,000,000

Product Details					
<b>4MP IR Vari-focal Bullet WizSense Network Camera</b>					
32	DH-IPC-HFW2441T-ZS	 	Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 ,(2560 × 1440)@25/30 fps Min. illumination, 0.008 lux@F1.5 (Color, 30 IRE), 0.0008 lux@F1.5 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate, Focal Length 2.7 mm~13.5 mm Built-in IR LED, and the max. illumination distance is 60 m ROI, SMART H.264+/H.265+, flexible coding, WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) 256G SD card, <b>built-in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67, IK10 (optional) protection, SMD Plus		84,000,000
33	IPC-HFW2439SP-SA-LED-0360B-S2		4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illumination 0.004 Lux@F1.0 high image definition 4MP@25/30fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/G/T		46,200,000
34	HFW2431TP-AS-S2		4MP Lite IR Fixed-focal Bullet Network Camera,1/3" CMOS image sensor Outputs max. 4MP (2688 × 1520) @20 fps, and supports 2560×1440 (2560 × 1440) @25/30 fps Built-in IR LED, max IR distance: 80 m, Intelligent detection: Intrusion, tripwire H.265; H.264; H.264B; MJPEG(only supported) WDR(120 dB), 3D NR, HLC, BLC, digital watermarking Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 GB Micro SD card 12V DC/POE , IP67 protection, IK10 protection (optional)		56,500,000
35	HFW2431TP-ZS-S2		4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. illumination:0.008 Lux@F1.5, 2.7~13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, max IR distance:60 m, Smart IR, IP67, PoE		73,500,000
36	IPC-HFW1431S1-S4-S5		4MP Entry IR Fixed-focal Bullet Netwok Camera 4MP, 1/3" Progressive CMOS low illuminance 0.03 Lux @ F2.0 high image definition 4MP@25/30fps 3.6mm fixed lens, Smart H.265+/H.264+ WDR(120db), Rol, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination 12V, PoE, IP67, 1 IR LEDs 30m Distance, ONVIF (Profile S/Profile G/Profile T)		31,500,000
37	HFW1431SP-0360B-S4		4MP Entry IR Fixed-focal Bullet Netwok Camera 1/3"4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. illumination:0.03 Lux@F2.0, 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR, IP67, PoE		37,000,000
38	HFW3541EP-AS	 	5MP IR Fixed focal Bullet WizSense Network Camera 1/2.7" CMOS image sensor,Outputs max. 5MP (2592 × 1944) @20 fps H.265 codecSMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking, Min illumination 0.0005 Lux@F1.6 (B/W, 30IRE) 12V DC/POE IP67 SMD Plus Supports max. 256 G Micro SD card, built-in Mic		Call
39	IPC-HFW3549T1P-AS-PV		5-MP 1/2.7" CMOS image sensor, low luminance, Smart Dual Illumination Min. Illumination : 0.003 lux@F1.0 (Color, 30 IRE) / 0.0003 lux@F1.0 (B/W, 30 IRE) / 0 lux (illuminator on) Lens Fixed-focal 3.6 mm , 15.6 m Recognize & 7.8 m Identify, Illumination Distance : 30 (2 IR LED) / 30 m (2 warm light) AI H.265, AI H.264, Smart H.265+, Smart H.264+, <b>Built-in MIC</b> Main stream: 2880 × 1620 or 2960 × 1668 @20fps / 2688 × 1520 @ (30 fps) WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol(4 years), Smart Illumination, Defog, Scence Self-adaption Storage : FTP, SFTP, Micro SD card (support max. 256 G), NAS ROM : 128MB, RAM : 512MB, S/N Ratio > 56dB , Sound and Light Alarm, Active Deterrence, IVS (Tripwire, intrusion), SMD 4.0, Smart Search, Quick Pick, AI SSA Audio In/out : 1/1 , Alarm in/out : 1/1, RJ-45 (10/100 Base-T) , 3.3 W (12 VDC); 4.4 W (PoE), IP67		99,500,000
40	HFW3549EP-AS-LED-0360B	 	SMP Full-color Fixed-focal Warm LED Bullet WizSense Network Camera SMP, 1/2.7" CMOS image sensor low illuminance 0.003 Lux@F1.0 SMP@20 fps, 4MP@25/30 fps, 3.6mm Fixed lens SMART H.264+/H.265+, IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, Built-in warm light, max. illumination distance: 30 m, Onvif Profile S/G/T		73,500,000

41	IPC-HFW3541TP-ZS-27135	<p>5MP IR Vari-focal Bullet WizSense Network Camera          5MP, 1/2.7" Progressive CMOS          0.005 Lux@F1.5 (Color, 30IRE), 0.0005 Lux@F1.5 (B/W, 30IRE), 0 Lux (Illuminator on)          high image definition 5MP@20fps          2.7-13.5mm Motorized Lens          SMART H.264+/H.265+ 3 Streams          IVS Intrusion, Tripwire, Accurate Human/Vehicle Classification, SMD Plus          Micro SD 256GB          WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch          12V, PoE, IP67, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p> <p><b>STARLIGHT Wiz Sense</b></p>	 111,000,000
42	IPC-HFW2531TP-AS-S2	<p>SMP Lite IR Fixed-focal Bullet Network Camera          5MP, 1/2.7" Progressive CMOS          low illuminance 0.008 Lux@F1.6          High image definition 5MP@20fps, 3.6mm fixed Lens          SMART H.264+/H.265+, IVS Intrusion/Tripwire          1ch Alarm I/O, 1ch Audio I/O, Micro SD 256GB          WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, Rol, Smart Illumination, Day/Night ICR Auto Switch          12V, PoE, IP67, IK10, IR LED 80m Distance, Onvif Profile S/G/T</p> <p><b>STARLIGHT</b></p>	 64,800,000
43	HFW2431SP-S-S2	<p>4MP WDR IR Bullet Network Camera          1/3" 4MP image sensor          SMART H.264/H.265 dual stream encoding          4MP (2688 × 1520) @20 fps, 2560 × 1440 @25fps          Min. Illumination:0.008 Lux@F1.6, 3.6mm Fixed lens          WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI          Smart Detection (Tripwire   Intrusion)          Micro SD memory 256 GB, max IR distance: 30 m, Smart IR, IP67, PoE</p> <p><b>Full-color</b></p> <p><b>STARLIGHT Wiz Sense</b></p>	 42,500,000
44	HFW2249SP-S-IL-0360B	<p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera          2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)          Outputs max. 2 MP (1920 × 1080) @25/30 fps, Fixed Lens 3.6mm          Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B          Built-in warm light/IR LED : 30m/30m          ROI, WDR, 3D NR, HLC, BLC, digital watermarking          SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human)          Supports max. 256 G Micro SD card, built in MIC.          12 VDC/PoE power supply, easy for installation, IP67</p> <p><b>Full-color</b></p> <p><b>STARLIGHT Wiz Sense</b></p>	 41,000,000
45	HFW2249SP-S-IL-0280B	<p>2MP Smart Dual Illumination Fixed-focal Bullet WizSense Network Camera          2-MP 1/2.8" CMOS image sensor, low luminance, 0.0002 lux@F1.6 (B/W, 30 IRE)          Outputs max. 2 MP (1920 × 1080) @25/30 fps, Fixed Lens 2.8mm          Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B          Built-in warm light/IR LED : 30m/30m          ROI, WDR, 3D NR, HLC, BLC, digital watermarking          SMD Plus, Intrusion, tripwire (two functions supported : detection of vehicle and human)          Supports max. 256 G Micro SD card, built in MIC.          12 VDC/PoE power supply, easy for installation, IP67</p> <p><b>Full-color</b></p> <p><b>STARLIGHT Wiz Sense</b></p>	 41,000,000
46	HFW2231SP-S-0360B-S2	<p>2MP WDR IR Bullet Network Camera, starlight          1/2.8" 2Megapixel progressive CMOS          Min. Illumination:0.002 Lux@F1.6          Outputs max. 2 MP (1920 × 1080) @25/30 fps, 3.6mm Fixed lens          SMART H.264/H.265 dual-stream encoding, IVS(Tripwire, intrusion)          WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Rol Micro SD memory 256GB          Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p> <p><b>STARLIGHT</b></p>	 31,000,000
47	HFW2230SP-S	<p>2MP IR Bullet Network Camera          1/2.7" CMOS image sensor, low illuminance, high image definition          H.265+/H.265/H.264+/H.264 Double-stream encoding          25/30fps@1080P(1920×1080)          DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI          3.6mm, Max. IR LEDs Length 30m, Smart IR          Micro SD card memory 128 GB, IP67, PoE, AVI(Tripwire Intrusion)</p> <p><b>Full-color</b></p> <p><b>STARLIGHT</b></p>	 30,000,000
48	IPC-HFW2239SP-SA-LED-S2	<p>2MP Lite Full-color Fixed-focal Bullet Network Camera          1/2.8" CMOS image sensor,Outputs max. 2MP (1920 × 1080) @25/30 fps          ROI, SMART H.264+/H.265+, flexible coding,          Min Illumination 0.0017 Lux@F1.0          Intelligent detection: Intrusion, tripwire          WDR(120db), 3D NR, HLC, BLC, digital watermarking          Supports max. 256 GB Micro SD card and built-in Mic,12V DC/PoE ,IP67</p> <p><b>Full-color</b></p> <p><b>STARLIGHT</b></p>	 37,500,000
49	IPC-HFW2231T-ZS-S2	<p>2MP Lite IR Vari-focal Bullet Network Camera          2MP, 1/2.8" Progressive CMOS, low illuminance 0.002 Lux@F1.5          high image definition 2MP@25/30fps, 2.7-13.5mm Motorized Lens, SMART H.264+/H.265+          IVS Intrusion, Tripwire, Micro SD card 256 GB          WDR(120db), Rol, BLC, HLC, 3D DNR, AWB, AGC, Day/Night Auto ICR, Smart Illumination          12V, PoE, IP67, IK10, 4 IR LEDs 60m Distance, Onvif Profile S/G/T</p> <p><b>STARLIGHT</b></p>	 65,000,000
50	HFW1530SP-0360B-S6	<p>5MP 1/2.7" CMOS image sensor          Outputs max. 5MP (2880 × 1620) @20 fps,Fixed-focal 3.6mm          min illumination 0.003 Lux@F2.0 (B/W, 30 IRE)          H.265 codec, SMART H.264 +/H.265+,          Built-in IR LED, and the max. illumination distance is 30 m          Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking          Built-in MIC, IP67,POE</p> <p><b>STARLIGHT</b></p>	 39,800,000

			
51	IPC-HFW1439S1-A-LED-S4	  <p>4MP Entry Full-color Fixed-focal Bullet Network Camera 4-MP 1/3" Progressive CMOS image sensor, Outputs max. 4 MP (2560 x 1440)@25/30 fps Min. Illumination 0.008 lux@F1.6, Illumination Distance 15 m (49.21 ft) (warm light) SMART H.264+/H.265+, ROI, WDR 120db, BLC, HLC, AWB, AGC, 3D DNR, Smart Illumination Built-in Mic, 12 VDC/PoE, Metal + plastic, IP67</p>	 36,800,000
52	DH-IPC-HFW1239S1-LED-S5	 <p>2MP Lite Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" Progressive CMOS low illumination 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens SMART H.264+/H.265+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 15m Distance, Onvif Profile S/T</p>	 27,500,000
53	HFW1230T1P-ZS	<p>2MP Entry, 1/2.8" CMOS image sensor, low luminance, and high definition image Outputs max. 2MP (1920 x 1080)@25/30 fps. Min. Illumination : 0.008 Lux@F1.7 (Color, 30 IRE), 0.0008 Lux@F1.7 (B/W, 30 IRE) Motorized vari-focal, 2.8 mm~12 mm, IR Distance 50 m(2 IR) Smart H.265+, Smart H.264+, H.265 codec, high compression rate, ultra-low bit rate. DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination, S/N Ratio &gt; 56 dB 1 Port RJ-45 (10/100 Base-T), 12V DC/PoE (802.3af), IP67, Humidity ≤95%</p>	 52,000,000
54	HFW1230S1P-0360B-S5	<p>2MP Entry IR Fixed-Focal Bullet Network Camera 1/2.8" CMOS image sensor, low illumination Fixed Lens 3.6mm, F2.0, Horizontal: 84° Outputs max. 2MP (1920 x 1080)@25/30 fps Smart H.265+, Smart H.264+, H.265, H.264, H.264B ONVIF (Profile S/Profile T) Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, DWDR, 3D NR, HLC, BLC, digital watermarking 24V DC/PoE power supply, IP67</p>	 25,500,000
55	HFW1230SP-S4-S5	<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 x 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30m, Smart IR IP67, PoE</p>	 27,000,000
56	IPC-HDBW5541E-ZE-S3	  <p>5MP IR Vari-focal Vandal-proof Dome WizMind Network Camera 5-MP (2960 x 1668) 1/2.7" CMOS image sensor, low luminance, and high definition image Super Low Illumination 0.0009 lux@F1.5(Color, 30 IRE) 0.0005 lux@F1.5(B/W, 30 IRE) 0 lux (Illuminator on 40m) 2.7 mm~13.5 mm Motorized Lens, Field of View H: 114°~32°; V: 58°~17°; D: 138°~36° Smart H.265+; Smart H.264+, AI Coding Deep learning algorithm, video metadata, smart sound detection, people counting, queue management, Heat Map, Smart Search face detection with 6 Face Attributes and 8 Face Expressions smart object detection: Smart abandoned object; smart missing object IVS: Intrusion, tripwire, fast moving, loitering, people gathering, parking detection SMD 3.0 ( Less false alarm, longer detection distance ) with detailed information about human body and vehicle features BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, ROI, EIS, Defog Built-in Mic, Audio I/O 1/1, Alarm I/O 2/1, Micro SD up to 512GB, ROM 4GB, RAM 1GB IP67 and IK10 protection</p>	 155,000,000
57	HDW4431EMP-AS-S4	 <p>4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688x1520) H.265&amp;H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>	 48,000,000
58	IPC-HDBW3541E-S-S2	  <p>5MP IR Fixed-focal Dome WizSense Network Camera 5-MP (2960 x 1668) @20fps 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images 0.005 lux@F1.4 (Color, 30 IRE), 0.0005 lux@F1.4 (B/W, 30 IRE), 0 lux (Illuminator on 50m) 2.8 mm: Horizontal: 111°; Vertical: 58°; Diagonal: 132° Smart H.265+, Smart H.264+, AI Coding IVS: Tripwire, Intrusion, SMD 4.0, Smart Search, Scene Changing, Audio Detection BLC, HLC, WDR 120db, Ai SSA, AWB, AGC, 3D DNR, ROI, Defog, AFSA Built-in Mic, Micro SD up to 256GB, ROM 128MB, RAM 512MB IP67, IK10 protection, Easy Installation</p>	 70,000,000

59	HDBW3441EP-AS	<p><b>STARLIGHT</b></p> <p><b>Wiz Sense</b></p> <p>4MP IR Fixed focal Dome WizSense Network Camera 1/3" CMOS image sensorOutputs max. 4MP (2688 × 1520)@30 fps H.265 codec,SMART H.264+/H.265+ WDR(120db), 3D DNR, HLC, BLC, digital watermarking Supports max. 256 G Micro SD card,12V DC/POE,IP67, IK10, SMD Plus Min Illumination 0.0005 Lux@F1.6 (B/W, 30IRE) Audio Input 1 channel (RCA port),Audio Output 1 channel (RCA port) Alarm Input 1 channel in, Alarm Output 1 channel out</p>	
60	HDW3441TMP-AS-0280B	<p><b>STARLIGHT</b> <b>Wiz Sense</b></p> <p>4MP IR Fixed focal Eyeball WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. illumination:0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>	
61	HDBW2831EP-S-S2	<p><b>STARLIGHT</b> <b>Wiz Sense</b></p> <p>1/2.7" 8Megapixel progressive CMOS Min. illumination:0.009 Lux@F2.0 3.6mm Fixed Lens max. 8MP (3840 × 2160) @15 fps, 2688×1520 (2688 × 1520) @25/30 fps SMART H.264+/H.265+, flexible coding IVS(Tripwire; intrusion), Abnormality detection: Motion detection, video tampering WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Built-in IR LED Max.Length 30m, IP67, PoE</p>	
62	HDBW2531RP-ZAS	<p><b>STARLIGHT</b></p> <p>1/2.7" 5Megapixel progressive CMOS 2.7-13.5mm Motorized lens 20fps@5M(2592×1944)&amp;25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Micro SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67,IK10, PoE</p>	
63	IPC-HDBW2531E-S-S2	<p><b>STARLIGHT</b></p> <p>SMP Lite IR Fixed-focal Dome Network Camera 5MP, 1/2.7" Progressive CMOS Min. illumination 0.008 Lux @ F1.6 Max 5MP@20fps SMART H.264+/H.265+ IVS: Intrusion, tripwire Micro SD card 256GB WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance: 30m, 12V DC, PoE, IP67,IK10</p>	
64	IPC-HDW2831TP-AS-S2	<p><b>STARLIGHT</b></p> <p>8MP Lite IR Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensorOutputs max. 8MP (3840 × 2160) @15 fps Min illumination 0.009 Lux@F2.0 Built-in IR LED, max IR distance: 30 m SMART H.264+/H.265+ WDR, 3D NR, HLC, BLC, digital watermarking Supports max. 256 GB Micro SD card, <b>built-in MIC</b> 12 VDC/PoE,IP67</p>	
65	IPC-HDW2449T-S-LED	<p><b>STARLIGHT</b></p> <p><b>NEW</b></p> <p><b>Wiz Sense</b> <b>Full-Color</b></p> <p>4MP Full-color Fixed-focal Eyeball Wizsense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, 4MP(2688×1520)@20fps, (2560×1440)@25/30fps Min. illumination 0.005 lux@F1.0, Built-in warm light, max. illumination distance 30m Smart H.265+: Smart H.264+ high compression rate, ultra-low bit rate ROI, WDR 120db, HLC, BLC, AGC, 3D DNR, Smart illumination Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB 12 VDC/PoE, IP67, Metal+Plastic Case</p>	
66	DH-IPC-HDW2449T-S-IL	<p><b>Wiz Sense</b> <b>Full-Color</b></p> <p><b>STARLIGHT</b></p> <p>4MP Smart Dual Illumination 2.8mm Fixed-focal Eyeball WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps Min. illumination : 0.008 lux@F1.6 (Color, 30 IRE), 0.0008 lux@F1.6 (B/W, 30 IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in warm light/IR LED, the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, WDR, 3D NR, HLC, BLC, digital watermarking Intrusion, tripwire (support the classification and accurate detection of vehicle and human Supports max. 256 G Micro SD card, built in MIC, 12 VDC/PoE power supply, easy for installation, IP67 protection,SMD Plus</p>	

67	IPC-HDW2439TP-AS-LED-0360B  	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 high image definition 4MP@25/30fps 3.6mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, <b>Built-in Mic</b> 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>	 47,200,000
68	IPC-HDW2439TP-AS-LED-0280B-S2  	<p>4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" Progressive CMOS low illuminance 0.004 Lux@F1.0 High image definition 4MP@25/30fps 2.8mm Fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, <b>Built-in Mic</b> 12V, PoE, IP67, 2 Warmlight LED 30m Distance, Onvif Profile S/G/T</p>	 47,200,000
69	DH-IPC-HDBW2441E-S  	<p>4MP 1/2.9" CMOS image sensor, IR Fixed-focal 2.8mm Dome WizSense Network Camera Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 fps Min. Illumination 0.008 lux@F1.6 (Color,30IRE), 0.0008 lux@F1.6 (B/W,30IRE), 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, , WDR 120db, 3D NR, HLC, BLC Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Supports max. 256 G Micro SD card; <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67, IK10 protection, SMD Plus</p>	 46,800,000
70	DH-IPC-HDBW2441R-ZS  	<p>4MP IR Vari-focal Dome WizSense Network Camera, 4-MP 1/2.9" CMOS image sensor Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 , (2560 × 1440)@25/30 fps Min. Illumination 0.008 lux@F1.5 (Color, 30 IRE) , 0.0008 lux@F1.5 (B/W, 30 IRE) , 0 lux (Illuminator on) H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance : 40 m, ROI, SMART H.264+/H.265+ WDR 120db, 3D NR, HLC, BLC, Focal Length 2.7 mm~13.5 mm Intrusion, tripwire (support the classification and accurate detection of vehicle and human) Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); 256G SD card; <b>built in MIC</b> 12 VDC/PoE power supply, easy for installation, IP67 and IK10 protection, SMD Plus</p>	 82,000,000
71	IPC-HDW2441T-S  	<p>4MP IR Fixed-focal Eyeball WizSense Network Camera 4-MP 1/2.9" Progressive CMOS image sensor, Output 4MP (2688 × 1520)@20 fps, 2560 × 1440@25/30 fps Min. Illumination 0.006 lux@F1.6 (Color, 30IRE) 0.0006 lux@F1.6 (B/W, 30IRE) 0 lux (Illuminator on) Smart H.265+; Smart H.264+, high compression rate, ultra-low bit rate Built-in IR LED, and the max. illumination distance is 30 m WDR 120db, 3D NR, HLC, BLC, ROI, AWB, AGC, 3D DNR Intelligent monitoring: Intrusion, tripwire, SMD Plus Built-in Mic, Micro SD 256GB, IP67, 12 VDC/PoE, Metal+Plastic</p>	 44,000,000
72	HDBW2431RP-ZS-27135-S2  	<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7~13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>	 72,000,000
73	HDBW2431RP-ZAS-S2  	<p>4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7~13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE</p>	 73,000,000

74	HDBW2431EP-S-0360B-S2	<p>4MP IR Mini Dome Network Camera            1/3" 4Megapixel progressive CMOS            SMART H.264/H.265 dual stream encoding            4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps            Min. Illumination:0.008 Lux @ F1.6            3.6 mm Fixed lens            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            Smart Detection (Tripwire Intrusion)            Micro SD memory 256 GB            max IR distance:30 m, Smart IR            IP67, IK10, PoE</p> 	41,000,000
75	HDBW2431EP-S-0280B-S2	<p>4MP IR Mini Dome Network Camera            1/3" 4Megapixel progressive CMOS            SMART H.264/H.265 dual stream encoding            4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps            Min. Illumination:0.008 Lux @ F1.6            2.6 mm Fixed lens            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            Smart Detection (Tripwire Intrusion)            Micro SD memory 256 GB            max IR distance:30 m, Smart IR            IP67, IK10, PoE</p> 	41,000,000
76	HDW2431TP-AS-0280B-S2	<p>4MP Lite IR Fixed-focal Eyeball Network Camera            1/3" CMOS image sensor, Outputs 4MP (2560 × 1440)@25/30 fps            H.265 coding, SMART H.264+/H.265+, Fixed Lens 2.8mm            Min. Illumination 0.008 Lux @ F1.6            WDR(120db), 3D NR, HLC, BLC, digital watermarking,            Intelligent detection: Intrusion, tripwire            Max. 256 GB SD card and built-in Mic,12V DC/POEIP67</p> 	43,200,000
77	HDW2431TMP-AS-0280B-S2	<p>4MP WDR IR Eyeball Network Camera, Starlight            1/3" 4Megapixel progressive CMOS            SMART H.264/H.265 dual stream encoding            4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps            Min. Illumination:0.008 Lux@F1.6            2.8 mm Fixed lens            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI            Smart Detection (Tripwire Intrusion)            Micro SD memory 256 GB, Built in Mic            max IR distance:30 m, Smart IR            IP67, PoE</p> 	44,000,000
78	HDBW1431EP-0280B-S4	<p>4MP Entry IR Fixed-focal Dome 1/3" CMOS image sensor Netwok, low illuminance            Min. Illumination : 0.03 Lux @ F2.0 ,Illumination Distance : 30 m(3 IR LED), S/N Ratio &gt; 56db            Lens Fixed-focal 2.8 mm , Horizontal: 93° / Vertical: 53° / Diagonal: 111°            Smart H.265+, H.265, Smart H.264+, H.264            Main Stream: 2688 × 1520 (20 fps), high compression rate, ultra-low bit rate            WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI(4 years), Smart Illumination            Storage(FTP, SFTP, NAS) , ROM : 128MB, RAM : 512MB            12V DC/POE (802.3af), Power Consumption &lt; 5.5W, 1 port RJ-45 (10/100 Base-T) ,IP67, IK10</p> 	37,500,000
79	HDW1431T1P-A-0360B-S4	<p>4MP Entry IR Fixed-focal Eyeball Netwok Camera            1/3"4Megapixel progressive CMOS,            Fixed-focal 3.6mm            20fps@4.1M(2688×1520) &amp; 25fps@4M(2560×1440)            H.265+/H.265/H.264+/H.264 dual-stream encoding            WDR(120dB), Day/Night(ICR), Image flip, 3D DNR, HLC, BLC, digital watermark            Support ROI,Built-in MIC            Max. IR LEDs Length 30m, IP67, PoE</p> 	37,900,000
80	HDW1431T1P-0280B-S4-S5	<p>4MP Entry IR Fixed-focal Eyeball Netwok Camera            1/3"4Megapixel progressive CMOS            20fps@4.1M(2688×1520) &amp; 25fps@4M(2560×1440)            H.265+/H.265/H.264+/H.264 dual-stream encoding            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC            Support ROI            Max. IR LEDs Length 30m, IP67, PoE</p> 	34,000,000
81	DH-IPC-HDW2249TP-S-IL-0280B	<p>2MP Smart Dual Illumination Fixed-focal Eyeball WizSense Network Camera            2-MP 1/2.8" CMOS image sensor, low luminance            Min. Illumination : 0.0002 lux@F1.6 (B/W, 30 IRE) , Fixed Lens 2.8 mm            Outputs max. 2 MP (1920 × 1080)@25/30 fps            Smart Codec : Smart H.265+, Smart H.264+, H.264H, H.265, H.264, H.264B            SMD Plus, Intrusion, tripwire (accurate detection of vehicle and human).            Supports max. 256G Micro SD card, <b>built in MIC</b>.            ROI, WDR, 3D NR, HLC, BLC, digital watermarking            Built-in warm light/IR LED : 30m/30m            12 VDC/PoE power supply, easy for installation, IP67</p> 	41,000,000

82	HDW2231TMP-AS-S2  	<p>2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>	 35,000,000
83	IPC-HDW2231TP-AS-0280B-S2  	<p>2MP Lite IR Fixed-focal Eyeball Network Starlight Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.002 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion/Tripwire WDR (120db), 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch Micro SD 256GB, Built-in Mic 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>	 34,500,000
84	IPC-HDW2230T-AS-S2  	<p>2MP IR Eyeball Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005 Lux @ F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens SMART H.264+/H.265+ IVS Intrusion, Tripwire Micro SD 256GB, Built-in Mic DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 2 IR LEDs 30m Distance, Onvif Profile S/G/T</p>	 30,000,000
85	IPC-HDBW2230E-S-S2  	<p>2MP Lite IR Fixed-focal Dome Network Camera 2MP, 1/2.7" Progressive CMOS low illuminance 0.005' Lux @F1.6 High image definition 2MP@25/30fps 2.8mm Fixed Lens SMART H.264+/H.265+ IVS Tripwire; intrusion Micro SD 256GB DWDR, 3D DNR, HLC, BLC, AWB, AGC, ROI, Smart Illumination, Day/Night ICR Auto Switch 12V, PoE, IP67, 3 IR LEDs 30m Distance, Onvif Profile S/G/T</p>	 29,800,000
86	HDW1530TP-0280B-S2  	<p>5MP Entry IR Fixed-focal Eyeball Network Cam 1/2.7" CMOS image sensor low illuminance 0.003 Lux @F2 Outputs max. 5MP (2880 × 1620) @20 H.265 code, SMART H.264 +/H.265 DWDR, 3D NR, HLC, BLC, digital watermarking Built-in MIC,12 V DC/PoE power supply</p>	 40,500,000
87	DH-IPC-HDW1239T1-A-LED-S5  	<p>2MP Lite Full-color Fixed-focal Eyeball Network Camera Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm fixed lens H.265 codec, high compression rate, ultra-low bit rate Min. Illumination : 0.005 Lux @F1.6, Built-in LEDs, max LED distance: 15 m, built in MIC ROI, SMART H.264/H.265, flexible coding, applicable to various Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, 12V DC/PoE power support, IP67 protection</p>	 30,000,000
88	DH-IPC-HDW1239T1-LED-0360B-S5  	<p>2 MP Entry Full-color Fixed-focal Bullet Netwok Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 3.6mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>	 26,400,000
89	DH-IPC-HDW1239T1P-LED-0280B-S5  	<p>2 MP Entry Full-color Fixed-focal Bullet Netwok Camera 2MP, 1/2.8" Progressive CMOS low illuminance 0.005 Lux @F1.6 high image definition 2MP@25/30fps 2.8mm fixed lens Smart H.265+/Smart H.264+ DWDR/BLC/HLC/AWB/AGC/3D DNR/ROI, Smart Illumination 12V, PoE, IP67, 1 Warmlight LED 30m Distance, Onvif Profile S/T</p>	 26,400,000
90	DH-IPC-HDW1230T1-A-S5  	<p>2MP Entry IR Fixed-Focal Eyeball Netwok Camera Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm fixed lens H.265 codec, high compression rate, ultra-low bit rate, Min. Illumination : 0.01 Lux @F2.0 Built-in efficient IR illuminator, and the max. illumination distance is 30 m ROI, SMART H.264+/H.265+, flexible coding, applicable to various, built in MIC Rotation mode, DWDR, 3D NR, HLC, BLC, S/N Ratio 56 dB, digital watermarking 12V DC/PoE power supply, IP67 protection</p>	 28,800,000

91	HDW1230T1P-0280B-S5	<p>2MP Entry IR Fixed-Focal Eyeball Network Camera            1/2.7" 2Megapixel progressive CMOS            SMART H.264/H.265 dual stream encoding            max. 2MP (1920 x 1080p) @25/30 fps            Min. Illumination:0.01 Lux@F2.0, 2.8 Fixed lens            DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS            max IR distance:30 m, Smart IR, IP67, PoE</p>	 24,000,000
92	HDBW1230EP-0360B-S2	<p>1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens            H.265+/H.265/H.264+/H.264 dual-stream encoding            25/30fps@1080P(1920x1080)            DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC            Max. IR LEDs Length 30m, IP67, IK10, PoE</p>	 27,000,000
93	DH-SD29204T-GN	<p>1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom            H.264+/H.264 Encoding            Max. 25/30fps@1080P, 25/30/50/60fps@720P            WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max 100°/s pan speed, 360° endless pan rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion   Scene Change   Face   Abandoned-Missing Object)</p>	 72,500,000
94	DH-SD1A203T-GN	<p> 1/2.8" 2MP STARVIS™ CMOS (<b>Starlight</b>)            H.265+/H.265/H.264+/H.264 Triple-streams encoding            Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max Pan: 80° /s; Tilt: 40° /s speed            Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE            (Tripwire Intrusion   Abandoned/Missing  Face Detection)</p>	 74,000,000
95	SD3A205-GNP-PV	<p> 2MP Starlight IR AI WizSense Network PTZ Camera            H.265; H.264B; H.264M; MJPEG; MJPEG (Sub Stream); H.265+; H.264+            Focal Length 2.7 mm~13.5 mm, Optical Zoom 5x            Tripwire and intrusion, Deep-learning-based perimeter protectionn SMD Plus            IR distance up to 30m            Starlight technology            Up to 300 presets            DWDR, HLC, BLC, AGC, AWB, 2D/3D DNR, Day/Night Auto (ICR), ROI, Defog            Built-in Mic, Built-in Speaker, Two Way Audio            ONVIF Profile S&amp;G&amp;T; CGI            IP66; TVS 2000V lightning proof; surge protection; voltage transient protection</p>	 96,500,000
96	DH-SD6CE230U-HNI	<p> 1/2.8" 2MP STARVIS™ CMOS            H.265+/H.265/H.264+/H.264 Encoding            Max. 50/60fps@1080P            4.5mm~135mm Powerful 30x optical zoom            Max 200°/s pan speed, 360° endless pan rotation            WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC            Auto-tracking,Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map, Support Defog, ROI, EIS            Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan            Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output            RS485, IR Distance up to 200m, PoE+, IP67, IK10</p>	 340,000,000
97	DH-SD6CE245XA-HNR	<p> 2MP 45x Starlight IR WizSense Network PTZ Camera            1/2.8" 2Megapixel STARVIS™ CMOS            H.265+/H.265/H.264+/H.264 Triple-streams encoding            Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6)            Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length            45x optical zoom            WDR(120dB), Day/Night(ICR), 2D/3D DNR, BLC, HLC, AGC, AWB            Auto-tracking, Perimeter protection, Face detection, SMD Plus            Tripwire and intrusion, alarm triggering by target types (human and vehicle)            Support Defog, ROI            Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan            1*Video output, Rs485            7/2 Alarm in/out, 1/1 Audio in/out            IR Distance up to 250m, PoE+, IP67, IK10</p>	 480,000,000
98	DH-SD6CE245U-HNI	<p> 2MP 45x Starlight IR PTZ Network Camera            1/2.8" 2Megapixel STARVIS™ CMOS            H.265+/H.265/H.264+/H.264 Triple-streams encoding            Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6)            Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length            45x optical zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB            Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map)            Support Defog, ROI, EIS            Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan            1*Video output, Rs485            7/2 Alarm in/out, 1/1 Audio in/out            IR Distance up to 250m, PoE+, IP67, IK10</p>	 Call

99	SD5A245XA-HNR	<p>2MP 45x Starlight IR WizSense Network PTZ Camera            1/2.8" 2Megapixel STARVIS™ CMOS            H.265; H.265+; H.264; H.264; MJPEG (Sub Stream)            Max. 50/60 fps@1080P            Pan/Tilt Range Pan: 0°~360°; Tilt: -15°~+90°            Manual Control Speed Pan: 0.1°/s~240°/s; Tilt: 0.1°/s~120°/s            WDR(120db), HLC, BLC, 2D/3D DNR, ROI, EIS, Defog, AWB, AGC, Privacy Masking, Day/Night Auto            Auto Tracking, SMD Plus, Intrusion, Tripwire, Object Abandoned/Missing, Face Detection            Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan            Alarm I/O 2/1, Audio I/O 1/1, Supports Two Way Talk  <b>Wiz Sense</b>            Focal Length 3.95 mm~177.7 mm, Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux (IR on)            IR distance up to 150 m, 45x optical zoom            ONVIF Profile S&amp;G&amp;T, DC 24V/2.5A ± 25%; PoE+ (802.3at), Operating Temperature -40°C to +70°C            IP67; IK10; TVS 6000V lightning protection; surge protection; voltage transient protection         </p>	470,000,000
100	DH-SD5A232XB-HNR	<p>2MP 32x Starlight IR WizSense Network PTZ Camera            1/2.8" 2Megapixel STARVIS™ CMOS            32x optical zoom, Max. 50/60 fps@2M            Min Illumination Color: 0.005 lux@F1.6, Focal Length 4.8 mm~154 mm            Smart H.265+; H.265; Smart H.264+; H.264            Face detection, tracking and perimeter protection, SMD PLUS            IR distance up to 150 m, PoE+, IP67, IK10            WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC</p> <p><b>STARLIGHT</b> <b>Wiz Sense</b></p>	407,000,000
101	DH-SD5A232XA-HNR	<p>1/2.8" 2Megapixel STARVIS™ CMOS            H.265+/H.265/H.264+/H.264 Triple-streams encoding            Max. 50/60fps@1080P, 4.9mm~156mm 32x optical zoom            Max 400°/s pan speed, 360° endless pan rotation            WDR(120dB), Day/Night(ICR), Ultra DNR(2D/3D), BLC, HLC            Support Defog, ROI, Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection)            Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan            Alarm 2/1 in/out, Audio 1/1 in/out            IR Distance up to 150m, PoE+, IP67, IK10</p> <p><b>STARLIGHT</b></p>	407,000,000
102	DH-SD49425ZB-HNR	<p>4MP 25x Starlight IR WizSense Network PTZ Camera, Image Sensor: 1/2.8" STARVIS™ CMOS            1/2.8" 4Megapixel CMOS, Powerful 25x optical zoom, ROM: 4GB, RAM: 1GB            Starlight technology, Max.25/30fps@4M, Illuminator Number: 4            Focal Length: 4.8 mm~120 mm, Field of View: H: 60.0°~2.5°; V: 30.8°~2.2°; D: 66.7°~2.9°            Min. Illumination: Color: 0.005Lux@F1.6, B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR light on)            Illuminator On/Off Control: Zoom Prio/Manual/SmartIR            Perimeter protection, Face Detection, Smart Capture, SMD PLUS, IVS: Object Abandoned/Missing            Support PoE+, IR distance up to 100m, BLC, WDR 120db, HLC, AGC, ANR, ROI, Electronic Defog            Pan: 0.1°~200°/s, Tilt: 0.1°~120°/s, Presets: 300, Tour: 8 (up to 32 presets per tour), Pattern: 5, Scan: 5            IP66, DC 12V/3A, PoE+ (802.3at) Audio Input: 1, Audio Output: 1, Alarm I/O: 2/1</p> <p><b>STARLIGHT</b> <b>Wiz Sense</b></p>	267,000,000
103	SD49425XB-HNR	<p>4MP 25x Starlight IR WizSense Network PTZ Camera            1/2.8" STARVIS™ Progressive CMOS            H.265+/H.265/H.264+/H.264/MJPEG (sub stream)            Max.25/30fps@4M, 960P, 720P            4.8mm~120mm 25x optical zoom            Max 240°/s pan speed, 360° endless pan rotation            WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus            IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest)            False Alarm Avoidance for Animals, Leaves, Bright Light            Support Defog and EIS            Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan            Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p> <p><b>STARLIGHT</b></p>	267,000,000
104	SD49225XA-HNR-S3	<p>2MP 25x Starlight IR WizSense Network PTZ Camera            1/2.8" 2Megapixel STARVIS™ CMOS,            25x optical zoom, Min Illumination Color: 0.005 lux@F1.6            Max. 25/30 fps@1080p            IR distance up to 100 m, Perimeter protection, Face detection, SMD Plus, IP66            Pan: 0° to 360° endless, Tilt: -15° to +90°, auto flip 180°, Pan: 200°/s; Tilt: 100°/s            Smart H.265+; H.265; Smart H.264+; H.264B; H.264M; H.264H; MJPEG (Sub Stream)            Tripwire and intrusion. Support alarm triggering by target types (human and vehicle)            WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC</p> <p><b>STARLIGHT</b> <b>Wiz Sense</b></p>	220,000,000



105	SD49225XA-HNR	2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS <b>STARLIGHT Wiz Sense</b> Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+	220,000,000
106	SD49225DB-HNY	2MP 25x Starlight IR Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm~120 mm Max. 25/30 fps@1080p Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on) Illumination Distance 100 m (328.08 ft) (IR) Max. Aperture F1.6~F3.5 Smart IR - 4 IR - S/N Ratio ≥ 55 dB IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+;H.265;Smart H.264+;H.264;H.264B;MJPEG(Sub Stream) WDR 120db, Day/Night Auto (ICR)/Color/B/W, HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, Rol, EIS, Defog Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, 12 VDC/3 A, PoE+, IP66, FTP/ Micro SD card (512 GB)/ NAS	220,000,000
107	SD49225ZB-HNR	1/2.8" 2Megapixel STARVIS™ CMOS Powerful 25x optical zoom - Focal Length 4.8 mm~120 mm Max. 25/30 fps@1080p Min. Illumination Color: 0.005 lux@F1.6 / B/W: 0.0005 lux / 0 lux (IR light on) Illumination Distance 100 m (328.08 ft) (IR) Max. Aperture F1.6~F3.5 Smart IR - 4 IR - S/N Ratio ≥ 55 dB IVS (Perimeter Protection) : Tripwire , intrusion / SMD Plus / Face Detection / Motion Detection Smart H.265+; H.265; Smart H.264+ WDR 120db, Day/Night Auto (ICR)/Color/B/W, HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, Rol, EIS, Defog Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm I/O : 2/1 - IP66 - Power Supply 12 VDC, 3 A - PoE+ Storage : FTP/ Micro SD card (512 GB)/ NAS	220,000,000
108	SD59430U-HNI	1/3" CMOS Sensor H.265+/H.265/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592x1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion   Scene Change   Face  Anondoned-Missing Object)	350,000,000
109	SD5A432XB-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.6, 0 Lux (IR on) 4.8 mm~154 mm Powerful 32x optical zoom, Max. Aperture F1.35~F4.4 Support human, motor vehicle and non-motor vehicle image capture Tripwire and intrusion. Support alarm triggering by target types (human and vehicle) Support filtering false alarms caused by animals, rustling leaves, bright lights, etc. Pan: 0° to 360° endless , Tilt: -15° to +90°, auto flip 180° , Pan: 0.1°~300°/s , Tilt: 0.1°~200°/s WDR(120), EIS, Defog, Rol,2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Alarm I/O : 2/1 , Audio I/O : 1/1 ,PoE+,IP67 ; IK10 ; TVS 6000 V	440,000,000
110	DH-SD5A432GB-HNR	4MP 32x Starlight IR WizSense Network PTZ Camera Image Sensor 1/2.8" CMOS, Max. Resolution 2560 (H) x 1440 (V) Electronic Shutter Speed 1/1 s~1/30,000 s, Min. Illumination, Color: 0.005 lux@F1.6, B/W: 0.0005 lux@F1.6 Illumination Distance 150 m(IR), Focal Length 4.8 mm~154 mm Manual Control Speed Pan: 0.1°/s~300°/s, Tilt: 0.1°/s~200°/s Preset 300, Tour 8 (up to 32 presets per tour), Pattern 5, Scan 5 Perimeter Protection, Face Detection, Auto Tracking, Quick Pick, SMD BLC, WDR 120 db, WB, AGC, ANR, Rol, EIS, Defog Electronic, S/N Ratio ≥55 dB Storage : FTP, Micro SD card (512 GB); NAS, Alarm I/O 2/1, Audio I/O 1/1 Power Supply 24 VDC, 2.5 A (± 25%), Operating Temperature -40 °C to +70 °C	460,000,000



111	SD5A432XA-HNR	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+, H.264+, H.265, H.264, MJPEG(Sub Stream) 3 Stream, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.35, B/W: 0.0005 Lux@F1.35, 0 Lux (IR on) 4.9 mm~156 mm Powerful 32x optical zoom, Max. Aperture F1.35~F4.4 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°~360° endless rotation WDR(120), EIS, Defog, ROI, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection; voltage transient protection</p> 	428,000,000
112	SD5A445GB-HNR	<p>4MP 45x Starlight IR Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.264H; H.264B; Smart H.265+; H.264; H.265; MJPEG(Sub Stream); Smart H.264+ Min. Illumination Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on) 3.95 mm~177.75 mm 45x optical zoom Starlight technology IR distance up to 150 m WDR(120), EIS, Defog, ROI, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Perimeter protection, Face detection, SMD 4.0, Quick Pick, Auto-tracking 3.0 Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Alarm in/out 2/1, Audio in/out 1/1, IP67, IK10, TVS 6000V lightning proof; surge protection; voltage transient protection</p> 	550,000,000
113	SD5A445XA-HNR-1T	<p><b>AI</b> STARLIGHT Wiz Sense</p> <p>4MP 45x Starlight IR DHOP Network PTZ Camera - Max. 25/30 fps@4MP 1/2.8" 4Megapixel STARVIS™ CMOS - Progressive CMOS - ROM : 4GB - RAM : 1GB 1T computing power for enhanced performance - Flash : 350 M - Memory : 300 M Compression H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) Min. Illumination Color: 0.005 Lux@F1.6 / B/W: 0.0005 Lux@F1.6 / 0 Lux (IR light on) Starlight technology - Illumination Distance : 150 m (492.13 ft) - Illuminator Number : 4 Focal Length 3.95 mm~177.7 mm - Max. Aperture F1.6~F4.95 - Field of View: H: 70.3°~1.8°; V: 37°~1° Pan: 0°~360°; Tilt: -15°~+90° / Manual Control Speed : Pan: 0.1°/s~300°/s; Tilt: 0.1°/s~200°/s Preset Speed : Pan: 400°/s; Tilt: 300°/s - Presets : 300 - Tour 8 (up to 32 presets per tour) - Pattern : 5 WDR(120), HLC, BLC, AWB, AGC, 2D DNR, 3D DNR, ROI, EIS, Electronic Defog Alarm I/O 2/1 - Audio I/O 1 (Line in; bare wire)/1 (Line out; bare wire) - 1 RJ-45 Port 10/100Base-T DC 24 V/2.5 A ± 25% - PoE+ (802.3at), 11 W / 20 W (IR light on) IP67, IK10</p> 	535,000,000
114	SD5A445XA-HNR	<p><b>AI</b> STARLIGHT Wiz Sense</p> <p>4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265/H.265+/H.264+/H.264/MJPEG(Sub Stream) 3 Streams, Max. 25/30fps@4M Min. Illumination Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux (IR light on) 3.95 mm~177.7 mm Powerful 45x optical zoom Max. Aperture F1.6~F4.95 Max Presets Speed: Pan: 400°/s Tilt: 300°/s, Pan: 0°~360° endless rotation WDR(120), EIS, Defog, ROI, 2D DNR, 3D DNR, HLC, BLC, AWB, AGC, Day/Night Auto ICR Deep Learning, Auto Track, Tripwire, intrusion, Object Abandoned/Missing, SMD Plus, Face Detection, human/motor vehicle/non-motor vehicle Classification, Animals/Leaves/Light False Alarm Filtering Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/1 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 150m, DC 24 V/2.5 A, PoE+, IP67, IK10, 6000V lightning proof; surge protection</p> 	535,000,000
115	SD6CE445XA-HNR	<p><b>AI</b> STARLIGHT Wiz Sense</p> <p>4MP 45x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ Progressive CMOS H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream) Max. 25/30fps@4MP Minimum Illumination Color: 0.005 Lux@F1.6; B/W: 0.0005 Lux@F1.6; 0 Lux@F1.6 (IR on) 3.95 mm~177.75 mm Powerful 45x optical zoom Max. Aperture F1.6~F4.95 Pan/Tilt Range Pan: 0°~360° endless; Tilt: -20°~90°, auto flip 180° Preset Speed Pan: 300° /s; Tilt: 200° /s WDR 120db, BLC, HLC, Auto ICR, AWB, AGC, 2D/3D DNR, ROI, EIS, Defog Deep-learning-based auto tracking and perimeter protection Face detection, SMD Plus, Tripwire, Intrusion, Human/Vehicle/Motor-non Motor Vehicle Detection Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan Micro SD card (256G), 1/1 Audio I/O, 2/2 Alarm I/O, ONVIF Profile S&amp;G&amp;T IR distance up to 250m, DC 24 V/2.5 A, PoE+, IP67, IK10</p> 	560,000,000
116	DHI-NVR1104HS-S3/H (V2.0)	<p><b>4K</b></p> <p>4 Channel IPC Input, 4K Lite H.265 NVR 1/4 Live &amp; Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60Mbps for forwarding. Up to 8MP Resolution for Preview &amp; Playback Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p> 	28,500,000

117	NVR2104HS-P-I <b>Wiz Sense</b>	<p>4 Channel Compact 1U 4PoE WizSense Network Video Recorder, New 4.0 user interface H.264/H.265/Smart H.264+/Smart H.265+/MJPEG, H.265 auto switch 1 VGA/1 HDMI simultaneous video output, HDMI 4K, non-simultaneous video output is also supported on 1080p 1-channel face detection and recognition (AI by NVR); or 2-channel perimeter detection (AI by NVR); or 4-channel SMD (AI by NVR); up to 10 face databases and 5,000 face images Max. decoding capability: 4x1080P@30fps. Supports adaptive decoding Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Resolution 12M/8M/5M/4M/3M/2M/720P/D1 AI disabled: 1-channel 12MP@30fps; 1-channel 8MP@30fps; 2-channel 5MP@30fps; 3-channel 4MP@30fps; 6-channel 1080p@30fps AI enabled: 1-channel 8MP@30fps; 1-channel 5MP@30fps; 2-channel 4MP@30fps; 4-channel 1080p@30fps 4 PoE Ports, 1 SATA port, up to 8 TB, 1 front USB 2.0 port, 1 rear USB 2.0 port, 1 RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE power supply (10/100 Mbps)</p>		60,000,000
118	NVR2104HS-4KS2 <b>4K</b>	<p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		32,500,000
119	NVR2104HS-P-4KS2 <b>4K</b>	<p>4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support</p>		42,500,000
120	DHI-NVR1108HS-S3/H <b>4K</b>	<p>8 Channel IPC Input, 4K Lite H.265 NVR 1/4/8/9 Live &amp; Playback Smart H.265+/Smart H.264+/H.265/H.264 Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. Up to 8MP Resolution for Preview &amp; Playback Decoding Capacity : 1-ch@8MP(30FPS) or 1-ch@5MP(30FPS) or 2-ch@4MP(30FPS) or 2-ch@3MP(30FPS) or 4-ch@1080P(30FPS) Video Output 1 VGA/1 HDMI simultaneous video output, maximum resolution 1080P 1 SATA 2.0 port, up to 8TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (10/100 Mbps), P2P Support, ONVIF(profile T/profile S/profile G)</p>		34,900,000
121	NVR2108HS-4KS2 <b>4K</b>	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		40,000,000
122	NVR2108HS-8P-4KS2 <b>4K</b>	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&amp;playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support</p>		56,500,000
123	NVR2108HS-S3 <b>4K</b>	<p>8 Channel Lite Series, Compact 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding AI by camera: perimeter protection, and SMD Plus Multi-channel Playback Up to 8 channels, HDD Interface 1 SATA port, up to 16 TB Audio Input/Out : 1/1 , Network Port 1 x RJ-45, 10/100 Mbps Power Supply 12 VDC, 1.5 A</p>		46,500,000
124	NVR2108HS-I2 <b>Wiz Sense</b> <b>AI</b>	<p>8 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 x 1080p@30 fps. Supports adaptive decoding 1-channel face detection and recognition (AI by NVR) 1-channel perimeter protection (AI by NVR), 4-channel SMD Plus (AI by NVR) AI by camera: Face detection and recognition, perimeter protection, and SMD Plus HDD 1 SATA port, up to 10 TB, RCA Input 1, RCA Output 1 Power Supply 12 VDC, 1.5 A, Operating Temperature -10 °C to +55 °C</p>		58,000,000
125	NVR2108HS-I <b>Wiz Sense</b> <b>AI</b> <b>12MP</b>	<p>8 Channel 12MP WizSense NVR 1/4/8 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled : 1ch 8MP@30fps or 1ch 5MP@30fps or 2ch 4MP@30fps or 4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		58,000,000

126 NVR4108HS-4KS2	<b>4K</b>	<p>8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		47,000,000
127 DHI-NVR2216-4KS2	<b>4K</b>	<p>16 Channel 4K Lite H.265 NVR 1/4 Live &amp; Playback Dual-core embedded processor, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth, Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output 2 SATA III Ports, up to 6TB capacity for each, Total 12TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support</p>		62,000,000
128 NVR2116HS-I	<b>12MP</b>	<p>16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth: 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 1 SATA II port, up to 8TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		73,000,000
129 NVR2116HS-I2	<b>12MP</b>	<p>16 Channel Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Network Bandwidth: Ai off: Access: 144 Mbps; Storage: 144 Mbps; Forward: 72 Mbps Ai on: Access: 72 Mbps; Storage: 72 Mbps; Forward: 36 Mbps Resolution: 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1 Decoding Capability: Ai disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps Ai enabled: 1-channel 8MP@30fps; 1-channel 5MP@30fps; 2-channel 4MP@30fps; 4-channel 1080p@30fps 1 × VGA, 1 × HDMI (simultaneous) 4K Output 1-channel face detection and recognition (Ai by NVR); 1-channel perimeter protection (Ai by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (Ai by NVR); AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 1 SATA II port, up to 10TB 1ch Audio I/O for Two Way Talk Only, 1 front USB 2.0 port, 1 rear USB 2.0 port 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		72,000,000
130 DHI-NVR2216-I	<b>12MP</b>	<p>16 Channel 12MP WizSense NVR 1/4/9/16 Live &amp; Playback Smart H.265+/H.264+/MJPEG Network Bandwidth 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding Ai Disabled: 1ch 12MP@30fps/1ch 8MP@30fps/2ch 5MP@30fps/3ch 4MP@30fps/6ch 2MP@30fps Ai Enabled: 1ch 8MP@30fps/1ch 5MP@30fps/2ch 4MP@30fps/4ch 2MP@30fps HDMI/VGA Simultaneous Max Output 4K, non-Simultaneous Max output 1080p 1ch Face Detection and Face Recognition Ai by NVR up to 5000 Face Library or 2ch Perimeter Ai By NVR or 4ch SMD Plus Ai by NVR, Human/Vehicle Classification 2 SATA 2.0 port, up to 8TB each, Total 16TB 1 front USB 2.0 port, 1 rear USB 2.0 port, 1ch Audio I/O for Two Way Talk Only 1 RJ-45 port (1000Mbps), P2P Support, ONVIF (profile T/profile S/profile G)</p>		93,000,000
131 DHI-NVR2216-I2	<b>12MP</b>	<p>16 Channel 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding Ai by NVR: 1-channel face detection and recognition; 1-channel perimeter protection; up to 10 face databases and 5,000 face images; 4-channel SMD Plus AI by camera: Face detection and recognition, perimeter protection, and SMD Plus 2 SATA each up to 10TB, 2 USB, 1 HDMI, 1 VGA, 1 LAN 1000Mbps, Audio in/out 1/1, Onvif (S, T, G)</p>		93,000,000
132 NVR4116HS-4KS2	<b>4K</b> <b>AI</b>	<p>16 Channel Compact 1U 4K&amp;H.265 Lite Network Video Recorder Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch Max 80Mbps Incoming Bandwidth Up to 8MP Resolution for Preview and Playback 8-channel decoding@1080p (30 fps) AI by Camera: Perimeter protection; SMD Plus; people counting; heat map target classification (human, vehicle) HDMI(4K)/VGA simultaneous video output 1 SATA III port, up to 10 TB, 1 front USB 2.0 port, 1 rear USB 3.0 port Audio I/O 1/1 for Two Way Talk Only 100 Mbps Network Card, P2P support</p>		69,000,000

133	NVR4116HS-4KS2/L		<p>16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>	
134	NVR4216-4KS2/L		<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p>	
135	NVR4216-16P-4KS2/L	 	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with Face Attributes, perimeter protection, IVS, people counting, heat map, and SMD Support 2 SATA HDD up to 10TB, 2 USB Ports (1 front USB2.0, 1 back USB2.0) 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, 16 Port PoE, ONVIF(profile T/S/G)</p>	
136	NVR4216-4KS3	   	<p>16CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. 160/160Mbps incoming/recording bandwidth Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps HDMI(4K)/VGA simultaneous video output AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map Supports IP cameras with a resolution up to 12MP 2 SATA ports. Each disk up to 10TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>	
137	NVR4232-EI	  	<p>32CH 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled) Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding HDMI(4K)/VGA simultaneous &amp; Independent video output AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus AI by Camera: Face detection(8CHs) and recognition(8CHs), perimeter protection(8CHs); SMD Plus(8CHs); people counting; stereo analysis; heat map Supports IP cameras with a resolution up to 16MP 2 SATA ports, up to 16TB., Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>	
138	NVR4232-4KS2/L	 	<p>32 Channel 1U 2HDDs Network Video Recorder Smart H.265+/H.264+ codec decoding Max160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps HDMI(4K)/VGA simultaneous video output AI by Camera: Face detection with attributes, perimeter protection, IVS, people counting, heat map, and SMD, Human &amp; Vehicle Classification 2 SATA III ports, up to 10 TB each port, 1 × front USB2.0; 1 × back USB2.0 4 Alarm Input, 2 Relay Output, 1*1000Mbps Network Card, P2P support, ONVIF(profile T/S/G)</p>	
139	NVR4232-4KS2		<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*1000Mbps Network Card, P2P support</p>	
140	NVR4432-4KS2/I	 	<p>32 Channel 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG Access, storage or forwarding at 256 Mbps, Max. decoding capability: 10 × 1080p@30 fps Face detection; face recognition; perimeter protection,SMD Plus Multi-channel Playback Up to 16 channel The maximum HDD capacity 4 SATA ports, up to 10 TB Alarm Input 16,Alarm Output 4 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port</p>	

Product Overview					
<b>NEW</b>					
141 NVR4232-4KS3	  	<p>32CH 1U 2HDDs Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats Max. 160Mbps incoming bandwidth Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps HDMI(4K)/VGA simultaneous video output AI by Recorder supports 4-channel SMD Plus AI by Camera supports face detection(6CHs) and recognition(6CHs), perimeter protection(6CHs), SMD Plus(6CHs), people counting, stereo analysis and heat map Supports IP cameras with a resolution up to 12 MP 2 SATA ports. Each disk up to 20TB, Audio in/out 1/1 for Two Way Talk, Alarm in/out 4/2, USB 2 Ports, LAN 1*1000, P2P support, ONVIF(profile T/S/G)</p>		112,000,000	
142 DHI-NVR5232-4KS2(V2.0)		<p>32Channel 1U 4K &amp; H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0, 1 USB2.0) 1*1000 Mbps Network Card, RS232, RS485, 4/2 Alarm In/out , P2P Support</p>		195,000,000	
143 NVR5232-EI	  	<p>32 Channels 1U 2HDDs WizSense network video recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Max. 384 Mbps incoming/recording/outgoing bandwidth 16ch AcuPick, N+M Clustering, Face Detection, Face Recognition, Face Attributes, Face Expression, SMD Plus, Perimeter Protection, Metadata, ANPR, Stereo Analysis, Heatmap, People Counting AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Audio in/out 1/1, Alarm in/out 1/2, 2 SATA each up to 16TB, RS232, RS485, 2*HDD 2, 1*HDD 2, 1*HDMI 1*VGA 1*LAN</p>		217,000,000	
144 NVR5432-EI		<p>32 Channels 1.5U 4HDD WizSense Network Video Recorder Industrial-grade processor - Embedded Linux OS Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2ch face detection and recognition, 4ch perimeter protection, and 8ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Network Port 2 (10/100/1000 Mbps Ethernet port, RJ-45) 4 SATA ports, up to 16 TB - Security baseline 2.3 - Supports 4K display - Alarm In/Out : 16ch/6ch</p>		300,000,000	
145 NVR5432-4KS2(V2.0)		<p>32Channel 1.5U 4K &amp; H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0, 1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485, 16/6 Alarm In/out , P2P Support</p>		255,000,000	
146 NVR5832-EI	   	<p>32 Channels 2U 8HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Max. 384 Mbps incoming/recording/outgoing bandwidth Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps Support AcuPick with Max. 16-Channel, Support N+M cluster AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection(16CHs) and recognition(16CHs), perimeter protection(16CHs), SMD Plus(16CHs), metadata(8CHs), ANPR(8CHs), stereo analysis, heat map, and people counting Audio in/out 1/2 for Two way talk only, Alarm in/out 16/8, USB*3, HDMI*2, VGA*2, LAN*2*1000, eSATA*1, 8 SATA Ports each up to 20TB, RS-232, RS-485, P2P Support, Onvif (S/T/G)</p>		460,000,000	
147 DHI-NVR5464-4KS2(V2.0)		<p>64Channel 1.5U 4K&amp;H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0, 1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card, RS232, RS485, 16/6 Alarm In/out , P2P Support</p>		300,000,000	
148 NVR5832-4KS2		<p>32 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview&amp;playback Max 16ch@1080P   4ch@4K H.265   H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232, 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10</p>		330,000,000	

<b>NEW</b>		
149 NVR5864-EI	<p><b>Wiz Sense</b></p> <p><b>AI</b></p> <p><b>4K</b></p>	<p>64 Channels 2U 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format Industrial-grade processor - Embedded Linux Max. decoding capability: 32 x 1080p@30 fps or 32 x 2MP@30 fps Support AcuPick with Max. 16-Channel - Support N+M cluster - Support Raid0/1/5/6/10 Max. 384 Mbps incoming/recording/outgoing bandwidth AI by recorder: 2-ch face detection and recognition, 4-ch perimeter protection, and 8-ch SMD Plus AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting Security baseline 2.3 - Alarm In/Out : 16/8 - 8 SATA ports, each disk up to 16 TB HDMI:2 - VGA:2 - USB:4 - RS485:2 - RS232:1</p>
150 DHI-NVR5864-4KS2(V2.0)	<p><b>4K</b></p>	<p>64 Channel 2U 4K &amp; H.265 Pro Network Video Recorder (V2.0) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth, Up to 12Mp resolution preview &amp; playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10TB for each HDD), 4 USB(2 USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card, RS232, RS485,16/6 Alarm In/out , P2P Support</p>
151 NVR608-32-4KS2	<p><b>4K</b></p>	<p>Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&amp;playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232, RS485, 16 Alarm In , 8 Relay Output</p>
152 NVR608-64-4KS2	<p><b>4K</b></p>	<p>Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview &amp; playback 2HDMI/VGA simultaneous video output 8 SATA III ports, up to 10 TB for a single HDD,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output</p>
153 DHI-NVR608H-32-XI	<p><b>Wiz Mind</b></p> <p><b>AI</b></p> <p><b>8K</b> <small>ULTRA HD</small></p>	<p>32 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, and people counting 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is <b>8K</b>, max. resolution of HDMI3 is <b>8K</b>, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p>
154 DHI-NVR608H-64-XI	<p><b>Wiz Mind</b></p> <p><b>AI</b></p> <p><b>8K</b> <small>ULTRA HD</small></p>	<p>64 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is <b>4K</b>, max. resolution of HDMI3 is <b>8K</b>, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p>
155 NVR608H-128-XI	<p><b>Wiz Mind</b></p> <p><b>AI</b></p> <p><b>8K</b> <small>ULTRA HD</small></p>	<p>128 Channels 2U 8HDDs WizMind Network Video Recorder Industrial-grade processor AI disabled: 1024 Mbps incoming, 1024 Mbps recording and 800 Mbps outgoing AI enabled: 512 Mbps incoming, 512 Mbps recording and 400 Mbps outgoing Resolution 32 MP; 24 MP; 16 MP; 12 MP; 8 MP; 5 MP; 4 MP; 1080p; 720p; D1 Supports N+M cluster Support Raid0/1/5/6/10 &amp; HDD hot swapping AI by recorder: 4ch face detection and recognition; 8ch metadata; 24ch perimeter protection; 32ch SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, and people counting 64ch - metadata, ANPR 32ch 2-channel VGA, 4-channel HDMI video output with Simultaneous &amp; Independent Video Mode HDMI1 and HDMI2 is <b>8K</b>, max. resolution of HDMI3 is <b>8K</b>, max. resolution of HDMI4 is 1080p Support Smart H.265+; H.265; Smart H.264+; H.264; MPEG4; MJPEG Audio I/O 1/2, Alarm I/O 16/8, HDD 8 SATA Ports 16TB Each, 1 e-SATA Port, 4 USB Ports, 2 Network Ports 10/100/1000</p>

156	DHI-NVR608-128-4KS2	<p>128 Channel 2U Ultra 4K H.265 Network Video Recorder            (1st Screen: 1/4/8/9/16/25/36, 2nd Screen: 1/4/8/9/16)  <b>4K</b>            H.265/H.264/MJPEG codec decoding            Max 384Mbps incoming bandwidth            Up to 12Mp resolution preview &amp; playback            2HDMI(different Source)/VGA simultaneous video output            Support 8 SATA (8TB for each HDD),1 eSATA Port            Support Raid 0/1/5/10            Support Smart Tracking and Intelligent Video            4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card            RS232 , RS485, 16/8 Alarm In/Output</p> 	<b>760,000,000</b>
157	ESS1508C	<p>2U standard 19-inch rack case            Connect master device via eSATA or USB            1 eSATA port transmission speed up to 3Gbps            1 USB 3.0 port data transmission higher than normal            Powerful R / W performance: read &gt;64MB/s, write &gt;64MB/s            ESS1508C: Max support Internal 8 SATA HDD up to 48TB            Recommended with DVR, NVR connection</p> 	<b>116,000,000</b>
158	PFS3006-4ET-36	<p>6-Port Fast Ethernet Switch with 4-Port PoE            4 PoE ports with 10/100 Mbps Base-TX            2 uplink ports with 10/100Mbps Base-TX            Port1-4 ≤30W, whole PoE budget ≤36W            Support 802.3af and 802.3at standards            OperatingTemperature: -10°C to +55°C            Support 250 m long distance PoE tansmission            Support PoE watchdog            Switching Capacity 1.2 Gbps, Packet Forwarding Rate 0.89 Mpps, MAC Table Size 2K, Jumbo Frame 2048 byte            Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3X            ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV</p> 	<b>22,500,000</b>
159	PFS3106-4ET-60 (V2.0)	<p>4-Port PoE Switch (Unmanaged)            4 × RJ-45 10/100 Mbps (PoE)            1 × RJ-45 10/100/1000 Mbps (Uplink)            1 × SFP 100/1000 Mbps (Uplink)            Intelligent PoE, Hi-PoE 60W (Orange Port), PoE watchdog, 250 m long distance PoE transmission            Wide operating temperature: -30°C to +65°C (-22°F to +149°F)            Switching Capacity 6.80 Gbps, Packet Forwarding Rate 3.57 Mpps, Packet Buffer Memory 1 Mbit, MAC Table Size 8K            Communication Standard IEEE802.3; IEEE802.3u; IEEE802.3X; IEEE 802.3ab; IEEE 802.3z            PoE Standard IEEE802.3af; IEEE802.3at; Hi-PoE, 250 m long distance PoE transmission            Statics Protection Air discharge:15kV Contact discharge:8kV, Thunder-proof Common mode:4kV Differential mode:2kV</p> 	<b>41,000,000</b>
160	PFS3010-8ET-65	<p>10-Port Fast Ethernet Switch with 8-Port PoE            Port 1~8: 8 × RJ-45 10/100 Mbps (PoE)            Port 9-10: uplink with 10/100 Mbps            Support 802.3af and 802.3at standards            Support 250 m long distance PoE tansmission            Support PoE watchdog            Port1-8 ≤30W, whole PoE budget ≤65W            Switching Capacity 2.0 Gbps, Packet Forwarding Rate 1.49 Mpps , MAC Table Size 2K, Jumbo Frame 2048 byte            ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 6kV Differential mode: 4kV</p> 	<b>32,150,000</b>
161	PFS3110-8ET-96 (V2.0)	<p>10-Port Unmanaged Desktop Switch with 8 Port PoE            Port 1~8: 8 × RJ-45 10/100 Mbps (PoE)            Port 9: 1 × RJ-45 10/100/1000 Mbps (uplink)            Port 10: 1 × SFP 1000 Mbps (uplink)            Communication Standard IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE 802.3ab/IEEE 802.3z            PoE Standard IEEE802.3af/ IEEE802.3at/ Hi-PoE/ IEEE802.3bt            Port 1~2 ≤ 90 W, Port 3~8 ≤ 30 W, totals 96 W            Intelligent PoE, BT 90W, Long distance PoE, PoE watchdog, Wide working temperature            Lightning Protection Air discharge:8kV Contact discharge:6kV, ESD Protection Common mode:4kV Differential mode:2kV</p> 	<b>59,500,000</b>
162	PFS3218-16ET-135	<p>Layer 2 PoE switch            2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            16 × RJ45 10/100 Mbps            Port 1~2≤60W, Port 3~16≤30W, total≤135W            IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z            PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE            Intelligent PoE, PD Alive(PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission            Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation            Switching Capacity 7.2 Gbps, Packet Forwarding Rate 5.3568 Mpps, Packet Buffer Memory 4 Mbit, MAC Table Size 8K            ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV</p> 	<b>102,000,000</b>
163	PFS3226-24ET-240	<p>Layer 2 PoE switch            2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            24 × RJ45 10/100Mbps            Intelligent PoE, PD Alive(PoE Watchdog), Long Distance PoE Transmission, Smooth Transmission            Wide Working Temperature: -10 to 55°C (14°F to 131°F), VLAN Port Isolation            Port1/2 support Hi-PoE (60W), PoE+, PoE            Port 1~2≤60W, Port 3~24≤30W, total≤240W            IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z            PoE Standard IEEE802.3af, IEEE802.3at, Hi-PoE            Switching Capacity 8.8Gbps, Packet Forwarding Rate 6.5472 Mpps            MAC Table Size 8K            ESD Air discharge: 8kV Contact discharge: 6kV, Thunderproof Common mode: 4kV Differential mode: 2kV</p> 	<b>131,000,000</b>

164	PFT1300	<p>PoE Extender</p> <p>1*10/100 Base-T PoE power receiving port</p> <p>1*10/100 Base-T PoE power supply port, supply power for the next extender</p> <p>1*10/100 Base-T PoE power supply port, supply power for IPC</p> <p>Support passive PoE cascade power supply and Ethernet data exchange</p> <p>Support IEEE 802.3af/at standard power supply IP Camera</p> <p>able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption &lt;=8W), max transmission distance 300m</p>	 6,650,000
165	PFM700	<p>*1 Channel HDMI Transmission Signal</p> <p>*1080P/1080I/720P/576P/576I/480P/480I Resolution Output Signal , *60M (max)Transmission Distance</p> <p>*Input voltage DC5V</p> <p>*Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3</p>	 18,700,000
166	NKB1000	<p>Keyboard to Control : Dahua High Speed Dome (all models)</p> <p>Dahua Standalone DVR , Dahua Network High Speed Dome</p> <p>Network Video Server, Connection : RS485, RS422, USB, RS232 &amp; Network</p> <p>Three Dimensional Joystick Control of PTZ Functions</p> <p>Preset Position, Auto Scan, Auto Pan, Auto Tour &amp; Pattern Control, On-Screen Menu &amp; User Operation Procedure Tips</p> <p>Connect to SmartPSS via USB</p>	 12,200,000



1 HAC-HFW1509MHP-A-LED-S2	 	<p>5MP Full-color HDCVI Bullet Camera Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 120 dB true WDR, HLC,HLC-Pro, BLC, 3D DNR, AGC, AWB 2 LEDs 50m Distance, Smart Light, IP67, DC12V</p>	
2 HAC-HFW1509TMP-IL-A	 	<p>5MP Smart Dual Illuminators Bullet Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR. Smart Dual Illuminators, 40 m illumination distance Min. Illumination, 0.001 lux@F1.0 (Color, 30 IRE), 0.0001 lux@F1.0 (B/W, 30 IRE) Super Adapt, Built-in MIC, BLC; HLC; WDR; HLC-Pro 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable, IP67, 12 VDC</p>	
3 HAC-HFW1509TLM-A-LED	 	<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>	
4 HAC-HFW1509TLMP-LED	 	<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m Distance, Smart Light, IP67, DC12V</p>	
5 HAC-HFW1509TP-LED	 	<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>	
6 HAC-HFW1509TP-A	 	<p>5MP Full-color HDCVI Bullet Camera 5MP 1/2.7 inch Progressive CMOS Minimum Illumination 0.001 Lux/F1.0, 0 Lux warm light on Max 5MP@25fps (16:9 video output) <b>Built-in mic</b> 3.6mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu WDR(120db), HLC, HLC-Pro, BLC, 3D DNR, AGC, AWB 1 LED 20m Distance, Smart Light, IP67, DC12V</p>	
7 DH-HAC-HFW1500RP-Z-IRE6		<p>5MP Starlight HDCVI IR Bullet Camera, Image Sensor 1/2.7 inch CMOS Max 25 fps@5MP (16:9 video output) CVI/CVBS/AHD/TVI switchable 2.7 mm–12 mm motorized lens, 0.005 Lux/f1.6, 30IRE, 0 Lux IR on Illumination Distance 60 m , S/N Ratio &gt; 65 dB Pan/Tilt/Rotation Range Pan: 0°–360°, Tilt: 0°–90°, Rotation: 0°–360° Max. IR length 60 m, Smart IR, BLC/HLC/DWDR IP67, 12V DC</p>	

ج

ت



(ر)

8	DH-HAC-HFW1500THP-I4	<p>5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 40m, Smart IR, IP67, DC12V±30</p> 	18,100,000
9	DH-HAC-HFW1500THP-I8	<p>5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max. IR length 80m, Smart IR, IP67, DC12V±30</p> 	20,700,000
10	DH-HAC-HFW1500TP-0360B-S3	<p>5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V</p> 	17,800,000
	<b>STARLIGHT</b>		
11	DH-HAC-HFW1500DP	<p>5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 80 m, Smart IR, IP67, DC12V</p> 	25,000,000
	<b>STARLIGHT</b>		
12	DH-HAC-HFW1500CMP	<p>5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP (16:9 video output) 3.6 mm fixed lens, Max. Aperture F1.6/Min. Illumination 0.005 Lux DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR CVI/CVBS/AHD/TVI switchable, Support OSD Menu Max. IR length 30 m, Smart IR, IP67, DC12V</p> 	17,800,000
	<b>STARLIGHT</b>		
13	HAC-B1A51	<p>Cooper Series</p> <p>5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm, 2.8mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Plastic</p> 	13,600,000
14	DH-HAC-B2A51P	<p>Cooper Series</p> <p>5MP HDCVI IR Bullet Camera, 1/2.7" 5 MegaPixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), BLC, HLC, AGC, AWB, 2D-DNR, Support OSD Menu, Max. IR length 20m, Smart IR, IP67, DC12V, Casing Aluminium</p> 	15,900,000
15	DH-HAC-B1A41P	<p>Cooper Series</p> <p>4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Plastic</p> 	11,500,000
16	DH-HAC-B2A41P	<p>Cooper Series</p> <p>4MP HDCVI IR Bullet Camera, 1/2.7" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 3.6mm fixed lens HD and SD output switchable, Max. IR length 20m IP67, DC12V, Casing: Aluminium</p> 	14,000,000
17	HFW1239TLMP-IL-A	<p>Full-Color</p> <p>Microphone icon</p> <p>2MP Smart Dual Illuminators Bullet Camera Progressive CMOS - Focal Length 3.6 mm Max. 30 fps@1080p 0.001 lux@F1.6 (Color, 30 IRE) - 0.0001 lux(B/W, 30 IRE) - 0 lux (Illuminator on) Smart Dual Illuminators - Built-in-mic CVI/CVBS/AHD/TVI Switchable, Support OSD Menu 130 dB true WDR, HLC, BLC, 3D DNR, AGC, AWB 2 LEDs 40m distance - 2 IR Lights 40m distance Smart IR &amp; WL, IP67, DC12V</p> 	22,700,000
18	HFW1239MHP-A-LED	<p>Full-Color</p> <p>Microphone icon</p> <p>2MP Full-color HDCVI Bullet Camera, 1/2.8" CMOS ,24/7 color imaging Max. 30 fps@1080p, 3.6 mm fixed lens (6 mm optional) 50 m illumination distance , Super Adapt, 130 dB true WDR, 3D NR Focal Length 3.6 mm; 6 mm , Built-in mic ,CVI/CVBS/AHD/TVI switchable Min Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on , IP67, DC 12 V</p> 	25,800,000

ج

ت

(ر)

19	DH-HAC-HFW1239TLMP-A-LED	 2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 MP CMOS Minimum Illumination: 0.005Lux/F1.6 1080@25fps, 720@25/50fps 3.6mm fixed lens <b>Built-in mic</b> CVI/CVBS/AHD/TVI Switchable WDR (130 db), BLC, HLC, 2DNR, AGC, AWB Electronic Defog 40m LED distance, IP67, DC12V		20,600,000
20	DH-HAC-HFW1239TLMP-LED	 2M Full-color Starlight HDCVI Bullet Camera 1/2.8 inch 2.16 Mega Pixels Progressive CMOS 0.005Lux/F1.6, 30IRE, 0Lux white Light on Max. 30fps@1080P 3.6mm fixed lens, 16x Digital Zoom CVI/TVI/AHD/CVBS Switchable, Support OSD Menu WDR (130 db), E-Defog/BLC/HLC/AWB/AGC/2D DNR 40m LED Distance Smart Light, IP67, DC12V		20,300,000
21	HAC-HFW1239TP-LED	 2MP Full-color HDCVI Bullet Camera 2MP 1/2.8" Progressive CMOS Max 2MP@25/30fps 3.6mm fixed lens CVI/CVBS/AHD/TVI switchable, Support OSD Menu WDR(130db), BLC, HLC, AWB, AGC, 3D DNR Smart Light, 1 LED 20m Distance, IP67, DC12V		19,500,000
22	DH-HAC-HFW1231RP-Z-A	 2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination: 0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable, <b>Built-in mic</b> , WDR(130dB), BLC, HLC, 3DNR, AGC, AWB 80m LED distance, Smart IR, IP67, DC12V		33,300,000
23	DH-HAC-HFW1231RP-Z-IRE6	 2MP Starlight HDCVI IR Bullet Camera 1/2.8" 2Megapixel CMOS (Starlight) Minimum Illumination: 0.002Lux/F1.5 1080@25fps, 720@25/50fps 2.7-12mm motorized lens HD and SD output switchable WDR(130dB), BLC, HLC, 3DNR, AGC, AWB 80m LED distance, Smart IR, IP67, DC12V		32,500,000
24	DH-HAC-HFW1230RP-Z-IRE6	 2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium		29,500,000
25	DH-HAC-HFW1230TP	 2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens (2.8mm, 6mm Optional) HD and SD output switchable, Support OSD Menu Starlight, DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V, Casing: Aluminium		14,200,000
26	DH-HAC-HFW1230TP-A	 2MP Starlight HDCVI IR Bullet Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, <b>Built-in mic</b> DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V		14,600,000
27	DH-HAC-HFW1230DP	 3.6mm Fixed lens, 25/30fps@1080P & @720P DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, OSD Menu Max. IR length 80m, Smart IR, IP67, DC12V		18,800,000

ج

ت

(ر)

28 DH-HAC-HFW1220THP-I4

**Value STARLIGHT**

2MP Value Starlight HDCVI IR Bullet Camera

1/2.7 inch CMOS

1080P@25fps, 720P@25fps, 720@50fps

3.6mm Fixed lens

Value Starlight

Minimum Illumination:0.008Lux/F1.85

DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D DNR

Smart IR, Eletronic Defog

CVI/CVBS/AHD/TVI switchable

Max. IR length 40m, Smart IR, IP67, DC12V



14,600,000

29 HAC-HFW1209TLMP-LED-0360B

**Full-Color**

2MP Full-color HDCVI Bullet Camera

1/2.8 inch 2MP Progressive CMOS

Max. 30fps@1080P

3.6mm Fixed lens

Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on

DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3D DNR

CVI/CVBS/AHD/TVI switchable, OSD Menu Support

40m LED distance, IP67, DC12V



16,200,000

30 HAC-HFW1209CMP-LED-0360B

**STARLIGHT****Full-Color**

2MP Full Color Starlight HDCVI Bullet CCTV Camera

1/2.8 inch 2.16 Mega Pixels Progressive CMOS

Max 30fps@2MP

3.6mm fixed lens

CVI/TVI/AHD/CVBS Switchable, Support OSD Menu

DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR

20m LED Distance

Smart Light, IP67, DC12V



15,200,000

31 HAC-HFW1209CP-LED-0360B

**Full-Color**

2MP Full-color HDCVI Bullet Camera

1/2.8 inch 2MP Progressive CMOS

Max. 30fps@1080P

3.6mm fixed lens

CVI/CVBS/AHD/TVI Switchable, Support OSD Menu

DWDR/BLC/AWB/AGC/2D DNR

20m LED Distance

Smart Light, IP67, DC12V



12,300,000

**NEW**

32 HAC-HFW1200TLM-IL-A

**DUAL LITE**  
Full-Color

2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera

\* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.

2 MP Progressive CMOS Sensor 3.6 mm Lens: H: 83°; V: 48°; D: 105°

Max. 30 fps@1080P, CVI/CVBS/AHD/TVI switchable

DWDR, BLC, HLC, AWB, AGC, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light,

Illumination Distance IR: 40 m (131.23 ft) Warm light: 40 m (131.23 ft) , Super Adapt, 3D

DNR, Built-in mic, 1 Audio in

Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux

(Illuminator on)

12 VDC, IP67, Metal+Plastic



16,000,000

33 DH-HAC-HFW1200RP-Z-IRE6

**STARLIGHT**

2MP HDCVI IR Bullet Camera, 1/2.7 inch CMOS

Max 30fps@1080P, Min Illumination 0.02Lux/F1.7, 30IRE, 0Lux IR on

Motorized vari-focal 2.7 mm-12 mm, Fixed iris

BLC/HLC/DWDR , Gain Control , Noise Reduction 2D NR , Smart IR

Max. IR length 60m,IP67, DC12V

Built-in mic(-A)



28,500,000

34 DH-HAC-HFW1200TLP

1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P

3.6 &amp; 2.8mm fixed lens

HD and SD output switchable, Support OSD Menu

DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR

Max. IR LEDs length 40m, Smart IR, IP67, DC12V



12,200,000

35 DH-HAC-HFW1200THP-A

**Microphone**

2MP HDCVI IR Bullet Camera

1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P

3.6mm fixed lens (2.8mm, 6mm Optional), Built-in mic

HD and SD output switchable, Support OSD Menu

DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR

Max. IR LEDs length 80m, Smart IR, IP67, DC12V



14,000,000

36 DH-HAC-HFW1200THP-I4

2MP HDCVI IR Bullet Camera

1080P@25fps, 720P@25fps, 720@50fps

3.6mm Fixed lens

Minimum Illumination:0.02Lux/F1.9

DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR

Smart IR, Eletronic Defog

HD and SD output switchable

Max. IR length 40m, Smart IR, IP67, DC12V



13,750,000

.

درا

ب

ل

دار را (Built-in MIC)

و

دوار (دار دار)

ه

د



XVR

ه

د

:

37	DH-HAC-HFW1200DP-0360B-S5	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V	
16,500,000			
38	HAC-HFW1200CMP-0360B	2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V	
13,000,000			
39	HAC-HFW1200CMP-A	2MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP, 3.6mm fixed lens, <b>Built-in mic</b> CVI/TVI/AHD/CVBS output switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR Max. IR length 30m, Smart IR, IP67, DC12V	
14,000,000			
40	HAC-HFW1200CM-IL-A  <b>DUAL LITE</b>  <b>Full-Color</b>	<b>NEW</b> 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera * In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version. 2 MP Progressive CMOS Sensor 3.6 mm: H: 83°; V: 48°; D: 105° Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on) 12 VDC, IP67, Metal	
15,300,000			
41	DH-HAC-HFW1200SP	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V	
13,100,000			
42	DH-HAC-HFW1200TP	25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm/3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 25m, Smart IR, IP67, DC12V	
13,600,000			
43	DH-HAC-HFW1200TP-A  <b>Starlight</b>	1/2.7" 2Megapixel CMOS 3.6mm fixed lens, <b>Built-in mic</b> HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR length 30m, Smart IR, IP67, DC12V	
14,000,000			
44	DH-HAC-HUM3201B  <b>Starlight</b>	1/2.8" 2Megapixel CMOS( <b>Starlight</b> ), 25/30fps@1080P & @720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR, DC12V	
17,200,000			
45	DH-HAC-B2A21P  <b>Cooper Series</b>	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	
10,900,000			
46	DH-HAC-B1A21P  <b>Cooper Series</b>	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Plastic	
8,850,000			
47	DH-HAC-HDW1509TP-IL-A  <b>Starlight</b>  <b>Full-Color</b>	5MP Smart Dual Illuminators Eyeball Camera Max 25 fps@5MP (16:9 video output). 120 dB true WDR, 3D NR Smart Dual Illuminators, 40 m illumination distance Super Adapt, Built-in MIC. 3.6 mm fixed lens (2.8 mm optional). CVI/CVBS/AHD/TVI switchable. IP67, 12 VDC.	
33,900,000			
48	DH-HDW1509TP-A-LED  <b>Starlight</b>  <b>Full-Color</b>	5MP Full-color HDCVI Eyeball Camera Progressive CMOS - Focal Length 2.8 mm Min. Illumination 0.001 Lux/F1.0, 0 Lux warm light on Illumination 2 LEDs Distance 40 m <b>Built-in mic</b> , CVI/CVBS/AHD/TVI switchable WDR 120db, BLC, HLC, HLC-Pro, AWB, AGC, 3DNR Privacy Masking, Smart Light, IP67 , DC 12V	
28,900,000			

		ت	(ر)
49	DH-HAC-HDW1509TLQP-A-LED	 	<p>5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V, Built-in mic</p>  <p>27,500,000</p>
50	DH-HAC-HDW1509TLQP-LED	 	<p>5MP Full-color HDCVI Quick-to-install Eyeball Camera 25fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu 120dB WDR, 3D/2D NR, Day/Night(ICR), AWB, AGC, BLC, HLC 20m illumination distance, Smart IR, IP67, DC12V</p>  <p>24,700,000</p>
51	DH-HAC-HDW1500SLP		<p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP/1080P, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V</p>  <p>14,300,000</p>
52	DH-HAC-HDW1500TRQP-A-0280B-S3		<p>5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP, 1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR, Built-in Mic Max. IR LEDs length 20m, Smart IR, IP50, DC12V</p>  <p>17,200,000</p>
53	DH-HAC-HDW1500TRQP-0280B-S3		<p>5MP Starlight HDCVI Quick-to-install IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 25/30 fps@5MP, 25/30fps@4MP, 1080P@25/30 fps, 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 20m, Smart IR, IP67, DC12V</p>  <p>15,400,000</p>
54	HAC-HDW1500CLQ-IL-A	 	<p><b>NEW</b></p> <p>5MP Smart Dual Light HDCVI Fixed-focal Quick-to-install Eyeball Camera  * In order to use the 5MP 16:9 and the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.000004.1.R.220323 or later version.</p> <p>5MP Progressive CMOS Sensor 2.8 mm: H: 106°; V: 56°; D: 125° Max 25 fps@5MP (16:9 video output), CVI/CVBS/AHD/TVI switchable DWDR, BLC, HLC, AWB, AGC, 2D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic Min. Illumination 0.05 lux@F1.6 (Color, 30 IRE) 0.005 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on) 12VDC, IP67, Plastic, Quick-to-install</p>  <p>20,900,000</p>
55	HAC-T2A51P		<p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP &amp; @1080P (16:9 video output) 3.6mm &amp; 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium</p>  <p>15,900,000</p>
56	HAC-T1A51P		<p>5MP HDCVI IR Eyeball Camera, 1/2.7" 5Megapixel CMOS 20fps@5MP, 25/30fps@4MP, 25/30@1080P (16:9 video output) 3.6mm and 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Plastic</p>  <p>13,300,000</p>
57	DH-HAC-T2A41P		<p>1/2.7" 4Megapixel CMOS, 25/30fps@4MP, 25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, IP67, DC12V, Casing: Aluminium</p>  <p>14,000,000</p>
58	DH-HAC-T1A41P		<p>1/2.7" 4Megapixel CMOS, 25/30fps@4MP, 25/30fps@1080P 2.8mm fixed lens, HD and SD output switchable Max. IR length 20m, DC12V, Casing: Plastic</p>  <p>11,500,000</p>

59	DH-HAC-HDW1239TLP-A-LED	 <b>STARLIGHT Full-Color</b>  <p>2MP Full-color Starlight HDCVI Eyeball Camera 1/2.8 inch 2.16 Mega Pixels CMOS Minimum Illumination:0.005Lux/F1.6 Full-color starlight 1080@25fps, 720@25fps, 720@50fps 3.6 mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Smart Light, Electronic Defog HCVI/CVBS/AHD/TVI switchable <b>Built-in Mic</b> 20m LED distance, IP67, DC12V</p>		19,000,000
60	DH-HAC-HDW1230MP	 <p>2MP Starlight HDCVI IR Eyeball Camera, 1/2.8" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P , 3.6mm Fixed Lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, DC12V</p>		12,500,000
61	HAC-HDW1209TLQP-A-LED-0280B	 <b>Full-Color</b>  <p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens <b>Built-in Mic</b> CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		14,500,000
62	HAC-HDW1209TLQP-LED-0280B	 <b>Full-Color</b>  <p>2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens CVI/CVBS/AHD/TVI Switchable, Support OSD Menu DWDR/BLC/AWB/AGC/2D DNR 20m LED Distance Smart Light, IP67, DC12V</p>		12,600,000
63	DH-HAC-HDBW1200EP	<p>2MP HDCVI IR Dome Camera, 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 2.8mm Fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR, IP67, IK10, DC12V</p>		13,700,000
64	DH-HAC-HDW1200LP	 <p>2MP HDCVI IR Eyeball Camera, 1/2.7" 2Megapixel CMOS Max 30fps@1080P, 2.1mm fixed lens HD and SD output switchable, <b>Built in Mic</b>, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 3m, Smart IR, IP67, DC12V</p>		16,300,000
65	DH-HAC-HDW1200MP	<p>1/2.7" 2Megapixel CMOS, 25/30fps@1080P, <b>Built-in MIC</b> 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V</p>		11,700,000
66	DH-HAC-HDW1200EMP-A <b>Metal Case</b>	 <p>1/2.7" 2Megapixel CMOS , 25/30fps@1080P, <b>Built-in MIC</b> 3.6 &amp; 2.8mm fixed lens Max. IR LEDs length 50m, Smart IR, IP67, DC12V</p>		14,500,000
67	HAC-HDW1200TRQP-A-0280B	  <p>2MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens <b>Built in Mic</b> CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto switch by ICR Max. IR length 25m, Smart IR, IP50, DC12V</p>		12,200,000
68	DH-HAC-HDW1200TLP-A	 <p>2MP HDCVI IR Eyeball Camera 1/2.7 inch CMOS Max 30fps@1080P 2.8mm Fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR <b>Built-in mic</b> Electronic Defog CVI/CVBS/AHD/TVI switchable Max. IR length 30m, Smart IR, IP67, DC12V</p>		12,900,000

NEW

## 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera

\* In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000004.1.R.220323 or later version.

69 HAC-HDW1200CLQ-IL-A



2 MP Progressive CMOS Sensor 2.8 mm: H: 102°; V: 60°; D: 129°  
 Max. 30 fps@1080p, CVI/CVBS/AHD/TVI switchable  
 DWDR, BLC, HLC, AWB, AGC, 3D DNR, Day/Night Auto(ICR)/Color/B/W, Smart Dual Light, Illumination Distance IR: 20m (65.62 ft) Warm light: 20m (65.62 ft), Super Adapt, Built-in mic, 1 Audio in  
 Min. Illumination 0.01 lux@F2.0 (Color, 30 IRE) 0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)  
 12VDC, IP67, Plastic, Quick-to-install



13,600,000

70 DH-HAC-T2A21P

Cooper Series

1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P

2.8mm fixed lens  
 HD and SD output switchable, Support OSD Menu  
 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR



10,900,000

71 DH-HAC-T1A21P

Cooper Series

1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P

2.8mm & 3.6 fixed lens  
 HD and SD output switchable, Support OSD Menu



8,650,000

72 DH-SD59225I-HC-S2

**STARLIGHT**

1/2.8" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P

4.8mm ~ 120mm 25x optical zoom  
 WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus



180,000,000

73 SD59230I-HC

**STARLIGHT**

2MP 30x Starlight IR PTZ HDCVI Camera, 1/2.8" Exmor R CMOS

Max. 25/30fps @1080P(1920x1080) & 50/60fps @720PResolution



210,000,000

74 DH-SD49225I-HC-LA

**STARLIGHT**

2MP 25x Starlight IR PTZ HDCVI Camera, 1/2.8" STARVIS CMOS

Max. 25/30fps @1080P(1920x1080) & 50/60fps @720P Resolution



168,000,000

75 DH-XVR1A04

Cooper Series

4CH Penta-brid 1080N/720P Real-Time Cooper Recorder

H.264 video compression, 4CH: 1/4 Playback



19,750,000

76 XVR1B04-I

Cooper Series

Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2 MP(20 Mbps)]

1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 8 TB



23,900,000

77 DH-XVR1A08


Cooper Series

HDMI , VGA ,simultaneous video Output

1 SATA port, up to 6 TB capacity



24,300,000

78	XVR1B08-I	<b>Wiz Sense</b> Cooper Series	8 Channel Penta-brid 1080p Real-time WizSense Ai XVR H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), 4CH: 1/4/9 Playback HDMI , VGA ,simultaneous video Output 1 SATA port, up to 6 TB capacity 2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification		29,100,000
79	XVR1B08H-I	<b>Wiz Sense</b> AI Cooper Series	8 Channels 5M-N/1080p Cooper 1U 1HDD Digital Video Recorder Supports Full-channel AI-Coding , H.265+/H.265 dual-stream Pentabrid (IP+CVI+AHD+TVI+CVBS) - Max 12 channels IP camera inputs Up to 8 channels SMD Plus Human/Vehicle Classification Encoding Capacity : 5M-N@(10 fps); 4M-N/1080p@(15 fps); 1080N@(25/30 fps) 1/4/8/9 Playback , 1 SATA port, up to 16 TB capacity 2*USB 2.0, Audio In/Out : 1/1 , 10/100 Mbps LAN Interface, P2P Support		50,000,000
80	XVR5104HS-I3	<b>Wiz Sense</b> AI	New GUI V4.0 Support - 4 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 6 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support		40,200,000
81	XVR5104HS-4KL-I3	<b>Wiz Sense</b> AI	New GUI V4.0 Support - 4 Channel Penta-brid 4K WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support		58,900,000
82	XVR5108HS-4KL(V.2)	<b>Wiz Sense</b> AI	New GUI V4.0 Support - 8CH Penta-brid 4K Recorder HDCVI 4K, AHD,5mp, HDTVI 5MP 8+4ch support H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8MP Tripwire, Intrusion, Face Detection, Smart Search 1/1 Audio In/Out, 1 SATA Port , Up to 8TB 1*HDMI, 1*VGA ,simultaneous video Output 2*USB 2.0, 1*10/100 Mbps LAN Interface , P2P Support		84,000,000
83	XVR5108HS-I3	<b>Wiz Sense</b> AI	New GUI V4.0 Support - 8 Channel Penta-brid 5M-N/1080p None Real-Time WizSense Ai XVR 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF H.265+/H.265/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9ch 1 SATA Port up to 10 TB capacity 2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 8ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support		60,500,000

	<b>4K</b>	New GUI V4.0 Support - 8 Channel Penta-brid 4K-N/5MP WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9ch 1 SATA Port up to 10 TB capacity 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support		98,000,000
84	XVR5108HS-4KL-I2	<b>Wiz Sense</b> <b>AI</b>		
85	XVR5108HS-4KL-I3	<b>Wiz Sense</b> <b>AI</b>		98,000,000
86	DH-XVR1B16	<b>Cooper Series</b>		48,000,000
87	XVR1B16-I	<b>Cooper Series</b>		58,850,000
88	XVR5116H-I2	<b>Wiz Sense</b> <b>AI</b>		101,000,000
89	XVR5116HS-S2(V.2)			86,700,000

90	XVR5116HS-I3	<b>WizSense</b> <b>AI</b>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS/IP video inputs Max 24 channels IP camera, up to 6MP; Max 128Mbps incoming bandwidth Supports Full-channel AI Coding / 16 channel SMD / 2 channel face recognition Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA HDD Interface 1 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature -10 °C to +55 °C</p>		101,000,000
91	XVR5216AN-S2(V.2)	<b>WizSense</b> <b>AI</b>	<p>New GUI V4.0 Support - 16CH Penta-brid 5MN/4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder, 5MN/4M-N/1080P@15fps , 1080N/720P@25fps H.264+/H.264 dual-stream video compression 1/4/9/16CH Playback, Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 MP (96 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB HDMI , VGA ,simultaneous video Output, RS485 for PTZ support 2 USB Ports (1 USB 2.0 , 1 USB 3.0) 10/100/1000 Mbps LAN Interface, P2P Support</p>		112,500,000
92	XVR5216AN-I2	<b>WizSense</b> <b>AI</b>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		129,500,000
93	XVR5216AN-I3	<b>WizSense</b> <b>AI</b>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 5M-N/1080P Encode Capacity All channel 5M-N (10 fps); 4M-N/1080p (15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 16+8 channels,each IP Channel up to 6MP Supports Full-channel AI Coding Perimeter Protection : 2 channel, 10 IVS for each channel / Face Detection : 6 attributes , 2 channels each channel up to 12 faces / Face Recognition : 2 channel up to 10 face databases / Full-channel SMD Plus Audio Input : 1, RCA (external) 16, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 2A / Power Consumption Lower than 12 W / Operating Temperature -10 °C to +55 °C</p>		129,500,000
94	XVR5216AN-4KL-I2	<b>WizSense</b> <b>AI</b>	<p>New GUI V4.0 Support - 16 Channel Penta-brid 4KN/5MP WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		196,100,000

95	DH-XVR5216AN-4KL	<p><b>4K</b></p> <p>New GUI V4.0 Support - 16 Channel Embedded Processor 16+8 Channel, each channel up to 8M HDCV 4K, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/ Record rate Main stream: 4K(1~7fps);4MP(1~15fps);1080P (1~25/30f) H.264+/H.26 dual-stream video compression Internal HDD 2 SATA Ports, up to 8TB capacity for each IP Camera Input 8+4/16+8 Channel, each channel up to 8 Audio In/Out 1/1, RC - 2 USB Ports (1 USB 2.0 , 1 USB 3), 1*RS485, 1*1000 Mbps</p>		169,000,000
96	DH-XVR5216AN-4KL-I3	<p><b>Wiz Sense</b> <b>AI</b></p> <p>New GUI V4.0 Support - 16 Channels Penta-brid 4K-N/5MP Encode Capacity All channel 4K@(7fps); 6MP@(10fps); 5MP@(12fps); 4K- N/4MP/3MP@(15fps); 4M-N/1080P(25/30fps); AI Coding; H.265+; H.265; H.264+; H.264 Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 32 channels IP camera inputs, each channel up to 8MP Supports Full-channel AI Coding Perimeter Protection : Advanced Model: 2 channels , General Model: 8 channels ; Face Detection : 2 channels ;Face Recognition : 2 channels , Up to 10 face databases , SMD Plus : 16 channels Audio Input :1-channel RCA , 16-channel BNC 16 / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 12 VDC, 5A / Power Consumption Lower than 15 W(without HDD) / Operating Temperature-10 °C to +55 °C</p>		196,100,000
97	DH-XVR5232AN-S2(V.2)	<p><b>Wiz Sense</b> <b>AI</b></p> <p>New GUI V4.0 Support - 32CH Penta-brid 1080P Recorder 4M-N/1080P@15fps, 1080N/720P@25fps H.264+/H.264 dual-stream video compression 16CH Playback Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 MP(128 Mbps)] Support Smart Search and Intelligent Video System 1/1 Audio In/Out, 2 SATA Port , Up to 16 TB 1*HDMI, 1*VGA ,simultaneous video Output RS485 for PTZ support, 2*USB(1 USB2.0 , 1 USB3.0) 1*10/100/1000 Mbps LAN Interface, P2P Support</p>		181,000,000
98	XVR5232AN-I2	<p><b>Wiz Sense</b> <b>AI</b></p> <p>New GUI V4.0 Support - 32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)+N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support</p>		209,500,000
99	XVR5232AN-I3	<p><b>Wiz Sense</b> <b>AI</b></p> <p>New GUI V4.0 Support - 32 Channels Penta-brid 5M-N/1080P Encode Capacity All channels 5M-N@(10fps); 4M-N/1080P@(15fps) AI Coding/H.265+/H.265 dual-stream video compression Supports HDCVI/AHD/TVI/CVBS 32 IP channels,up to 6MP / bandwidth: 128 Mbps Supports 16-channel AI Coding Perimeter Protection : Up to 4 channels 10 IVS for each channel / Face Detection :2 channels (up to 12 face images/s) / Face Recognition : Up to 2 channels, Up to 10 face databases /16 channels SMD Plus) Audio Input : 1, RCA (external) 32, BNC (coaxial) / Audio Output 1, RCA HDD Interface 2 SATA Port, up to 16TB for a single HDD RS-485 : 1 Port / 2 USB Ports / HDMI / VGA / Network Port 10/100/1000 DC12V, 5A / Power Consumption Lower than 17 W / Operating Temperature -10 °C to +55 °C</p>		209,500,000

(ر.ل)

ل د

ت

100 XVR5432L-I3

**Wiz Sense**

**AI**

32 Channels Penta-brid 5M-N/1080P 4HDDs WizSense Digital Video Recorder  
 H.265+/H.265 dual-stream video compression.  
 Supports 16-channel AI-Coding.  
 Supports HDCVI/AHD/TVI/CVBS/IP video inputs.  
 Max 32 channels IP camera, each channel up to 8MP; 128 Mbps bandwidth.  
 Up to 8 channels video stream (analog channel) perimeter protection.  
 Up to 16 channels video stream (analog channel) SMD plus.  
 Up to 2 channels video stream (analog channel) human face recognition.  
 Perimeter Protection, Face Detection, Face Recognition : Up to 10 face databases with 10,000 face images, SMD Plus  
 Multi-screen Display 1/4/8/9/16/25/36  
 IoT & POS functionalities.



345,000,000

101 DH-XVR4232AN-I

**Wiz Sense**

32 Channels Penta-brid 1080N/720P 1U 2HDDs WizSense Digital Video Recorder  
 Video Compression AI Coding; H.265+; H.265; H.264+; H.264  
 Supports 8-channel AI-Coding.  
 Supports HDCVI/AHD/TVI/CVBS/IP video inputs.  
 Max 16 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth. Multi-screen Display 1/4/8/9/16/25/36  
 Audio Input 1-channel RCA (external) 32-channel BNC (coaxial audio)  
 Two-way Talk, HDD Interface 2 SATA ports, up to 16 TB  
 Up to 16 channels video stream (analog channel) SMD Plus.  
 Long transmission distance over coax cable.



140,000,000

