



آتی نگر الکترونیک

لیست قیمت محصولات تیاندی

Tiandy

آدرس دفتر مرکزی: تهران، خیابان بهشتی،

خیابان احمد قصیر، کوچه ششم غربی،

پلاک ۱، واحد ۱۶:

021-91006008

WWW.TIANDY.CENTER

SPARK

1 IRR 18,300,000

TC-C32QN Spec:I3/E/Y/2.8mm/V5.0

KEY FEATURES

- Plastic Housing
- Up to 1920x1080@25fps
- S+265/H.265/H.264
- DWDR

- Min. illumination Color: 0.02Lux@F2.0
- Smart IR, IR Range: 30m
- Built-in Mic
- Operating Conditions -30°~60°, 0~95% RH
- POE, IP67



2 IRR 18,300,000

TC-C32XN Spec:I3/E/Y/2.8mm/V5.0

- Plastic Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F2.0
- Smart IR, IR Range: 30m
- DWDR

- Operating Conditions -30°~60°, 0~95% RH
- POE



3 IRR 26,000,000

TC-C34QN Spec:I3/E/Y/4mm/V5.0

- Plastic Housing
- Up to 2560x1440@20fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F1.6
- Smart IR, IR Range: 30m
- Built-in Mic
- POE, IP67
- DWDR
- Operating Conditions -30°~60°, 0~95% RH



4 IRR 26,000,000

TC-C34XN Spec:I3/E/Y/2.8mm/V5.0

- 2MP Fixed IR
- Up to 2560x1440@20fps
- Color: 0.02Lux@F1.6
- Operating Conditions -30°~60°, 0~95% RH
- Plastic Housing
- S+265/H.265/H.264
- Smart IR, IR Range: 30m
- POE
- Min. illumination Color: 0.02Lux@F1.6
- Built-in Mic
- DWDR



5 IRR 43,900,000

TC-C32KN Spec:I3/Y/WIFI/2.8mm

- 2MP Fixed IR Wi-Fi Dome Camera
- Up to 1920x1080@30fps
- Min. illumination Color: 0.02Lux@F2.0
- Smart IR, IR Range: 30m
- SD Card Slot
- IP66
- Metal+Plastic Housing
- S+265/H.265/H.264
- DWDR
- Reset button
- Support Wi-Fi



6 IRR 43,900,000

TC-C32WN Spec:I5/Y/WIFI/4mm/V4.0

- Metal+Plastic Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F2.0
- Smart IR, IR Range: 50m
- Operating Conditions -35°C~65°C, 0~95% RH
- Built-in Mic, SD Card Slot, Reset Button
- Support Wi-Fi
- IP67



7 IRR 57,000,000

TC-H334S Spec:I5W/C/WIFI/4mm/4.1

- Metal+Plastic Housing
- Up to 2304x1296@25fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F1.6
- Smart IR, IR Range: 50m
- White Light : 20-30m
- Operating Conditions -30°C~60°C, 0~95% RH
- Built-in Mic, SD Card Slot, Reset Button
- Support Wi-Fi
- IP67



8 IRR 29,800,000

TC-R3105 Spec:I/B/L/S/Eu

- Up to 5-channel input
- S+265/H.265/H.264 video formats
- HDMI Video output at up to 1920x1080 resolution
- 1 SATA interface, up to 6TB for 1 HDD
- 1xRJ45 self-adaptive 10/100 Mbps network interface
- Up to 5MP resolution



9 IRR 48,100,000

TC-R3105 Spec:I/B/P/L/S

- Up to 5-channel input
- S+265/H.265/H.264 video formats
- Up to 5MP resolution
- 8 POE ports
- HDMI Video output at up to 1920 x 1080 resolution
- 1 SATA interface, up to 6TB for 1 HDD
- 1xRJ45 self-adaptive 10/100 Mbps



10 IRR 34,000,000

TC-R3110 Spec:I/B/L/S/Eu

- Up to 10- channel Input
- S+265/H.265/H.264 video formats
- Up to 5MP resolution
- HDMI Video output at up to 4K resolution
- 1 SATA interface, up to 6TB for 1 HDD
- 1xRJ45 self-adaptive 10/100 Mbps



11 IRR 57,950,000

TC-R3110 Spec:I/B/P8/L/S

- S+265/H.265/H.264 video formats
- Up to 10-channel input
- 8 PoE ports
- Up to 5MP resolution
- HDMI Video output at up to 4K (3840 x 2160)resolution
- 1 SATA interface, up to 6TB for 1 HDD



SUPER LITE

12 IRR 22,000,000

TC-C32GN Spec:I5/E/Y/C/2.8mm/V4.2

- 2MP Fixed IR Bullet Camera
- Up to 1920x1080@30fps
- Min. illumination Color: 0.02Lux@F2.0
- Built-In Mic
- Operating Conditions -30°C~60°C, 0~95% RH
- No Power Cable (12V)
- Metal+Plastic Housing
- S+265/H.265/H.264
- Smart IR, IR Range: 50m
- Support tripwire and perimeter
- POE, IP67



13 IRR 22,000,000

TC-C32HN Spec:I3/E/Y/C/2.8mm/V4.2

- 2MP Fixed IR Turret Camera
- Up to 1920x1080@30fps
- Color: 0.02Lux@F2.0
- Support tripwire and perimeter
- 0~95% RH
- POE, IP66
- No Power Cable (12V)
- Metal+Plastic Housing
- S+265/H.265/H.264
- Smart IR, IR Range: 30m
- Built-In Mic
- Operating Conditions -30°C~60°C



14 IRR 26,148,000

TC-C32GN I5/E/Y/C/2.8mm/V4.1

- 2MP Fixed IR Bullet Camera
- 1920x1080@30fps, Metal+Plastic, 1/2.8", 0.02Lux, Digital WDR, 50m IR
- ,S+265/H.265/H.264, IP67
- Mic-in



15 IRR 28,400,000

TC-C32GN Spec:I5/E/Y/C/SD/2.8mm/V4.1

- 1920x1080@30fps, Metal + Macrolon
- 1/2.8", 0.002Lux, 50m IR
- , S+265/H.265/H.264, IP67
- Mic-in,
- DWDR
- 512GB SD-Card



16 IRR 26,148,000

TC-C32HN Spec: I3/E/Y/C/2.8mm/V4.1

- 1/2.8", F2.0, Fixed Iris, Digital WDR, 30m IR, 0.02Lux, 1920x1080@30fps,
- Built-in Mic, IP67, PoE, Metal+Plastic housing, No Power Cable



17 IRR 32,000,000

TC-C34GN Spec:I5/E/Y/C/2.8mm/V4.2

.4MP Fixed IR Bullet Camera ·Metal+Plastic Housing ·Up to 2560×1440@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F1.6 ·Smart IR, IR Range: 50m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP67 ·No Power Cable (12v)



18 IRR 32,000,000

TC-C34HN Spec:I3/E/Y/C/2.8mm/V4.2

.4MP Fixed IR Turret Camera ·Metal+Plastic Housing ·Up to 2560×1440@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.02Lux@F1.6 ·Smart IR, IR Range: 30m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP66 ·No Power Cable (12v)



19 IRR 37,900,000

TC-C34GS Spec: I5/E/Y/C/2.8MM/V4.0

4MP Fixed Starlight IR Bullet Camera
2560×1440@25fps, Metal+Plastic
1/2.7", 0.002Lux, Digital WDR, 50m IR
S+265/H.265/H.264 .IP67 .Mic-in



20 IRR 37,900,000

TC-C34HS Spec:I3/E/Y/C/2.8mm/V4.0

4MP Fixed Turrent Camera ·Metal+Plastic Housing ·Up to 2560x1440@25fps ·S+265/H.265/H.264 ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP66



21 IRR 39,300,000

TC-C34HS Spec:I3/E/Y/C/SD/2.8mm/V4.0

.4MP Fixed Starlight IR Turret Camera ·Metal+Plastic Housing ·Up to 2560×1440@25fps ·S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m ·Built-In Mic ·Support tripwire and perimeter ·Operating Conditions -30°C~60°C, 0~95% RH ·POE, IP66 ·SD Card Slot



LITE SERIES

22 IRR 63,000,000

TC-C34KS Spec:I3/E/Y/2.8mm/V4.0

1/2.7" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux,
2560x1440@30fps, Built-in Mic, IP66, PoE, Metal+Plastic housing



23 IRR 72,000,000

TC-C35KS Spec:I3/E/Y/C/H/2.8mm/V4.0

.5MP Fixed Starlight IR Dome Camera ·Metal+Plastic Housing
·Up to 2560x1940@20fps ·S+265/H.265/H.264 ·Min. illumination
Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m ·Built-In Mic
·Support tripwire and perimeter ·Operating Conditions -35°C~65°C,
0~95% RH ·POE, IP66 ·SD Card Slot



24 IRR 66,000,000

TC-C35WS Spec:I5/E/Y/C/H/2.8mm/V4.0

·Up to 2592x1944@30fps ·S+265/H.265/H.264/M-JPEG
·Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 50m
·Built-in Mic, audio I/O 1/1, alarm I/O 1/1
·Plugin Free ·Operating Conditions -40°C~65°C, 0~95% RH ·POE, IP67



25 IRR 58,700,000

TC-C35XS Spec:I3/E/Y/2.8mm/V4.0

.5MP Fixed Starlight IR Turret Camera ·Default: Metal+Plastic
·Up to 2592x1944@20fps ·S+265/H.265/H.264 ·Min. illumination Color:
0.002Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 30m
·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button
·Operating Conditions -40°C~60°C, 0~95% RH
·POE, IP66



26 IRR 95,500,000

TC-C38KS Spec:I3/E/Y/2.8mm/V4.0

- 8MP Fixed Starlight IR Dome Camera ·Metal+Plastic Housing
- Up to 3840x2160@20fps ·S+265/H.265/H.264
- Min. illumination Color: 0.003Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 30m ·Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -35°~65°, 0~95% RH
- POE, IP67, IK10



27 IRR 108,000,000

TC-C38WS Spec:I5/E/Y/M/2.8mm/V4.0

- 8MP Fixed Starlight IR Bullet Camera ·Full Metal Housing
- Up to 3840x2160@20fps ·S+265/H.265/H.264
- Min. illumination Color: 0.003Lux@F1.6 ·120dB WDR ·Smart IR, IR Range: 50m
- Support tripwire and perimeter ·Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -40°~65°, 0~95% RH ·POE, IP67



28 IRR 108,000,000

TC-C38WS Spec:I5/E/Y/M/4mm/V4.0

- 8MP Fixed Starlight IR Bullet Camera ·Full Metal Housing
- Up to 3840x2160@20fps ·S+265/H.265/H.264
- Min. illumination Color: 0.003Lux@F1.6 ·120dB WDR
- Smart IR, IR Range: 50m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°~65°, 0~95% RH



29 IRR 97,500,000

TC-C38XS Spec:I3/E/Y/M/2.8mm/V4.0

- 8MP Fixed Starlight IR Turret Camera ·Full Metal Housing
- Up to 3840x2160@20fps ·S+265/H.265/H.264
- Min. illumination Color: 0.003Lux@F1.6
- 120dB WDR ·Smart IR, IR Range: 30m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -40°~65°, 0~95% RH
- POE, IP67



30 IRR 174,000,000

TC-H324S Spec:23X/I/E/C/V3.0

- 2MP 23x Starlight IR PTZ Camera ·Up to 1920X1080@30fps ·Optical zoom: 23x
- Smart IR, IR Range: 150m ·S+265/H.265/H.264/M-JPEG ·Intelligent monitoring
- Support Human/Vehicle Classification ·Plugin Free ·IP66



31 IRR 279,300,000

TC-H324S Spec:25X/I/E

- 2MP 25× Starlight IR PTZ Camera Up to 1920×1080@30fps ·Min. illumination Color: 0.001Lux@F1.5 ·Optical zoom: 25×, digital zoom 16×
- Smart IR, IR Range: 150m ·S+265/H.265/H.264/M-JPEG
- Intelligent monitoring/ Face Capture mode ·Support Auto-tracking
- Plugin Free ·IP66, IK10



32 IRR 335,000,000

TC-H354S Spec:23X/I/E/V3.0

- 5MP 23× Starlight IR PoE AI PTZ Camera ·Up to 2880×1620@30fps
- Optical zoom: 23×, digital zoom 16× ·Smart IR, IR Range: 150m
- S+265/H.265/H.264/M-JPEG ·Intelligent monitoring
- Support Human/Vehicle Classification ·Plugin Free ·IP66



33 IRR 33,000,000

TC-R3105 Spec:I/B/L/EU

- S+265/H.265/H.264 video formats
- up to 6MP resolution
- HDMI and VGA ·HDMI Video output at up to 4K (3840x2160) resolution
- 1 SATA interface, up to 8TB for 1 HDD
- 1×RJ45 self-adaptive 10/100 Mbps network interface



34 IRR 52,500,000

TC-R3105 Spec:I/B/P/L

- S+265/H.265/H.264 video formats
- up to 6MP resolution
- 1×HDMI and 1×VGA
- HDMI Video output at up to 4K resolution
- 1 SATA interface, up to 8TB for 1 HDD
- 1×RJ45 self-adaptive 10/100 Mbps network interface
- PoE Port: 4×RJ45 self-adaptive 10/100 Mbps network interfaces



35 IRR 40,500,000

TC-R3108 Spec:I/B

- H.265 1HDD 8ch
- 60Mbps/40Mbps, recording resolution up to 6MP,
- decoding ability 1*6MP, 3*1080p, 4*720p,
- 1 HDMI & 1VGA
- USB interface: 2xUSB 2.0
- Aluminum Plastic housing



36 IRR 37,000,000

TC-R3110 Spec:I/B/L/Eu

- S+265/H.265/H.264 video formats
- up to 6MP resolution
- 1xHDMI and 1xVGA
- HDMI Video output at up to 4K resolution
- 1 SATA interface, up to 8TB for 1 HDD
- 1xRJ45 self-adaptive 10/100 Mbps network interface



37 IRR 43,500,000

TC-R3110 Spec:I/B/V3.0

- S+265/H.265/H.264 video formats
- Up to 10-channel input
- up to 6MP resolution
- HDMI and VGA
- HDMI Video output at up to 4K(3840 × 2160) resolution
- 1 SATA interface, up to 10TB for 1 HDD
- 1xRJ45 self-adaptive 10/100 Mbps network interface



38 IRR 85,900,000

TC-R3120 Spec:I/B/K/V3.0

- S+265/H.265/H.264 video formats
- Up to 20-channel input
- up to 8MP resolution
- HDMI and VGA
- HDMI Video output at up to 4K (3840×2160) resolution
- 1 SATA interface, up to 10TB for 1 HDD
- 1xRJ45 self-adaptive 10/100 Mbps network interface



39 IRR 119,000,000

TC-R3220 Spec:I/B/K

- S+265/H.265/H.264 video formats
- Up to 20-channel input
- up to 8MP resolution
- HDMI and VGA
- HDMI Video output at up to 4K (3840×2160) resolution
- 2 SATA interfaces, up to 10TB for each HDD
- 1xRJ45 self-adaptive 10/100/1000 Mbps network interface



40 IRR139,000,000

TC-R3232 Spec:I/B/K/V3.1

- S+265/H.265/H.264 video formats
- up to 8MP resolution HD Output
- 1×HDMI and 1×VGA
- HDMI Video output at up to 4K resolution
- 2 SATA interface, up to 10TB for 1 HDD
- 1×RJ45 self-adaptive 10/100/1000 Mbps network interface



41 IRR 182,000,000

TC-R3432 Spec:I/B/K/V3.1

- S+265/H.265/H.264 video formats
- up to 8MP resolution HD Output
- 1×HDMI and 1×VGA
- HDMI Video output at up to 4K resolution
- 1 SATA interface, up to 10TB for 1 HDD
- 1×RJ45 self-adaptive 10/100/1000 Mbps network interface
- PoE Port: 8×RJ45 self-adaptive 10/100 Mbps network interfaces



42 IRR 245,000,000

TC-R3440 Spec:I/B/N/H/C

- S+265/H.265/H.264 video formats
- Up to 40-channel input • up to 12MP resolution
- HDMI and VGA
- HDMI Video output at up to 4K resolution (3840 × 2160)
- 4 SATA interface, up to 10TB for each HDD
- 2×RJ45 self-adaptive 10/100/1000 Mbps network interface



COLOR MAKER

43 IRR 41,000,000

TC-C32WP Spec: I5/E/Y/2.8mm(4mm)/V4.0

- .2MP Fixed Super Starlight IR Bullet Camera
- Default: Metal+Plastic, M: Metal Housing
- Up to 1920x1080@30fps • S+265/H.265/H.264
- Min. illumination Color: 0.0008Lux@F1.6 • Smart IR, IR Range: 50m
- Support tripwire and perimeter • Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -40~65, 0~95% RH • POE, IP67



44 IRR 46,800,000

TC-C32WP Spec:I5W/E/Y/M/2.8mm/V4.2

- 2MP Fixed Color Maker Bullet Camera ·Default: Plastic, M: Metal Housing
- Up to 1920x1080@30fps ·S+265/H.265/H.264
- Min. illumination Color: 0.0008Lux@F1.6 ·2 Warm lights, 15~20m
- Smart IR, IR Range: 50m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button ·Operating Conditions -35~60, 0~95%RH
- POE, IP67



45 IRR 36,000,000

TC-C32XP Spec:W/E/Y/2.8mm/V4.2

- Metal+Plastic Housing ·Up to 1920x1080@30fps
- S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6
- Smart IR, IR Range: 30m ·2 Warm lights, 15m
- Support tripwire and perimeter ·Built-in Mic, support max 512G Micro SD Card
- Operating Conditions -40~65, 0~95% RH
- POE,DC12V ·IP66



46 IRR 38,700,000

TC-C32XP Spec:I3W/E/Y/2.8mm/V4.2

- 2MP Fixed Color Maker Turret Camera (colormaker)
- Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264
- Min. illumination Color: 0.002Lux@F1.6 ·Smart IR, IR Range: 30m
- 2 Warm lights, 15m ·Support tripwire and perimeter
- Built-in Mic, support max 512G Micro SD Card ·Operating Conditions -40~65, 0~95% RH
- POE,DC12V ·IP66



47 IRR 57,500,000

TC-C34XP Spec:W/E/Y/M/2.8mm/V4.0

- 4MP Fixed Color Maker Turret Camera ·Default: Metal+Plastic, M: Metal Housing
- Up to 2592x1520@25fps ·S+265/H.265/H.264
- Min. illumination Color: 0.0008Lux@F1.0 ·120dB WDR
- 2 Warm lights, 15~20m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -40~60, 0~95% RH ·POE, IP67



48 IRR 88,550,000

TC-C34UP Spec:W/E/Y/M/4mm/V4.0

- 4MP Fixed Color Maker Bullet Camera ·Full Metal Housing
- Up to 2560x1440@25fps ·S+265/H.265/H.264
- Min. illumination Color: 0.0002Lux@F1.0 ·120dB WDR
- 4 Warmlights, 20~30m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -40~60, 0~95% RH ·POE, IP67



ECO PRO

49 IRR 79,000,000

TC-C32MS SPEC:I3/A/E/Y/M/C/H/2.7-13.5MM/V4.0

- 2MP Starlight Motorized IR Dome Camera ·Full Metal Housing
- Motorized Lens 2.7-13.5mm ·Up to 1920x1080@30fps
- S+265/H.265/H.264 ·Min. illumination Color: 0.001Lux@F1.6
- Smart IR, IR Range: 50m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button ·Audio I/O 1/1, Alarm I/O 2/1
- Operating Conditions -35~60, 0~95% RH ·POE, IP67,IK10



50 IRR 81,000,000

TC-C35US Spec:I8/A/E/Y/M/C/H/2.7-13.5mm

- 5MP Motorized Starlight IR Bullet Camera ·Full Metal Housing
- Motorized Lens 2.7-13.5mm ·Up to 2592x1944@20fps
- S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6
- Smart IR, IR Range: 80m ·Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button ·Audio I/O 1/1, Alarm I/O 1/1
- Operating Conditions -35~60, 0~95% RH ·POE, IP67



51 IRR 98,000,000

TC-C35MS Spec:I3/A/E/Y/M/2.8-12mm

- 5MP Dome Camera · Full Metal Housing
- Motorized Lens 2.8-12mm ·Up to 2592x1944@20fps
- S+265/H.265/H.264 ·Min. illumination Color: 0.001Lux@F1.6
- IR Range: 30m ·Support tripwire and perimeter
- Micro SD Card Slot, Reset Button ·Audio I/O Mic in , Alarm I/O N/A
- Operating Conditions -40~65, 0~95% RH ·POE, IP67, IK10



52 IRR 98,000,000

TC-C35US Spec:I8/A/E/Y/M/C/H/2.7-13.5mm/V4.0

- 5MP Starlight IP BulletA Metal Eco H 2.7-13.5mm ·Up to 2592X1944@20fps
- S+265/H.265/H.264
- Min. illumination Color: 0.002Lux@F1.6
- 120dB WDR
- Smart IR, IR Range: 80m
- Operating Conditions -35°C~60°C, 0~95% RH
- POE



53 IRR 51,250,000

TC-C32KS Spec:I3/E/Y/C/H/2.8mm/V4.0

2MP Fixed Starlight IR Dome Camera

- Metal+Plastic Housing ·Up to 1920x1080@30fps ·S+265/H.265/H.264
- Min. illumination Color:0.002Lux@F1.6 ·Smart IR,IR Range:30m ·Support tripwire and perimeter ·Built-in Mic,SD Card Slot,Reset Button ·Audio I/O 1/1,Alarm I/O 1/1
- Operating Conditions -35°C~65°C,0~95% RH ·POE,IP66,IK10



TRI-LIGHT

54 IRR 49,000,000

TC-C34WS Spec:I5W/E/Y/2.8mm/V4.2

4MP Fixed Starlight IR Bullet Camera

- Metal+Plastic Housing ·Up to 2560x1520@25fps
- S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6
- 120dB WDR ·2 warm lights,15m ·Smart IR, IR Range: 50m
- Support tripwire and perimeter
- Built-in Mic, support max 512G micro SD Card
- Operating Conditions -40~60, 0~95% RH ·POE, DC12V ·IP67,IK10



55 IRR 53,900,000

TC-C34WS Spec:I5W/E/Y/M/2.8mm/V4.2

4MP Fixed Color Maker IR Bullet Camera

- Metal Housing ·Up to 2592x1520@25fps ·S+265/H.265/H.264
- Min. illumination Color: 0.002Lux@F1.6 ·120dB WDR
- 2 Warm lights, 15m ·Smart IR, IR Range: 50m
- Support tripwire and perimeter ·Built-in Mic, support max 512G Micro SD Card
- Operating Conditions -40~65, 0~95% RH ·POE, DC12V ·IP67



56 IRR 49,000,000

TC-C34XS Spec:I3W/E/Y/2.8mm/V4.2

4MP Fixed Color Maker IR Turret Camera

- Metal+Plastic Housing ·Up to 2560x1440@25fps
- S+265/H.265/H.264 ·Min. illumination Color: 0.002Lux@F1.6
- 120dB WDR ·2 Warm lights, 15m ·Smart IR, IR Range: 30m
- Support tripwire and perimeter ·Built-in Mic, support max 512G Micro SD Card
- Operating Conditions -40~65, 0~95% RH ·POE,DC12V ·IP66



PRO

57 IRR 229,400,000

TC-R3220 Spec:I/B/P16/K/V3.0

- S+265/H.265/H.264 video formats
- Up to 20-channel input • 16 PoE ports .up to 8MP resolution
- 1xHDMI and 1xVGA
- HDMI Video output at up to 4K (3840 × 2160) resolution
- 2 SATA interfaces, up to 10TB for each HDD
- 1xRJ45 self-adaptive 10/100/1000 Mbps network interface
- PoE Port: 16xRJ45 self-adaptive 10/100 Mbps network interfaces



58 IRR 142,000,000

TC-C35TS Spec:I8/A/E/Y/M/H/2.7-13.5mm/V4.0

- 5MP Starlight Motorized IR Bullet Camera · Full Metal Housing · Motorized Lens 2.7-13.5mm · Up to 2592x1944@30fps, 1920x1080@60fps
- S+265/H.265/H.264/M-JPEG · Min. illumination Color: 0.001Lux@F1.6 · Smart IR, IR Range: 80m · Support Video Analytics · Support Human/Vehicle Classification
- Support Face Capture Mode · Built-in Mic, Audio I/O 1/1, alarm I/O 2/1
- Plugin Free · Operating Conditions -35~65, 0~95% RH · POE, IP67



59 IRR 388,500,000

TC-R3440 Spec:I/B/N

- S+265/H.265/H.264 video formats
- Up to 40 IP cameras can be connected
- up to 12MP resolution
- HDMI and VGA
- HDMI Video output at up to 4K (3840 × 2160) resolution
- 4 SATA interfaces , up to 10TB for each HDD
- 2xRJ45 self-adaptive 10/100/1000 Mbps network interfaces



ECO PRO

60 IRR 142,000,000

TC-C34LP I5/A/E/M/H 2.7-13.5MM

- Full Metal Housing · Motorized Lens 2.7-13.5mm
- Up to 2560x1440@30fps, 1920x1080@60fps · S+265/H.265/H.264/M-JPEG
- Min. illumination Color: 0.0004Lux@F1.2 · Smart IR, IR Range: 80m
- Support Human/Vehicle Classification · Support Face Capture Mode
- Support Early Warning · Built-in Mic&Speaker, audio I/O 1/1, alarm I/O 2/1
- Plugin Free · Operating Conditions -35~65, 0~95% RH · POE, IP67, IK10

