












Turbo HD Camera DVR			
Items	Description	User Price	
Turbo HD - 1MP			
1	DS-2CE16C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 6,160,000	
2	DS-2CE56C0T-IRP 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR	IRR 5,410,000	
3	DS-2CE56C0T-IRPF 1.0 Megapixel high-performance CMOS - Analog HD output, up to 720P resolution - True Day/Night - Up to 20m IR distance - Video Frame Rate: 720p@25fps/720p@30fps - Min. Illumination : 0.01 Lux - IP66 weatherproof - DNR, Smart IR - Switchable TVI/AHD/CVI/CVBS	IRR 5,820,000	
Turbo HD - 2MP			
4	DS-2CE16D0T-IF 2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR	ناموجود	
5	DS-2CE16D0T-IRF 2 MP Fixed Mini Bullet Camera 2 MP bullet camera Smart IR: up to 20 m IR distance Water and dust resistant (IP66) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS);	IRR 9,500,000	
6	DS-2CE16D0T-ITFS 2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 10,180,000	
7	DS-2CE16D0T-IT3 2 MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens - IP66 weatherproof	IRR 12,310,000	
8	DS-2CE16D0T-VFIR3F 2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 20,210,000	
9	DS-2CE56D0T-IPF 2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 20 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - True Day/Night, Smart IR	ناموجود	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن












 t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com

11	DS-2CE76D0T-ITPF	2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 7,870,000	
12	DS-2CE76D0T-ITMF	2 MP turret camera. EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67) 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS).	IRR 9,600,000	
13	DS-2CE76D0T-ITMFS	2 MP coaxial audio camera Enhancing safety with discreet and economical built-in microphone Transmits audio over the coaxial cable EXIR 2.0: advanced infrared technology with 30 m IR distance Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 10,180,000	
14	DS-2CE56D0T-VFIR3F	2 MP high performance CMOS - 1920 × 1080 resolution - 2.8 mm, 3.6 mm fixed lens - Up to 40 m IR distance - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP66 weatherproof - True Day/Night, Smart IR - Lens 2.8 - 12 mm @ F1.4	IRR 15,600,000	
15	Turbo HD - 2MP built-in PoC			
16	DS-2CE16D0T-IRE	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 10,810,000	
17	DS-2CE16D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu. IP66, 2.8/3.6/6mm Lens	ناموجود	
18	DS-2CE56D0T-IT1E	2M HD1080p CMOS Sensor , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 9,950,000	
19	DS-2CE56D0T-IT3E	2M HD1080p CMOS Sensor , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu, IP66, 2.8/3.6/6mm Lens	IRR 13,720,000	
20	Turbo HD - 2MP - Starlight Value Series			
21	DS-2CE16D3T-I3F	2 MP high-performance CMOS .Ultra low light . 1920 × 1080 resolution . 2.8 mm, 3.6 mm, 6 mm fixed lens .Smart IR, up to 30 m IR distance . OSD menu, 3D DNR, 120 dB true WDR , day/night switch .4 in 1 video output (switchable TVI/AHD/CVI/CVBS) .IP67.Up the coax (HIKVISION-C)	IRR 11,180,000	
22	DS-2CE56D8T-ITME	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2 , 12 VDC/ built-in PoC , Smart IR, 3D DNR , OSD Menu, 120 dB True WDR , IP67, 2.8/3.6/6mm Lens	IRR 16,630,000	
23	DS-2CE56D8T-IT1E	2.0 megapixel high-performance CMOS, EXIR 2.0, smart IR, up to 20 m IR distance, Outdoor EXIR Bullet, ICR, Ultra Low-Light 0.005 Lux/F1.2, 12 VDC/ built-in PoC , Smart IR, 3D DNR, OSD Menu, 120 dB True WDR, IP67, 2.8/3.6/6mm Lens	IRR 17,460,000	

آتیه نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن













t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com

24 Turbo HD - 3MP				
25	DS-2CE56F1T-IT3	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8mm, 3.6mm, 6mm lens - True Day/Night - OSD menu, DNR, Smart IR - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 12,940,000	
26	DS-2CE56F7T-IT3Z	3 Megapixel high-performance CMOS - Analog HD output, up to 3MP resolution - 2.8-12mm motorized vari-focal lens - True Day/Night - OSD menu, DNR, Smart IR - True WDR , up to 120dB - EXIR technology, up to 40m IR distance - IP66 weatherproof	IRR 33,260,000	
27 Turbo HD - 5MP				
28	DS-2CE16H0T-ITF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 11,600,000	
29	DS-2CE16H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 13,120,000	
30	DS-2CE16H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 14,580,000	
31	DS-2CE16H0T-IT5F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 80 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 17,880,000	
32	DS-2CE16H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 28,690,000	
33	DS-2CE76H0T-ITMF	5 MP coaxial - Enhanced safety with discreet and economical Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 11,380,000	
34	DS-2CE76H0T-ITMFS	5 MP coaxial audio camera , Enhanced safety with discreet and economical built-in microphone Transmit audio over coaxial cable, EXIR 2.0: advanced infrared technology with 30 m IR distance, Water and dust resistant (IP67), 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)	IRR 12,500,000	
35	DS-2CE56H0T-ITMF	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 12,890,000	

آتیه نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن











 t.me/TehranHikvision
 t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجمع تجاری یگانه)



www.atineh.com
www.basicctv.com

36	DS-2CE56H0T-IT1F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 11,690,000	
37	DS-2CE56H0T-IT3F	5 MP high performance COMS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 16,250,000	
38	DS-2CE56H0T-IT3ZF	5 MP high performance COMS - 2560 × 1944 resolution - 2.7 mm to 13.5 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, 2D DNR, DWDR - 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - IP67	IRR 21,490,000	
39	Turbo HD - 5MP - built-in PoC			
40	DS-2CE56H1T-ITME	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 14,200,000	
41	DS-2CE56H1T-IT1E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 20 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 19,960,000	
42	DS-2CE56H1T-IT3E	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67- PoC.af	IRR 21,620,000	
43	DS-2CE56H1T-IT3ZE	5 MP high-performance CMOS - 2560 × 1944 resolution - 2.8 mm to 12 mm motorized vari-focal lens - EXIR 2.0, smart IR, up to 40 m IR distance - OSD menu, DNR, DWDR - IP67 - PoC.at	ناموجود	
44	DS-2CC52H1T-FITS	5MP IR Fisheye Camera, 5 Megapixel high-performance CMOS, Analog HD output, up to 5MP resolution, 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR, IR cut filter with auto switch, OSD menu, Built-in microphone, 1-ch audio output	ناموجود	
45	TURBO HD 5MP (TURBO HD 5.0) PIR Series			
46	DS-2CE11H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 14,550,000	
47	DS-2CE12H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 15,800,000	

آتیه نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن




t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com

48	DS-2CE71H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens - PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 14,550,000	
49	Turbo HD - 8MP			
50	DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 24,840,000	
51	DS-2CE18U8T-IT3	4K Ultra-Low Light Bullet Camera - 8.29 Megapixel high-performance CMOS - Ultra-low light - 3840 × 2160 resolution - 2.8 mm, 3.6 mm, 6 mm fixed focal lens - 120 dB true WDR, 3D DNR - EXIR 2.0, smart IR, up to 60m IR distance - IP67	IRR 26,360,000	
52	Turbo HD PTZ Camera			
53	DS-2AE4225TI-D	High quality imaging with 2 MP resolution - Excellent low-light performance via powered-by-DarkFighter technology - Clear imaging against strong back lighting due to 120 dB WDR technology - Pan and tilt ability enables camera to monitor zones of interest - 25 × optical zoom allows for closer viewing of subjects in expansive areas - Up to 100 m IR range ensures safety at night - Water and dust resistant (IP66)	IRR 105,330,000	
54	DS-2AE5223TI-A (24VAC)	1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output - 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	ناموجود	
55	DS-2AE7230TI-A (24VAC)	High performance 1/3" CMOS - Max. image resolution: 1920 × 1080 - Min. illumination: Color: 0.05Lux @ (F1.6,AGC ON); B/W: 0.005Lux @ (F1.6, AGC ON); 0 Lux with IR - 30× optical zoom, focal length 4-120mm - 16× digital zoom - 120m IR distance - IR cut filter - 3D DNR, Digital WDR, BLC - TVI and CVBS dual output	IRR 212,830,000	
56	Turbo HD DVR 720P / 1080p lite			
57	DS-7208HGHI-F1	Analog video input 8-ch - Encoding resolution 1080p lite/HD 720p lite/WD1/4CIF/VGA/CIF - Video compression H.264+/H.264 - Full channel recording at up to 1080p lite resolution - Frame rate: 1080p lite/HD 720p lite/WD1/4CIF/VGA@12fps; CIF@25fps (P)/30fps (N) - IP video input 2-ch (up to 10-ch) Up to 2 MP resolution - Support H.264+/H.264 IP cameras - Audio input 1-ch - HDMI output 1-ch, 1920 × 1080/60Hz - Capacity 1 SATA interface Up to 6 TB capacity	IRR 26,300,000	
58	DS-7216HGHI-K1	Analog video input 16-ch - Encoding resolution 1080p lite/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 1080p lite resolution - Frame rate: 1080p lite/720p lite/WD1/4CIF/VGA@15fps; CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 18-ch) Up to 5 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 29,490,000	
59	Turbo HD DVR 1080p / 3MP / 4MP lite			

آیة نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن



t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com

60	DS-7204HQHI-K1	Analog video input 4-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 2-ch (up to 6-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 26,620,000	
61	DS-7208HQHI-K1/Eco	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - ECO CASE	IRR 38,020,000	
62	DS-7208HQHI-K1	Analog video input 8-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 4-ch (up to 12-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 1920 × 1080/60Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 40,140,000	
63	DS-7116HQHI-K1	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 6 TB capacity	IRR 46,070,000	
64	7216HQHI-K1-Eco	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity - ECO CASE	IRR 65,460,000	
65	DS-7216HQHI-K1	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity	IRR 61,800,000	
66	DS-7216HQHI-K2	Analog video input 16-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 24-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 × 2160)/30Hz - Audio input 1-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk	IRR 67,610,000	
67	DS-7224HQHI-K2	Analog video input 24-ch - Encoding resolution 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - Frame rate: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - IP video input : 8ch (up to 32-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output : 1-ch, 4K (3840 ×	ناموجود	

آیة نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن



t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com

		2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk		
68	DS-7232HQHI-K2	<u>Analog video input</u> 32-ch - <u>Encoding resolution</u> 4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 4 MP lite resolution - <u>Frame rate</u> : 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) - <u>IP video input</u> : 8ch (up to 40-ch) Up to 6 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> : 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 1-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 118,210,000	
69	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite			
70	DS-7204HUHI-K1	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 1920 × 1080/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 42,840,000	
71	DS-7208HUHI-K1	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> :8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity	IRR 61,260,000	
72	DS-7216HUHI-K2	<u>Analog video input</u> 16-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 16-ch (up to 32-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk	IRR 116,500,000	
73	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP lite (Built in PoC Series)			
74	DS-7204HUHI-K1/P	<u>Analog video input</u> 4-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - 8 MP@8 fps is only available for channel 1 of DS-7204HUHI-K1 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch 2K (2560 × 1440)/60Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 1 SATA interface Up to 10 TB capacity - Provide power supply to PoC cameras over coaxial cable	IRR 47,050,000	
75	DS-7208HUHI-K2/P	<u>Analog video input</u> 8-ch - <u>Encoding resolution</u> 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - <u>Video compression</u> H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - <u>Frame rate</u> : 8 MP@8 fps/5MP@12 fps/4 MP@15 fps/3 MP@18 fps 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - <u>IP video input</u> : 8-ch (up to 12-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - <u>HDMI output</u> 1-ch, 4K (3840 × 2160)/30Hz - <u>Audio input</u> 4-ch, RCA - <u>Capacity</u> 2 SATA interface Up to 10 TB capacity for each disk - Provide power supply to PoC cameras over coaxial cable	IRR 87,770,000	
76	Turbo HD DVR 1080p / 3MP / 4MP / 5MP / 8MP			

آتے نگر الکترونیک نماینده رسعے فروش محصولات هایک ویژن





t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com

77	DS-7204HTHI-K1	<p>Analog video input 4-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Full channel recording at up to 8 MP resolution - Frame rate: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 4-ch (up to 8-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 1 SATA interface Up to 10 TB capacity</p>	IRR 49,890,000	
78	DS-7208HTHI-K2	<p>Analog video input 8-ch - Encoding resolution 8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF - Video compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 - Frame rate: 8 MP@15 fps, 5 MP@20 fps, 3 MP@18 fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) - IP video input : 8-ch (up to 16-ch) Up to 8 MP resolution - Support H.265+/H.265/H.264+/H.264 IP cameras - HDMI output 1-ch, 4K (3840 × 2160)/30Hz - Audio input 4-ch, RCA - Capacity 2 SATA interface Up to 10 TB capacity for each disk</p>	IRR 96,990,000	

آتیه نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن



t.me/TehranHikvision
t.me/HikvisionYeganeh



۰۲۱۹۱۰۰۶۰۰۸ - دفتر مرکزی فروش
۰۲۱۶۶۳۴۲۷۶۶ - فروشگاه (مجتمع تجاری یگانه)



www.atineh.com
www.basicctv.com