
























NO	Product	Features	Price	Picture
1	DS-2CD2020F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE cable, , Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi	IRR 6,270,000	
2	DS-2CD2042WD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	IRR 8,850,000	
3	DS-2CD2052-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	IRR 11,440,000	
4	DS-2CD2120F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile	IRR 6,270,000	





		Monitoring via EZVIZ P2P		
5	DS-2CD2120F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	IRR 6,828,000	
	DS-2CD2142FWD-I	Up to 4 megapixel high resolution, Dual stream, 2.8mm/4mm/6mm fixed lens, 120dB Wide Dynamic Range, 3D Digital Noise Reduction, DC12V & PoE, Support H.264+, Up to 30m IR range, IP67 weather-proof protection, -S: Audio/Alarm IO	IRR 9,220,000	
6	DS-2CD2142FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB (SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 9,600,000	





7	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 11,980,000	
8	DS-2CD2322WD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6/8/12mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 9,400,000	
9	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 10,330,000	
10	DS-2CD2352-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 12,520,000	
11	DS-2CD2420F-IW	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	IRR 6,820,000	

12	DS-2CD2442FWD-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams,DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to10m, support on-board storage up to 128GB(SD card not included), built-in WIFI	IRR 9,310,000	
	DS-2CD2520F	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution,Standard video compression with high compression ratio,Progressive scan CMOS,PoE (Power over Ethernet),Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB ,3D Digital Noise Reduction	IRR 6,480,000	
13	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service -S: Built-in MIC, audio/alarm IO	ناموجود	
14	DS-2CD2620F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P <b>-Z:Motorized VF lens</b>	ناموجود	





15	DS-2CD2620F-IZ	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V &amp; PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P</p> <p><b>-Z:Motorized VF lens</b></p>	ناموجود	
16	DS-2CD2622FWD-IS	<p>1/2.8" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service</p> <p><b>-S: Audio/alarm IO</b></p>	ناموجود	
17	DS-2CD2642FWD-IS	<p>1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service</p> <p><b>-S: Audio/alarm IO</b></p>	ناموجود	
18	DS-2CD2642FWD-IZS	<p>1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service</p> <p><b>-S: Audio/alarm IO</b></p>	ناموجود	





		-Z: Motorized VF lens		
19	DS-2CD2652F-IS	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2560×1920:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service -S: Audio/alarm IO	ناموجود	
20	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	ناموجود	
21	DS-2CD2720F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	ناموجود	




22	DS-2CD2722FWD-IS	1/2.8" Progressive Scan CMOS, Up to 2 megapixel resolution, 120dB WDR, 3D DNR, Up to 30 meters IR range, Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB, Audio/alarm I/O (-S), Mobile Monitoring via cloud P2P or iVMS-4500,	IRR 13,700,000	
23	DS-2CD2742FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO	ناموجود	
24	DS-2CD2742FWD-IZS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO -Z: Motorized VF lens	ناموجود	
25	DS-2CD2752F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO	ناموجود	







26	DS-2CD2752F-IZS	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, 3 streams, IP67, DC12V &amp; PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service</p> <p>-S: Audio/alarm IO -Z: Motorized VF lens</p>	ناموجود	
27	DS-2CD2942F-IS	<p>1/3" Progressive CMOS, Electronic Day/night, Up to 2464 x 1520 resolution, 1.6mm/F1.6 fixed lens, 180° Panoramic view, H.264/MJPEG, 3D DNR, DC12V &amp; PoE, Support on-board storage up to 64GB (SD card not included), software de-warping via iVMS5200 or iVMS4200, Support mobile monitoring via HIK-cloud P2P</p> <p>-I: 3pcs IR LEDs, up to 10m IR -S: Audio/Alarm IO -W: Built-in Wi-Fi</p>	IRR 21,000,000	
27	DS-2CD2T22WD-I3	<p>1/2.8" Progressive Scan CMOS. Up to 2 megapixel resolution. Full HD1080p real-time video. 120dB Wide Dynamic Range. 3D DNR.EXIR high performance LED. Up to 30/50/80 meters IR range. 12V DC±25% &amp; PoE(802.3af Class3). Support H.264+. IP67</p>	IRR 8,280,000	
	DS-2CD2T42WD-I3	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG,VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service</p> <p>-I3: 1pcs EXIR LED, up to 30m IR range</p>	IRR 9,970,000	











38	DS-2CD2T42WD-I5	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG,VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service</p> <p>-I5: 2pcs EXIR LEDs, up to 50m IR range</p>	ناموجود	
29	DS-2CD2T42WD-I8	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG,VCA functions; 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service</p> <p>-I8: 4pcs EXIR LEDs, up to 80m IR range</p>	IRR 11,660,000	
30	DS-2CD2T52-I5	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range</p>	IRR 12,550,000	
31	DS-2CD2F52F-IS	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V &amp; PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service</p> <p>-S: Audio/Alarm IO</p>	IRR 14,920,000	






32	DS-2CD2D14WD	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	IRR 7,630,000	
33	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional (Black, Silver, Golden) -W: Built-in Wi-Fi	IRR 8,620,000	
34	DS-2CD2Q10FD-IW	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection, Support Mobile Monitoring via EZVIZ P2P	IRR 8,160,000	
35	DS-2CV2Q21FD-IW/32GB-T	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. Default: No SD card included.	IRR 9,210,000	

		/32GB-T: Include 16GB sd card.		
36	DS-2CV2U21FD-IW/32GB-T	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. /32GB-T: Include 32GB sd card.	IRR 7,370,000	
37	DS-2DE4220IW-DE	2MP, 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	IRR 32,740,000	
38	DS-2DE5220IW-AE	H.265+/H.265/H.264+/H.264; 2MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 46,260,000	

39	DS-2DE5230W-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	IRR 56,720,000	
40	DS-2DE7220IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 52,910,000	
41	DS-2DE7230IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 66,190,000	
47	DS-7604NI-E1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 6,624,000	
48	DS-7604NI-E1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 9,860,000	
49	DS-7604NI-K1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 7,935,000	

50	DS-7604NI-K1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	ناموجود	
51	DS-7608NI-E2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, <b>380 1U case</b>	IRR 9,257,500	
52	DS-7608NI-E2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, <b>380 1U case</b>	ناموجود	
53	DS-7608NI-K2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	ناموجود	
54	DS-7608NI-K2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	ناموجود	
55	DS-7616NI-E2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, <b>380 1U case</b>	IRR 10,200,500	
56	DS-7616NI-E2/8P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, <b>380 1U case</b>	IRR 16,310,000	

57	DS-7616NI-E2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, <b>380 1U case</b>	IRR 20,964,500	
58	DS-7616NI-K2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	ناموجود	
59	DS-7616NI-K2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 24,725,000	
60	DS-7716NI-E4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	
61	DS-7716NI-E4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 30,969,500	
62	DS-7716NI-K4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 24,840,000	
63	DS-7716NI-K4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 35,121,000	

64	DS-7732NI-K4	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	
65	DS-7732NI-K4/16P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 41,158,500	
66	DS-7732NI-E4	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	
67	DS-7732NI-E4/16P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 37,007,000	
68	DS-7600NI-E1/A/1T	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, 22 inch monitor, <b>1TB HDD WD10JUCT pre-installed</b>	ناموجود	

آدرس: تهران، خیابان مطهری، تقاطع سهروردی، پلاک 123، شرکت آتی نگر الکترونیک (تهران داهوا)