

کلیه محصولات شامل گارانتی 24 ماهه پارس ارتباط می باشند



HIKVISION











نماینده رسمی فروش محصولات هایک ویژن در سراسر ایران

تلفن های واحد فروش و پشتیبانی فنی

۰۲۱-۸۸۳۹۸۷۴۱
۰۲۱-۸۸۳۹۸۷۴۲

لیست قیمت هایک ویژن (Network Camera - NVR)

قیمت های قرمز رنگ قیمت جدید می باشد. در صورت درخواست قیمت های دیگر تماس بگیرید.

تصویر	قیمت محصول (ریال)	ویژگی ها	محصول
20 Series			
	IRR 12,630,000	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE cable, , Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi	DS-2CD2020F-I
	IRR 17,580,000	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	DS-2CD2042WD-I
	IRR 16,210,000	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS 2560 x 1440@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR 2 Behavior analyses, and face detection - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	DS-2CD2043G0-I
	IRR 22,700,000	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	DS-2CD2052-I
	IRR 19,460,000	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	DS-2CD2063G0-I
	IRR 22,870,000	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS 3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - BLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	DS-2CD2083G0-I
21 Series			
	IRR 12,630,000	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	DS-2CD2120F-I
	IRR 10,600,000	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	DS-2CD2120F-IS
	ناموجود	Up to 4 megapixel high resolution, Dual stream, 2.8mm/4mm/6mm fixed lens, 120dB Wide Dynamic Range, 3D Digital Noise Reduction, DC12V & PoE, Support H.264+, Up to 30m IR range, IP67 weather-proof protection, -S: Audio/Alarm IO	DS-2CD2142FWD-I
	IRR 19,290,000	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB (SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	DS-2CD2142FWD-IS

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:


















www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com

11	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera 1/3" Progressive Scan CMOS, 2688 × 1520@30fps, 2.8/4/6/8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67, IK10, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB, 3-Axis adjustment	IRR 17,750,000	
12	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 23,890,000	
13	DS-2CD2163G0-I(S)	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 21,160,000	
14	DS-2CD2183G0-I(S)	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 1/2.5" Progressive Scan CMOS 3840 × 2160 @ 15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR	IRR 24,920,000	
23 Series				
15	DS-2CD2322WD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6/8/12mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	ناموجود	
16	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 20,820,000	
17	DS-2CD2352-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 25,330,000	
4MG				
18	DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264, IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 13,310,000	
19	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens, PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 14,000,000	
20	DS-2CD1643G0-IZ	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS BLC/3D DNR/ROI, 2560 × 1440@20fps, Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens, IP67, H.265+, H.265, H.264+, H.264 120 dB WDR, Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 23,890,000	
21	DS-2CD1743G0-IZ	4.0 MP VF Network Bullet Camera, 1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens, PoE (Power over Ethernet), IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB WDR (Wide Dynamic Range)	IRR 23,890,000	
24 Series				
22	DS-2CD2420F-IW	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	IRR 12,630,000	
23	DS-2CD2442FWD-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB(SD card not included), built-in WIFI	IRR 14,610,000	
25 Series				
24	DS-2CD2520F	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution, Standard video compression with high compression ratio, Progressive scan CMOS, PoE (Power over Ethernet), Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB, 3D Digital Noise Reduction	IRR 10,040,000	
25	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service -S: Built-in MIC, audio/alarm IO	IRR 19,210,000	
26 Series				
26	DS-2CD2620F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -Z: Motorized VF lens	IRR 21,840,000	
27	DS-2CD2620F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -Z: Motorized VF lens	ناموجود	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:


















www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com

28	DS-2CD2622FWD-IS	1/2.8" Progressive CMOS, ICR, 0.01lux/F1.2, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service -S: Audio/alarm IO	ناموجود	
29	DS-2CD2642FWD-IS	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service -S: Audio/alarm IO	ناموجود	
30	DS-2CD2642FWD-IZS	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service -S: Audio/alarm IO -Z: Motorized VF lens	ناموجود	
31	DS-2CD2652F-IS	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), HIK-Connect cloud service -S: Audio/alarm IO	IRR 34,660,000	
27 Series				
32	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 24,596,000	
33	DS-2CD2720F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	IRR 25,890,000	
34	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P -Z: Motorized VF lens	IRR 21,930,000	
35	DS-2CD2722FWD-IS	1/2.8" Progressive Scan CMOS, Up to 2 megapixel resolution, 120dB WDR, 3D DNR, Up to 30 meters IR range, Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB, Audio/alarm I/O (-S), Mobile Monitoring via cloud P2P or iVMS-4500,	IRR 26,000,000	
36	DS-2CD2742FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO	IRR 34,810,000	
37	DS-2CD2742FWD-IZS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO -Z: Motorized VF lens	ناموجود	
38	DS-2CD2752F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO	ناموجود	
39	DS-2CD2752F-IZS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 2.8~12mm VF lens, IP67, H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), Vandal-proof housing, HIK-Connect cloud service -S: Audio/alarm IO -Z: Motorized VF lens	IRR 39,530,000	
29 Series				
40	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 x 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 56,800,000	
2T Series				
41	DS-2CD2T22WD-IZ	1/2.8" Progressive Scan CMOS. Up to 2 megapixel resolution. Full HD1080p real-time video. 120dB Wide Dynamic Range. 3D DNR. EXIR high performance LED. Up to 30/50/80 meters IR range. 12V DC±25% & PoE(802.3af Class3). Support H.264+. IP67	IRR 12,860,000	
42	DS-2CD2T42WD-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I3: 1pcs EXIR LED, up to 30m IR range	ناموجود	
43	DS-2CD2T42WD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I5: 2pcs EXIR LEDs, up to 50m IR range	ناموجود	
44	DS-2CD2T42WD-I8	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I8: 4pcs EXIR LEDs, up to 80m IR range	IRR 22,700,000	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:
















www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com

45	DS-2CD2T43G0-I5	1/3" Progressive Scan CMOS, 2688 × 1520 @ 30fps, 2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 18,940,000	
46	DS-2CD2T52-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range	IRR 24,920,000	
47	DS-2CD2T63G0-I5	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR	IRR 22,190,000	
48	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - up to 80m IR range	IRR 23,550,000	
49	DS-2CD2T83G0-I5	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR . BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 G	IRR 26,620,000	
50	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR . BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 27,990,000	
2F Series				
51	DS-2CD2F52F-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 2048×1536: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 23,220,000	
2D Series				
52	DS-2CD2D14WD	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	IRR 15,450,000	
2E Series				
53	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional (Black, Silver, Golden) -W: Built-in Wi-Fi	IRR 13,420,000	
2Q Series				
54	DS-2CD2Q10FD-IW	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection, Support Mobile Monitoring via EZVIZ P2P	IRR 12,710,000	
55	DS-2CV2Q21FD-IW/32GB-T	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. Default: No SD card included. /32GB-T: Include 16GB sd card.	IRR 16,050,000	
2U Series				
56	DS-2CV2U21FD-IW/32GB-T	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Built-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. /32GB-T: Include 32GB sd card.	IRR 12,630,000	
IP PTZ Camera				
2" IR PTZ				
57	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 × 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	IRR 85,020,000	
58	DS-2CD2202I-DE3	2 MP High Resolution, Compact IR Pan/Tilt/Zoom Camera, 1920 x 1080p HD Real-Time Resolution, 2x Zoom, 16x Digital Zoom, 20 Meters IR Distance, PoE and 12 VDC Power Supply, Built-In Mic, WiFi, MicroSD Card Local Storage, Up to 128 GB, Easy To Install and Adjust	IRR 22,900,000	
4" IR PTZ				
59	DS-2DE4220IW-DE	2MP, 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	IRR 67,510,000	
5" IR PTZ				

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:


















www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com

60	DS-2DE5220IW-AE	H.265+/H.265/H.264+/H.264; 2MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 112,260,000	
5" PTZ				
61	DS-2DE5230W-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	IRR 116,970,000	
7" IR PTZ				
62	DS-2DE7220IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 117,750,000	
63	DS-2DE7230IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 136,200,000	
64	DS-2DE7330IW-AE	1/2.8" Progressive Scan CMOS 2048 × 1536@30fps Resolution 30× optical zoom, 16× digital zoom WDR 3D Positioning 24VAC & Hi-PoE Up to 150m IR distance	IRR 159,750,000	
65	DS-2DE7530IW-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 203,320,000	
66	DS-2DE7430IW-AE	1/1.9" progressive scan CMOS, Up to 2560 × 1440 resolution, 30× Optical Zoom, 16× Digital Zoom, Defog, EIS, 3D DNR, BLC, HLC, Digital WDR, IR distance up to 150 m, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression	IRR 186,830,000	
67	DS-2DE7420IW-AE	1/1.9" progressive scan CMOS, Up to 2560 × 1440 resolution, 20× Optical Zoom, 16× Digital Zoom, Defog, EIS, 3D DNR, BLC, HLC, Digital WDR, IR distance up to 150 m, 24 VAC & Hi-PoE, Support H.265+/H.265 video compression	IRR 163,280,000	
68	DS-2DE7320IW-AE	1/2.8" Progressive Scan CMOS ,2048 × 1536@30fps Resolution, 20× optical zoom, 16× digital zoom ,WDR ,3D Positioning ,24VAC & Hi-PoE, Up to 150m IR distance	IRR 134,240,000	
PanoVu Mini Series IR Network PTZ Camera				
69	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera: 1/2.8" progressive scan CMOS, 3-ch 1920 × 1080@30fps resolution, Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° × 3 PTZ Camera: 1/2.8" progressive scan CMOS, Up to 1920 × 1080@30fps resolution, Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression, 4× optical zoom, 8× digital zoom	IRR 70,000,000	
NVR				
70	DS-7600NI-E1/A	Advertising files import and preview, The output resolution of LCD is up to 1080P, Third party network cameras supported, Up to 8-ch synchronous playback at 720P resolution, Up to 8 network cameras can be connected, Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 62,900,000	
71	DS-7604NI-E1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 12,390,000	
72	DS-7604NI-E1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 20,170,000	
73	DS-7604NI-Q1	IP video input 4-ch, Up to 8 MP resolution, Incoming bandwidth 40 Mbps, Outgoing bandwidth 80 Mbps, Audio output 1-ch, Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	IRR 14,860,000	
74	DS-7604NI-Q1/4P	IP video input 4-ch, Up to 8 MP resolution, Incoming bandwidth 40 Mbps, Outgoing bandwidth 80 Mbps, Audio output 1-ch, Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk, 4 independent PoE network interfaces	IRR 20,170,000	
75	DS-7604NI-K1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	ناموجود	
76	DS-7604NI-K1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 20,170,000	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:






















www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com

77	DS-7608NI-Q1	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	IRR 20,000,000	
78	DS-7608NI-Q1/4P	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,8 independent PoE network interfaces	IRR 32,000,000	
79	DS-7608NI-E2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case	IRR 17,340,000	
80	DS-7608NI-E2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	ناموجود	
81	DS-7608NI-K2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 212,300,000	
82	DS-7608NI-K2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	ناموجود	
83	DS-7616NI-E2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	IRR 19,110,000	
84	DS-7616NI-Q1	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 1 SATA interfaces ,Two-way audio 1-ch	IRR 21,000,000	
85	DS-7616NI-Q2/16P	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 2 SATA interfaces ,Two-way audio 1-ch, 16 independent PoE network interfaces	IRR 44,220,000	
86	DS-7616NI-E2/8P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	ناموجود	
87	DS-7616NI-E2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	ناموجود	
88	DS-7616NI-K2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	ناموجود	
89	DS-7616NI-K2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 44,220,000	
90	DS-7716NI-E4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 37,500,000	
91	DS-7716NI-E4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	
92	DS-7716NI-K4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 46,350,000	
93	DS-7716NI-K4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	
94	DS-7732NI-K4	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	
95	DS-7732NI-K4/16P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 77,120,000	
96	DS-7732NI-E4	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 49,180,000	
97	DS-7732NI-E4/16P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	ناموجود	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:



www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com

98	DS-7104NI-E1/M	4-ch, 1-ch, RCA (2.0 Vp-p, 1kΩ) ,40 Mbps,4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF /DCIF/2CIF/CIF/QCIF ,Main stream: 50 fps (P)/60 fps (N), sub-stream: 50 fps (P)/60 fps (N)	IRR 10,580,000	
99	DS-7108NI-E1/M	4-ch, 1-ch, RCA (2.0 Vp-p, 1kΩ) ,40 Mbps,4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF /DCIF/2CIF/CIF/QCIF ,Main stream: 50 fps (P)/60 fps (N), sub-stream: 50 fps (P)/60 fps (N)	ناموجود	

کلیه محصولات شامل گارانتی 24 ماهه پارس ارتباط می باشند



آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران
شماره های تماس شرکت:

02188398741 02188398742 02188397455 02188397460

کانال های رسمی شرکت در تلگرام:

www.t.me/Tehranhikvision

www.t.me/HIKVISIONMARKAZI

www.t.me/IRANCCTVSHOP

وبسایت شرکت:

www.atineh.com www.shop.atineh.com