









Network Camera - NVR



Items	Description	User Price	
<b>Lite Mini Bullet Series</b>			
1	<b>DS-2CD1023G0-E</b> 2.0 MP IR Network Bullet Camera-1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 1920 x 1080@30fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67 Dual stream Digital WDR (Wide Dynamic Range)	<b>IRR 8,438,800</b>	
2	<b>DS-2CD1023G0-I</b> 2.0 MP IR Network Bullet Camera-1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 1920 x 1080@30fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67 Dual stream Digital WDR (Wide Dynamic Range)	<b>IRR 8,744,800</b>	
3	<b>DS-2CD1031-I</b> 1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8mm/4mm/6mm fixed focal lens Up to 30 m IR range- Dual stream- Digital WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction)- PoE (Power over Ethernet)- IP67 Mobile monitoring via Hik-Connect or iVMS-4500	<b>IRR 10,530,000</b>	
4	<b>DS-2CD1043G0-I</b> 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264, IP67, Dual stream, Digital WDR (Wide Dynamic Range)	<b>IRR 11,961,200</b>	
<b>Lite Dome Series</b>			
6	<b>DS-2CD1123G0-I</b> IP67, 2MP dome Exir, fixed lens 2.8mm, white color-1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 1920 x 1080@30fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67, IK10 Dual stream Digital WDR (Wide Dynamic Range)	<b>IRR 13,760,000</b>	
7	<b>DS-2CD1323G0-E</b> 1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	<b>IRR 8,438,800</b>	
8	<b>DS-2CD1323G0-I</b> 1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	<b>IRR 9,200,400</b>	
9	<b>DS-2CD1131-I</b> 1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8 mm/4 mm/6 mm fixed focal lens Up to 30 m IR range- Dual stream- Digital WDR (Wide Dynamic Range)- 3D DNR (Digital Noise Reduction)- PoE (Power over Ethernet) IP67, IK10- Mobile monitoring via Hik-Connect or iVMS-4500	<b>IRR 10,530,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)











[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

10	<b>DS-2CD1143G0-I</b>	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 3 streams, Digital WDR (Wide Dynamic Range)	<b>IRR 18,490,000</b>	
11	<b>Mini Bullet Series</b>			
12	<b>DS-2CD2020F-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE cable, , Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi	<b>IRR 16,690,000</b>	
13	<b>DS-2CD2023G0-I</b>	2 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS 1920 × 1080@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 3 streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67 3-Axis adjustment Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 13,900,000</b>	
14	<b>DS-2CD2043G0-I</b>	4 MP IR Fixed Bullet Network Camera - 1/3" Progressive Scan CMOS 2560 × 1440@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 3 streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67 3-Axis adjustment Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 15,100,000</b>	
15	<b>DS-2CD2052-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	<b>IRR 15,723,500</b>	
16	<b>DS-2CD2063G0-I</b>	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 17,225,700</b>	
17	<b>DS-2CD2083G0-I</b>	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR BLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 20,247,400</b>	
18	<b>Dome Series</b>			
19	<b>DS-2CD2120F-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	<b>IRR 16,690,000</b>	
20	<b>DS-2CD2120F-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	<b>IRR 16,690,000</b>	
21	<b>DS-2CD2123G0-IS</b>	2 MP IR Fixed Dome Network Camera - 1/2.8" Progressive Scan CMOS • 1920 × 1080@30fps • 2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • Three streams • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI/HLC • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB  • 3-Axis adjustment	<b>IRR 21,650,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)

[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

22	<b>DS-2CD2143G0-IS</b>	4 MP IR Fixed Dome Network Camera 1/3" Progressive Scan CMOS, 2688 ×1520@30fps, 2.8/4/6/8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67, IK10, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB, 3-Axis adjustment	<b>IRR 23,450,000</b>	
23	<b>DS-2CD2152F-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	<b>IRR 16,549,000</b>	
24	<b>DS-2CD2163G0-I(S)</b>	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	<b>IRR 27,960,000</b>	
25	<b>DS-2CD2183G0-I(S)</b>	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR	<b>IRR 22,056,400</b>	
26	<b>Bullet Series</b>			
27	<b>DS-2CD2T35FWD-I8</b>	Up to 3 megapixel high resolution-Max. 2048 × 1536 @30fps 2.8 mm/4mm/6mm/8 mm/12mm fixed lens,-optional Ultra-low light-265, H.265+, H.264+, H.264- 120dB Wide Dynamic Range 3D Digital Noise Reduction 12 VDC & PoE (802.3af)- IR range: 50m, 80m, optional- Support on-board storage, up to 128 GB-IP67	<b>IRR 20,500,000</b>	
28	<b>DS-2CD2T43G0-I5</b>	1/3" Progressive Scan CMOS, 2688 ×1520@30fps, 2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	<b>IRR 24,360,000</b>	
29	<b>DS-2CD2T52-I5</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range	<b>IRR 32,920,000</b>	
30	<b>DS-2CD2T63G0-I5</b>	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR	<b>IRR 29,320,000</b>	
31	<b>DS-2CD2T63G0-I8</b>	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - up to 80m IR range	<b>IRR 31,120,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)











[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

32	<b>DS-2CD2T83G0-IS</b>	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens ÷ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR ÷ H.265+, H.265, H.264+, H.264 ÷ 2 Behavior analyses ÷ 120dB WDR . ÷ BLC/3D DNR/ROI ÷ IP67 ÷ Built-in micro SD/SDHC/SDXC card slot, up to 128 G	<b>IRR 35,180,000</b>	
33	<b>DS-2CD2T83G0-I8</b>	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens ÷ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR ÷ H.265+, H.265, H.264+, H.264 ÷ 2 Behavior analyses ÷ 120dB WDR . ÷ BLC/3D DNR/ROI ÷ IP67 ÷ Built-in micro SD/SDHC/SDXC card slot, up to 128 G- up to 80m IR range	<b>IRR 36,980,000</b>	
34	<b>Exir Dome Series</b>			
35	<b>DS-2CD2342FWD-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	<b>IRR 22,190,000</b>	
36	<b>DS-2CD2352-I</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	<b>IRR 33,150,000</b>	
37	<b>Mini Dome Series</b>			
38	<b>DS-2CD2523G0-IS</b>	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	<b>IRR 18,557,200</b>	
39	<b>DS-2CD2542FWD-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service -S: Built-in MIC, audio/alarm IO	<b>IRR 20,644,495</b>	
40	<b>DS-2CD2543G0-IS</b>	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 × 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	<b>IRR 21,460,495</b>	
41	<b>DS-2CD2563G0-IS</b>	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 × 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	<b>IRR 23,922,400</b>	
42	<b>Lite Bullet Vari-Facal Motorized Series</b>			
43	<b>DS-2CD1623G0-I</b>	Hikvision DS-2CD1623G0-I 2MP (1920 × 1080) Vari-focal IR Bullet Network Camera SPECIFICATIONS2MP HD1080P 1/2.8" Progressive Scan CMOS1920 × 1080@30fps (N)2.8~12mm VF lens IR range: Up to 30m	<b>IRR 17,788,800</b>	
44	<b>DS-2CD1623G0-IZ</b>	S-2CD1623G0-IZ Bullet Network camera 2MP, 2.8-12mm varifocal lens, EXIR, microSD1/2.8" progressive scan CMOSBLC/3D DNR/ROI1920 × 1080@30fps Up to 30 m IR rangelP672.8 mm to 12 mm varifocal lensDigital WDRH.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 LuxBuilt-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens	<b>IRR 19,644,400</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)











[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

45	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS ȳ BLC/3D DNR/ROI, 2560  imes 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens, IP67, H.265+, H.265, H.264+, H.264 ȳ 120 dB WDR, Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 31,570,000	
46	<b>Lite Dome Vari-Facal Series</b>			
47	DS-2CD1723G0-I	ȳ 1/2.8" progressive scan CMOS ȳ 3D DNR (Digital Noise Reduction) ȳ 1920  imes 1080@30fps ȳ Up to 30 m IR range ȳ 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens ȳ PoE (Power over Ethernet) ȳ IP67, IK10 ȳ H.265+, H.265, H.264+, H.264 ȳ Dual stream ȳ Digital WDR (Wide Dynamic Range)	IRR 17,788,800	
48	DS-2CD1743G0-I	4.0 MP VF Network Bullet Camera, 1/3" progressive scan CMOS ȳ 3D DNR (Digital Noise Reduction), 2560  imes 1440@20fps ȳ Up to 30 m IR range, 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens, PoE (Power over Ethernet), IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB WDR (Wide Dynamic Range)	IRR 19,325,600	
49	<b>Bullet Vari-Facal Motorized Series</b>			
50	DS-2CD2620F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 28,870,000	
51	DS-2CD2643G0-IZS	<b>4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS</b> <ul style="list-style-type: none"> <li>• 2688  imes 1520@30fps</li> <li>• 2.8 to 12 mm varifocal lens</li> <li>• Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I</li> <li>• H.265+, H.265, H.264+, H.264</li> <li>• Three streams</li> <li>• 120dB WDR</li> <li>• 2 Behavior analyses, and face detection</li> <li>• BLC/3D DNR/ROI</li> <li>• IP67, IK10</li> <li>• Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</li> </ul> <b>- Z: Motorized VF lens</b>	IRR 47,360,000	
52	DS-2CD2663FG0-IZS	ȳ BLC/3D DNR/ROI ȳ IP67, IK10 ȳ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB ȳ ȳ 1/2.9" Progressive Scan CMOS ȳ 3072  imes 2048@20 fps ȳ 2.8 to 12 mm varifocal lens ȳ Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR ȳ H.265+, H.265, H.264+, H.264 ȳ 2 Behavior analyses - <b>Z: Motorized VF lens</b>	IRR 54,570,000	
53	DS-2CD2683G0-IZS	<b>8 MP(4K) IR Vari-focal Bullet Network Camera</b> • 1/2.5" Progressive Scan CMOS <ul style="list-style-type: none"> <li>• 3840  imes 2160@15fps</li> <li>• 2.8 to 12 mm varifocal lens</li> <li>• Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR</li> <li>• H.265+, H.265, H.264+, H.264</li> <li>• 120dB WDR</li> <li>• 2 Behavior analyses, and face detection</li> <li>• BLC/3D DNR/ROI</li> <li>• IP67, IK10</li> </ul> <b>- Z: Motorized VF lens</b>	IRR 63,140,000	
54	<b>Dome Vari-Facal Motorized Series</b>			
55	DS-2CD2720F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 16,250,000	
56	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - <b>Z: Motorized VF lens</b>	IRR 37,430,000	
57	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8 " 2MP progressive scan CMOS Up to 1920  imes 1080 resolution (25 fps) 2.8~12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA, Micro SD (Up to 128 GB), Reset Button 1 Audio I/O , 1 Alarm I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support - <b>Z: Motorized VF lens</b>	IRR 42,850,000	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)










[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

58	<b>DS-2CD2743G0-IZS</b>	4 MP IR VF Dome Network Camera - 1/3" Progressive Scan CMOS • 2560 × 1440@30fps • 2.8 to 12 mm Varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+ • Three streams • 120dB WDR • 2 behavior analyses, and face detection -WDR-Day & Night IR Cut Filter Digital Noise Reduction 3D DNR - <b>Z: Motorized VF lens</b>	<b>IRR 42,850,000</b>	
59	<b>DS-2CD2763G0-IZS</b>	6 MP IR Vari-focal Dome Network Camera • 1/2.9" Progressive Scan CMOS • 3072 × 2048@20fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Z: Motorized VF lens</b>	<b>IRR 54,570,000</b>	
60	<b>DS-2CD2783G0-IZS</b>	8 MP(4K) IR Vari-focal Dome Network Camera • 1/2.5" Progressive Scan CMOS • 3840 × 2160@15fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Z: Motorized VF lens</b>	<b>IRR 63,140,000</b>	
61	<b>Fish Eye Series</b>			
62	<b>DS-2CD2942F-IS</b>	Color: 0.01lux @(F1.2, AGC ON), 0.018lux @(F1.6, AGC ON), 0 lux with IR 2560 × 1440 1.6mm, F1.6 Angle of view: 186°(horizontal), 106°(vertical) H.264/MJPEG 50Hz: 12.5fps(2560 × 1440), 25fps(1920 × 1080, 1280 × 720) 60Hz: 15fps(2560 × 1440), 30fps(1920 × 1080, 1280 × 720) 8 meters 12 VDC ± 10%, PoE (802.3af)	ناموجود	
63	<b>DS-2CD2955FWD-IS</b>	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	<b>IRR 42,848,000</b>	
64	<b>Cube Smart Series</b>			
65	<b>DS-2CD2420F-IW</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	<b>IRR 16,690,000</b>	
66	<b>DS-2CD2423G0-IW</b>	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - <b>PIR: 10m</b> - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR	<b>IRR 12,267,200</b>	
67	<b>DS-2CD2442FWD-IW</b>	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB(SD card not included), built-in WIFI	<b>IRR 23,000,000</b>	
68	<b>Pin Hole Series</b>			
69	<b>DS-2CD2D14WD</b>	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	<b>IRR 17,250,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)










[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

70	<b>Hologen Series</b>			
71	<b>DS-2CD2E20F-W</b>	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional (Black, Silver, Golden) -W: Built-in Wi-Fi	<b>IRR 24,580,000</b>	
72	<b>2Q Smart Series</b>			
73	<b>DS-2CD2Q10FD-IW</b>	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection, Support Mobile Monitoring via EZVIZ P2P	<b>IRR 13,230,000</b>	
74	<b>DS-2CV2Q21FD-IW</b>	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. Default: No SD card included. /32GB-T: Include 16GB sd card.	<b>IRR 19,170,000</b>	
75	<b>2U Smart Series</b>			
76	<b>DS-2CV2U21FD-IW</b>	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. /32GB-T: Include 32GB sd card.	<b>IRR 9,204,000</b>	
77	<b>Mini PTZ Series</b>			
78	<b>DS-2CD2F52F-IS</b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 2048x1536: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB (SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	<b>IRR 24,710,000</b>	
79	<b>IP PTZ Camera</b>			
80	<b>DS-2DE4A220IW-DE</b>	1/2.8" Progressive Scan CMOS, Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	<b>IRR 69,447,000</b>	
81	<b>DS-2CD2202I-DE3</b>	2 MP High Resolution, Compact IR Pan/Tilt/Zoom Camera, 1920 x 1080p HD Real-Time Resolution, 2x Zoom, 16x Digital Zoom, 20 Meters IR Distance, PoE and 12 VDC Power Supply, Built-In Mic, WiFi, MicroSD Card Local Storage, Up to 128 GB, Easy To Install and Adjust	<b>IRR 26,400,000</b>	
82	<b>DS-2DE4220IW-DE</b>	2MP, 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W: 0.02lux/F1.5, Optical Zoom: 20x, Focus: 4.7-94.0mm, Digital Zoom: 16X, Pan range: 360° endless; Tilt range: -15°~90° (Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	<b>IRR 77,570,000</b>	
83	<b>DS-2DE4225IW-DE</b>	1/2.8" progressive scan CMOS Up to 1920 x 1080@30fps resolution - Min. illumination: Color: 0.005 Lux @ (F1.6, AGC ON) B/W: 0.001 Lux @ (F1.6, AGC ON) 0 Lux with IR 25x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus Up to 100 m IR distance 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression	<b>IRR 56,511,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)











[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

84	DS-2DE5220IW-AE	2MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 90,286,000	
85	DS-2DE5230W-AE	1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	IRR 134,390,000	
86	DS-2DE7220IW-AE	2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
87	DS-2DE7230IW-AE	2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
88	DS-2DE7320IW-AE	1/2.8" Progressive Scan CMOS 2048 × 1536@30fps Resolution 20× optical zoom, 16× digital zoom 3D Positioning 24VAC & Hi-PoE Up to 150m IR distance	IRR 107,961,000	
89	DS-2DE7330IW-AE	1/2.8" Progressive Scan CMOS 2048 × 1536@30fps Resolution 30× optical zoom, 16× digital zoom 3D Positioning 24VAC & Hi-PoE Up to 150m IR distance	ناموجود	
90	DS-2DE7420IW-AE	1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,20× Optical Zoom, 16× Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
91	DS-2DE7430IW-AE	1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,30× Optical Zoom, 16× Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	IRR 205,190,000	
92	DS-2DE7530IW-AE	1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
93	<b>PanoVu Mini Series IR Network PTZ Camera</b>			
94	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 × 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° × 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 × 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4× optical zoom, 8× digital zoom	IRR 71,960,000	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)

[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)












[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)



95	<b>NVR-Monitor</b>			
96	<b>DS-7600NI-E1/A</b>	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	<b>IRR 69,190,000</b>	
97	<b>NVR 4 Channel</b>			
98	<b>DS-7104NI-Q1/M</b>	Incoming bandwidth: 40Mbps - P video input: 4-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	<b>IRR 7,282,800</b>	
99	<b>DS-7104NI-Q1/4P/M</b>	Incoming bandwidth: 40Mbps - P video input: 4-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	<b>IRR 12,390,000</b>	
100	<b>DS-7604NI-E1</b>	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	<b>IRR 14,670,000</b>	
101	<b>DS-7604NI-E1/4P</b>	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	<b>IRR 20,980,000</b>	
102	<b>DS-7604NI-Q1</b>	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	<b>IRR 11,220,000</b>	
103	<b>DS-7604NI-Q1/4P</b>	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk, 4 independent PoE network interfaces	<b>IRR 23,000,000</b>	
104	<b>DS-7604NI-K1</b>	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	<b>IRR 16,500,000</b>	
105	<b>DS-7604NI-K1/4P</b>	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	<b>IRR 23,000,000</b>	
106	<b>NVR 8 Channel</b>			
107	<b>DS-7108NI-Q1/M</b>	Incoming bandwidth: 60Mbps - P video input: 8-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	<b>IRR 9,128,000</b>	
108	<b>DS-7108NI-Q1/8P/M</b>	Incoming bandwidth: 60Mbps - P video input: 8-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	<b>IRR 17,444,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)














[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

109	<b>DS-7608NI-E2</b>	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, <b>380 1U case</b>	<b>IRR 20,540,000</b>	
110	<b>DS-7608NI-E2/8P</b>	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, <b>380 1U case</b>	<b>IRR 33,132,000</b>	
111	<b>DS-7608NI-Q1</b>	IP video input 8-ch, Up to 8 MP resolution, Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch, Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	<b>IRR 22,850,000</b>	
112	<b>DS-7608NI-Q1/8P</b>	IP video input 8-ch, Up to 8 MP resolution, Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch, Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk, 8 independent PoE network interfaces	<b>IRR 37,065,000</b>	
113	<b>DS-7608NI-Q2</b>	sales, [05.01.19 11:19] IP video input 8-ch, Up to 8 MP resolution, Incoming bandwidth: 80 Mbps, Outgoing bandwidth: 80 Mbps, 2 SATA interfaces, Two-way audio	<b>IRR 25,180,000</b>	
114	<b>DS-7608NI-K2</b>	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	<b>IRR 25,180,000</b>	
115	<b>DS-7608NI-K2/8P</b>	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	<b>IRR 39,820,000</b>	
116	<b>NVR 16 Channel</b>			
117	<b>DS-7616NI-E2</b>	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, <b>380 1U case</b>	<b>IRR 22,630,000</b>	
118	<b>DS-7616NI-E2/8P</b>	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, <b>380 1U case</b>	<b>IRR 34,742,000</b>	
119	<b>DS-7616NI-E2/16P</b>	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, <b>380 1U case</b>	<b>IRR 46,490,000</b>	
120	<b>DS-7616NI-Q1</b>	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 1 SATA interfaces , Two-way audio 1-ch	<b>IRR 23,760,000</b>	
121	<b>DS-7616NI-Q2/16P</b>	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 2 SATA interfaces , Two-way audio 1-ch, 16 independent PoE network interfaces	<b>IRR 52,800,000</b>	
122	<b>DS-7616NI-K2</b>	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	<b>IRR 27,240,000</b>	

آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران

شماره های تماس: 02188398741 - 02188398742

کانال های تلگرام شرکت

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)








[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

وب سایت شرکت

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)

123	<b>DS-7616NI-K2/16P</b>	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	<b>IRR 52,800,000</b>	
124	<b>DS-7716NI-E4</b>	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 34,552,000</b>	
125	<b>DS-7716NI-E4/16P</b>	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 51,856,000</b>	
126	<b>DS-7716NI-K4</b>	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 42,700,000</b>	
127	<b>DS-7716NI-K4/16P</b>	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 58,443,000</b>	
128	<b>NVR 32 Channel</b>			
129	<b>DS-7732NI-E4</b>	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 45,311,000</b>	
130	<b>DS-7732NI-E4/16P</b>	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 88,479,000</b>	
131	<b>DS-7732NI-K4</b>	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 53,781,000</b>	
132	<b>DS-7732NI-K4/16P</b>	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	<b>IRR 68,411,000</b>	

**آتی نگر الکترونیک نماینده رسمی فروش محصولات هایک ویژن در ایران**

**شماره های تماس: 02188398741 - 02188398742**

**کانال های تلگرام شرکت**

[www.t.me/HIKVISIONMARKAZI](http://www.t.me/HIKVISIONMARKAZI)

[www.t.me/IRANCCTVSHOP](http://www.t.me/IRANCCTVSHOP)

[www.t.me/Tehranhikvision](http://www.t.me/Tehranhikvision)

**وب سایت شرکت**

[www.atineh.com](http://www.atineh.com)

[www.shop.atineh.com](http://www.shop.atineh.com)